HP LaserJet 1160 Printer





Rely on the high-quality, personal HP LaserJet 1160 Printer – producing professional-looking, black-and-white documents at fast print speeds with easy compatibility – all at an affordable price.

| | - | |
|---|--------|--|
| | | |
| _ | - Life | |
| | | |

HP LaserJet 1160 Printer

HP LaserJet 1160 Printer is ideal for business professionals in any size office seeking an affordable personal printer combining value, fast print speeds and compatibility for their black-and-white business documents.

Powerful performance at an affordable price.

- Enjoy the dependable, high-quality output you expect from HP, combined with the performance you need all at an affordable price.
- This compact 350 x 352 x 256 mm printer features a 133 MHz Motorola Coldfire processor and 16 MB memory to maximise throughout. Print office documents of almost any length with a 250-sheet input tray, single-sheet priority input tray and 125-sheet output tray.
- Print in Economode and save up to 50% of your toner.

Print professional-looking documents quickly.

- Get professional-looking documents with the HP LaserJet 1160 Printer, featuring print quality of up to 1200 dpi (optical 600 x 600 dpi using Resolution Enhancement technology (REt) and FastRes 1200).
- Boost office productivity with instant-on fuser technology requiring no warm-up from hot or cold start plus an 8.5 second first-page-out time and print speeds of up to 19 ppm A4 that ensure your print job is finished before many printers have even started printing.

Fits your office environment.

- The highly reliable HP LaserJet 1160 Printer fits easily into your office with support for multiple operating systems including Microsoft[®] Windows[®], Mac, optional Netware, Linux[®] and HP-UX, and more.
- Enjoy simple connectivity via USB and parallel ports, and add network capabilities with an optional HP Jetdirect External Print Server.
- Operate and manage your printer effortlessly with a simplified control panel and integrated HP Toolbox or HP Web Jetadmin Software.



Technical specifications

| lechnical specification | 15 | U | |
|---------------------------------|---|-----|--|
| Print technology | Monochrome Laser | Q59 | |
| Print speed | Up to 19 ppm (A4) First page out: 8.5 seconds Due to instant-on fuser technology (no warm-up time from warm or cold start) | | |
| Processor | 133 MHz, Motorola V4 Coldfire | | |
| Memory | 16 MB, not expandable, Memory Enhancement technology (MEt) | | |
| Print quality | 1200 dpi effective output (optical 600 x 600 dpi with HP Resolution Enhancement REt and FastRes) | | |
| Printer languages | HP PCL 5e | C65 | |
| Economical printing | Economode (saves up to 50% toner), immediate return to power-save mode after each print job due to instant-on fuser technology (saves electricity), N-up printing and manual duplex (saves paper) | | |
| Typefaces/fonts | 26 scalable fonts built in | | |
| Duty cycle | Up to 10,000 pages per month | C29 | |
| Print margins | A4: top: 4 mm, left: 4 mm, right: 4 mm, bottom: 4 mm | | |
| Media handling | Input: Capacity Weight Size Priority Tray 1 sheet 60 to 105 g/m² using the standard output bin of to 103 g/m² using the standard output bin media path A4, A5, A6, B5, B6 envelopes, (C5, DL), 76 x127 mm to 216 x 356 mm Standard Tray Up to 250 sheets, 30 envelopes 60 to 105 g/m² A4, A5, A6, B5, B6 envelopes, (C5, DL), 76 x127 mm to 216 x 356 mm Output: Sheets: up to 125, envelopes: 1, transparencies: 100 147 x 211 mm to 216 x 356 mm | Q5 | |
| Media types | Duplex printing: Manual (driver support provided) Plain paper, envelopes, transparencies, cardstock, postcards, labels | J32 | |
| Paper handling | Single-sheet priority input tray, 250-sheet input tray | J60 | |
| Interface and connectivity | Standard: Full-speed USB port (compatible with USB 2.0 specifications), IEEE 1284-B compliant parallel port Optional: HP Jetdirect External Print Servers; HP Wireless Print Servers; Bluetooth® Wireless Printer Adapter | | |
| Operating systems compatibility | Microsoff® Windows® 98, Me, NT 4.0 (printer driver only), 2000, XP 32-bit, XP 64-bit (printer driver only), Server 2003, Mac OS 9, OS X v 10.1, 10.2, 10.3, MS-DOS, Linux, UNIX® Latest drivers and software available from the HP LaserJet support Website: http://www.hp.com/support/lj1160/ | | |
| Network operating systems | Via HP Jedired Print Server: Microsoft [®] Windows [®] 98, Me, 2000, XP, NT 4.0 (print driver only), Microsoft Windows XP 32-bit, XP 64-bit (print driver only), Server 2003, Mac OS 9, OS X v 10.1, 10.2, 10.3; optional: Novell [®] NetWare 3.2, 4.2, 5.x, 6; Red Hat Linux [®] 6.x and later; SuSE Linux 6.x and later; HPUX 10.20, 11.x; Solaris [®] 2.5x, 2.6, 7, 8; IBM [®] AIX 3.2.5 and later; MPE-iX | | |
| Minimum system requirements | Microsoft Windows [®] 98 and later, Pentium [®] , 166 MHz, 64 MB RAM Mac OS 9.1 and later, 96 MB RAM; Mac OS X v 10.1 and later: 128 MB RAM, CD-ROM drive | | |
| Standard software | HP printer software on CD-ROM includes HP installer/uninstaller, drivers, HP Toolbox for diagnostic status and configuration, control panel simulator, help, documentation | | |
| Control panel | Comprised of 3 lights and 2 buttons (Go and Cancel); these lights produce patterns that identify the printer's status (Toner, Attention, Ready) | | |
| Power requirements | Input voltage 110 to 127 VAC (± 10 %), 50/60 Hz (± 2 Hz); 220 to 240 VAC (±10 %), 50/60 Hz (± 2 Hz). Internal | | |
| Power consumption | 0 watts (off), 6 watts maximum (powersave/standby), 345 watts maximum (printing) | | |
| Dimensions (w x d x h) | Out of package: 350 x 355 x 256 mm, packaged: 500 x 400 x 498 mm | H5 | |
| Weight | Out of package: 10.5 kg, packaged: 14.06 kg | 110 | |
| Printer management | HP Toolbox, HP Web Jetadmin | H5 | |
| Operating environment | Environmental ranges: Operating temperature: 10 to 32.5° C, recommended operating temperature: 10 to 32.5° C, operating humidity: 20 to 80% RH, (non-condensing), storage temperature: 0 to 40° C, storage humidity: 10 to 80% RH. Noise level per ISO 9296: Sound power: LwAd: 6.2 B(A), sound pressure LpAm: 57 dB(A) printing (operating position), 49 dB(A) printing (bystander position) | | |
| Safety | printing (operating position), 49 dB(A) printing (bystander position) Czech Republic (CSN-IEC 60950-IEC 60825-1), Estonia (EEI-EN 60950-IEC 60825-1), EU (CE Mark-Low Voltage Directive 73/23/EEC), Germany (TÜV- EN 60950-IEC 60825-1), Hungary (MEEI- IEC 60950-IEC 60825-1), Lithuania (LS- IEC 60950-IEC 60825-1), Poland (B Mark- IEC 60950-IEC 60825-1), Russia (GOST- R50377), Slovakia (IEC 60950-IEC 60825-1), Slovenia (SQI- IEC 60950-EN 60825-1), South Africa (IEC 60950-IEC 60825-1. Energy Star [®] | | |
| Certifications | EU (EMC Directive 89/336/EEC), ISE Countries (CISPR 22), Poland (B-Mark-CISPR 22), Russia (GOST-CISPR 22) | | |
| Warranty | One-year standard bench repair and return to HP authorised service centre warranty | | |

Ordering information

933A HP LaserJet 1160 Printer, power cord, HP LaserJet Print Cartridge, user's guide, printer documentation and software on CD-ROM, single-sheet priority input tray, 250-sheet input tray Cables

C6518A HP USB cable - 2 m C2950A HP IEEE parallel cable (B-type) - 2 m C2951A HP IEEE parallel cable (B-type) - 3 m

Supplies

25949A HP LaserJet Print Cartridge (2,500 standard pages in accordance with ISO/IEC 19752)

Connectivity

| J3258B | HP Jetdirect 170x Externa Print Server: Etherne |
|-----------|---|
| J6035C | HP Jetdirect 175x Externa Print Server: Fast Etherne |
| J3263A | HP Jetdirect 300x Externa |
| Print S | Server: Ethernet/Fast Etherne |
| J3265A | HP Jetdirect 500x Externa |
| Print S | Server: Ethernet/Fast Etherne |
| J7942A | HP Jetdirect en3700 |
| Extern | nal Print Server: Fast Etherne |
| J7951A | HP Jetdirect ew2400 |
| 802.11g E | External Wireless Print Server |
| J6072A | HP bt1300, Bluetooth ^a Print Adapter |

Support & services

| H2634A/E | HP Care Pack, return to HP, 3 years |
|-------------------------|--|
| H5465A/E | HP Care Pack, next day exchange, 3 years |
| H5473A/E | *HP Care Pack, next day on-site, 3 years |
| H3110A/E | *Installation & network configuration |
| U8047PA/PE wa | HP Care Pack, post rranty, return to HP, 1 year |
| H2639PA/PE warran | HP Care Pack, post ty, next day on-site, 1 year |
| | *Available in LIK |

Available III UK.

http://www.hp.com

For more information, please call your local HP sales office or representative: Austria: 0800 242 242, Algeria: (0)61 56 45 43, Bahrain: 800 728, Belgium: (078) 15 20 30 (0.0496 EUR/min), Bulgaria: (+359) 2960 1940, Croatia: (+385 1) 60 60 200, Czech Republic: (00 420 2) 261 108 108 (Prague), Denmark: 48 12 10 00, Egypt: 532 5222, Estonia: (+372) 6813 823, Finland: (+358) 0205350 or 0205 350, France: 0 826 800 400, Germany: 0180 532 6222 (12 Cent/min), Greece: (01) 678 96 00, Hungary: (+36) 1 382-1111, Iceland: (354) 570 1000, Ireland: + 353 1 6158200, Israel: (972) 9 8304848, Italy: (02) 92121, Kazakhstan: +7 (3272) 980 824, Latvia: (371) 800 80 12, Lithuania: 8 800 10000 or 8 5 210333, Luxembourg: (+352) 263 160 34, Middle East: 00971 4 883 4427, Morocco (African Region): +212 22 40 47 47, Netherlands: (020) 5476666, Norway: 22 735600, Poland: infolinia: 0-800 122 622, Portugal: (808) 206 0011, Romania: (+401) 205 3300, Russia: +7 (95) 797 35 00, Slovakia: +421-250222111, Slovenia: +3861 2307 420, South Africa: 0800 118 883, Spain: (91) 634 88 00, Sweden: (08) 444 2000, Switzerland: 0848 88 44 66, Tunisia: 71 891 222, Turkey: +90 (216) 579 71 71, UAE: 8004910, UK: 08705 474747, Ukraine: +380 44 490 61 20.





©2004 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 09/04 5982-7323EEE