# **HP DesignJet T1530 Printer series**



Dual-roll 91.4-cm (36-inch), 6-ink printer for professional-quality CAD and GIS applications



#### QUALITY – Your projects, presented at their best

- Six Original HP inks produce a wide colour gamut ideal for colour graphics.
- Original HP grey and photo black inks achieve precise line accuracy, dark blacks, and true neutral greys.
- Make your architectural prints shine with professional, high-resolution graphics – opt for Adobe PostScript<sup>®</sup>.
- Communicate with precision produce plans, drawings, and maps with fine line quality, and up to 2400 dpi.

### PRODUCTIVITY – Ease, efficiency empower workgroups

- Stay organised and on task the integrated 50-page output stacking tray delivers flat, collated prints.
- Two rolls help save time easy front loading, automatic alignment; two media types/sizes, smart switching.
- Print complex files fast one A1 in 21 sec (120 A1 per hr), 500 GB hard drive, parallel processing power.
- Improve workgroup efficiency using the job center manage job queues and job storage, track print costs.

## SECURITY – Enterprise compatible, IT manageable

- Enable highly unattended printing with two 91.4-m (300-ft) rolls and Original HP ink cartridges up to 300 ml.
- Safeguard information with security protocols like IPSec, 802.1x, SNMPv3, PIN printing, and other options.<sup>1</sup>
- Easily configure/manage your printer with HP Embedded Web Server or the HP printer fleet with HP Web Jetadmin.
- Integrates easily with your other office devices iOS and Android<sup>™₂</sup> compatibility with HP Mobile Printing.<sup>3</sup>

<sup>&</sup>lt;sup>1</sup> Optional security solutions include Secure Disc Erase, Encrypted HD – available only in specific models.
<sup>2</sup> The HP Print Service Plugin app is available for Android<sup>™</sup> mobile devices running Android<sup>™</sup> v.4.4 or later. The app is free from Google Play.

Google Pray. <sup>3</sup> Local printing requires mobile device and printer to be on the same network (usually Wi-Fi access points bridge wireless to wired connections) or have a direct wireless connection. Wireless performance is dependent on physical environment and distance from access point. Wireless operations are compatible with 2.4 GHz operations only. Remote printing requires an Internet connection to an HP web-connected printer. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. See http://www.hp.com/go/design/entmobility for more details.

## HP DesignJet T1530 Printer series

#### **Technical specifications**

| Print                                 |   | What's in the box   |  |
|---------------------------------------|---|---|--|
| Line Drawings                         | 21 sec/page; 120 A1 prints per hour   | L2Y24A  | HP DesignJet T1530 Printer; Printhead; Introductory ink cartridges; Stacking tray; Printer stand<br>and media bin; Spindles; Quick reference guide; Setup poster; Startup software; Power cord |
| Print resolution                      | Up to 2400 x 1200 optimised dpi   |   |  |
| Margins (top x bottom x left x right) | Roll: 3 x 3 x 3 x 3 mm<br>Sheet: 3 x 22 x 3 x 3 mm  | L2Y24B  | HP DesignJet T1530 Printer; Printhead; Introductory ink cartridges; Stacking tray; Printer stan<br>and media bin; Spindles; Quick reference guide; Setup poster; Startup software; Power cord  |
| Technology                            | HP Thermal Inkjet   | L2Y23A  | HP DesignJet T1530 Printer; Printhead; Introductory ink cartridges; Stacking tray; Printer stan<br>and media bin; Spindles; Quick reference guide; Setup poster; Startup software; Power cord  |
| Ink types                             | Dye-based (C, G, M, pK, Y); Pigment-based (mK)  | Certification   | מות הופעום טווז, סטווענפג, ענוכג דפופופורב שנועפ, ספנעף טוגנפו, סגמו עף סטרגשמופ, רטשפו כטוע   |
| Ink colours                           | 6 (cyan, grey, magenta, matte black, photo black, yellow)   | Safety  | USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapor   |
| ink drop                              | 6 pl (C, M, Y, G, pK); 9 pl (mK)  | Salety  | (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KATS)  |
| Print head nozzles                    | 9632  | Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC   |  |
| Print Heads                           | 1 (cyan, grey, magenta, matte black, photo black, yellow)   |   | Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A<br>product: Korea (KCC)   |
| Line accuracy                         | +/- 0.1% (+/- 0.1% of the specified vector length or +/- 0.2 mm (whichever greater) at 23°C<br>(73°F), 50-60% relative humidity, on A0/E HP Matte Film in Best or Normal mode with Original<br>HP inks)   | Environmental   | ENERGY STAR®; WEEE; EU RoHS; China RoHS; REACH; EuP; FEMP; EPEAT Bronze  |
| Minimum line width                    | 0.02 mm (HP-GL/2 addressable)   | ENERGY STAR   | Yes  |
| Guaranteed minimum line width         |   | Warranty  |  |
|                                       | 0.07 mm (ISO/IEC 13660:2001(E))   |   | 2-year commercial hardware warranty  |
| Maximum media roll weight             | 11.9 kg   |   |  |
| Maximum optical density               | 6 L* min/2.15 D   | Ordering informat   | ion  |
| Media                                 |   | Duradurat   |  |
| Handling                              | Input: two automatic front-loading roll feeds, smart roll switching, sheet feed; Output: integrated<br>output stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media bin, automatic<br>cutter   | Product   |  |
|                                       |   | L2Y24A  | HP DesignJet T1530 36-in PostScript Printer  |
| Турез                                 | Bond and coated paper (bond, coated, heavyweight coated, super heavyweight plus matte,<br>coloured), technical paper (natural tracing, translucent bond, vellum), film (clear, matte,   | L2Y24B  | HP DesignJet T1530 36-in PostScript Printer with Encrypted Hard Disk   |
|                                       |   | L2Y23A  | HP DesignJet T1530 36-in Printer   |
|                                       | polyester), photographic paper (satin, gloss, semi-gloss, matte, high-gloss), backlit,  | Accessories   |  |
| <b>e</b> *                            | self-adhesive (two-view cling, indoor paper, polypropylene, vinyl)  | CN538A  | HP Designjet 3-in Core Adapter   |
| Size                                  | 210 x 279 to 914 x 1219 mm  | L4R66A  | HP DesignJet 36-in Spindle   |
| Thickness                             | Up to 19.7 mil  | Printheads  |  |
| Memory                                |   | B3P06A  | HP 727 DesignJet Printhead   |
| RAM                                   | 96 GB (file processing)   | Ink supplies  |  |
| Connectivity                          |   | B3P19A  | HP 727 130-ml Cyan DesignJet Ink Cartridge   |
| Interfaces (standard)                 | Gigabit Ethernet (1000Base-T)   | B3P20A  | HP 727 130-ml Magenta DesignJet Ink Cartridge  |
| Print languages (standard)            | L2Y24A: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG,<br>CALS G4, HP-PCL3GUI, URF; L2Y24B: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3,<br>HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP-PCL3GUI, URF; L2Y23A: HP-GL/2, HP-RTL, TIFF, JPEG,<br>CALS G4, HP-PCL3GUI, URF; | B3P21A  | HP 727 130-ml Yellow DesignJet Ink Cartridge   |
|                                       |   | B3P22A  | HP 727 130-ml Matte Black DesignJet Ink Cartridge  |
|                                       |   | B3P23A  | HP 727 130-ml Photo Black DesignJet Ink Cartridge  |
| Environmental ranges                  |   | B3P24A  | HP 727 130-ml Gray DesignJet Ink Cartridge   |
| Operating temperature                 | 5 to 40°C   | C1Q12A  | HP 727 300-ml Matte Black DesignJet Ink Cartridge  |
| Storage temperature                   | -25 to 55°C   | F9J76A  | HP 727 300-ml Cyan DesignJet Ink Cartridge   |
| Operating humidity                    | 20 to 80% RH  | F9J77A  | HP 727 300-ml Magenta DesignJet Ink Cartridge  |
| Storage humidity                      | 0 to 95% RH   | F9J78A  | HP 727 300-ml Yellow Design Jet Ink Cartridge  |
| Acoustic                              |   | F9J79A  | HP 727 300-ml Photo Black DesignJet Ink Cartridge  |
| Sound Pressure                        | 47 dB(A)  | F9J80A  | HP 727 300-ml Gray DesignJet Ink Cartridge   |
| Sound Power                           | 6.5 B(A)  | Service & support   |  |
| Dimensions (w x d x h)                |   | H4518E HP Installation Service  | with Network Setup   |
| Printer                               | 1399 x 916 x 1110 mm  | U1XV4E Preventive Maintenance Service<br>U8PM8E HP 3 year Next business day Onsite Support with Defective Media<br>U8UB4E HP 4 year Next business day Onsite Support with Defective Media<br>U8PM9E HP 5 year Next business day Onsite Support with Defective Media<br>U8PM0E HP 1 year Post Warranty Next business day Onsite Support with Defective Media |  |
| Packaged                              | 1500 x 781 x 815 mm   |   |  |
| Weight                                |   |   |  |
| Printer                               | 88 kg   |   |  |
| Packaged                              | 120 kg  | U8UA5PE HP 2 year Post Warra  | nty Next business day Onsite Support with Defective Media  |
| Power consumption                     | 120 ng  |   | vices offer solutions for business critical environments - installation, extended suppor   |
| Maximum                               | 120 watts (printing); 1.3 watts (5 watts with embedded Digital Front End) (sleep)   |   | as variety of value added services. For more information, please visit   |
|                                       |   | <ul> <li>hp.com/go/designjet/support.</li> <li>For more information about HP Care Packs, please visit www.hp.com/go/cpc</li> <li>Use Original HP inks and printheads to experience consistent high quality and reliable performance that enable<br/>less downtime. For more information, visit hp.com/go/OriginalHPinks.</li> </ul>                         |  |
| Power requirements                    | Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 4.2 A max (peak<br>current)   |   |  |
|                                       |   |   |  |



Contact us

United Kingdom 0800.408.0784 Ireland 1.800.94.4757 Middle East 800.035703174 South Africa 0800.999.693













#### For the entire HP Large Format Printing Materials portfolio, please see globalBMG.com/hp.

For more HP Large Format Media substrates and sizes please visit us online at: http://www.hp.com/go/designjet/supplies

The product could differ from the images shown. © Copyright 2016 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

