

HP LaserJet Enterprise 700 MFP M725 series

Ideal for large workgroups who need a high-performance, reliable MFP that prints on a range of paper sizes up to A3, and helps speed work with robust scanning capabilities, a convenient colour touchscreen and powerful manageability features.



HP LaserJet Enterprise 700 MFP M725dn



HP LaserJet Enterprise 700 MFP M725f



HP LaserJet Enterprise 700 MFP M725z



HP LaserJet Enterprise 700 MFP M725z+

Empower teams to do more – print, scan, copy and fax' on paper sizes up to A3 – from a desktop MFP

- Stay focused on work paper capacity up to 4,600 sheets and high-capacity cartridges limit interruptions.²
- Get impressive document quality with near edge-to-edge printing and a convenient, built-in stapler.⁴
- Print what you need, even on the go from your smartphone or tablet – using HP ePrint^s or Apple Airprint[™].⁶

Quicken your business pace.

- Set a swift pace use this powerful MFP to keep your work moving. Save time and make your job easier, using HP Quick Sets.
- Efficiently capture the right content: automatically remove blank pages, preview, edit and control jobs on the large colour touchscreen.
- Incorporate paper documents into digital workflows easily send scans to fax³, email, network folders or USB. Print right from a memory device via the USB port.



Simplify fleet management and safeguard devices using world-class tools.⁷

- Monitor your devices with industry-leading tools, including HP Web Jetadmin.⁷ Help protect data both in transit and at rest.
- Enhance security with PIN printing. Add safeguards via the hardware integration pocket. Integrate tomorrow's solutions with ease.
- Add security tools such as card and badge readers via the hardware integration pocket.⁹

Reduce energy use with HP Auto-On/Auto-Off Technology® and HP Instant-on Technology.®

- Help conserve resources and meet corporate environmental goals. HP Auto-On/Auto-Off Technology helps reduce energy use.⁹
- Easily manage your printers with HP EcoSMART Fleet. Create and manage environmental printing policies and practices.¹¹
- Save paper and cut costs, using automatic two-sided printing.
- Easily recycle Original HP LaserJet toner cartridges through HP Planet Partner s.¹²

¹ Maximum paper capacity of 4,600 sheets; requires the purchase of optional paper tray accessorie

² High-capacity cartridges are optional for the HP Laser Jet Enterprise 700 MFP Series M725.

³ Fax capabilities are available with an optional fax card on the HP Laser Jet Enterprise MFP M725dn

⁴ In-line stapler is not available on the HP Laser Jet Enterprise MFP M725dn or M725f.

⁵ Requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see www.hpconnected.com). Mobile devices require Internet Connection and email capability. Hay require wireless access point. Separately purchased data plans or usage fees may apply. Print times and connection speeds may vary. Some HP Laser let printer's may require firmware upprades.

⁶ Supports the following devices running IOS 4.2 or later: IPad[®], IPad[®] 2, IPhone[®] (3GS or later) or IPad touch[®] (3rd generation or later). Works with HP's AirPrint-enabled printers and requires the printer be connected to the same network as your IOS device. Wireless performance is dependent upon physical environment and distance from the access point. AirPrint, the AirPrint Logo, IPad, Phone and IPad touch are trademarks of Apple[®] Inc., registered in the U.S. and other countries.

⁷ HP Web Jetadmin is free and can be downloaded at www.hp.com/go/webjetadmin.

⁸ Solutions deployed through the hardware integration pocket may require additional purchase.
⁹ HP Auto-On/Auto-Off Technology capabilities subject to printer and settings; may require a firmware upgrade

¹⁰ Compared with products that use traditional fusing.

¹¹ HP EcoSMART Fleet must be purchased separately

² Programme availability varies. Original HP partridge return and recycling is currently available in more than 50 countries, territories and regions in Asia, Europe, and North and South America through the HP Planet Partners programme or more information, vsit www.hp.com/recycle.

Print









Product walkaround

- HP LaserJet Enterprise 700 MFP M725z+:
- 1. 100-sheet automatic document feeder
- 2. Intuitive 20.3 cm (8-inch) pivoting light touch SVGA colour control panel with
- FutureSmart firmware and scan preview
- 3. Hardware integration pocket for solution integration
- 4. Easy-access USB port to save and print files directly
- 5. In-line stapler/stacker for stapling up to 30-pages and a 500-sheet output tray
- 6. Standard 250-sheet stacker output bin
- 7. Front door allows convenient access to print cartridge 8. Built-in automatic two-sided printing
- 9. 2 x 250-sheet input tray 2 and tray 3
- 10. 3,500-sheet high-capacity feeder with cabinet for a 4,100-sheet total input capacity
- 11. 100-sheet multipurpose tray 1 handles up to 100 pages 12. Fax port
- 13. 800 MHz processor, 1 GB standard memory (Expandable to 1,5 GB)
- 14. HP High Performance Encrypted Hard Drive
- 15. Hi-Speed USB 2.0 printing port
- 16. HP Jetdirect Gigabit Ethernet print server





Series at a glance



HP LaserJet Enterprise 700 MFP M725dn

- Print, copy, scan, digital send
- print/copy speed of up to 41 ppm
- up to 1200 x 1200 dpi
 - I X
- 1024 MB RAM
- 800 MHz processor
- 1 HP High Performance Secure Hard Disk
- 1 Hi-Speed USB 2.0 Host
- 1 Hi-Speed USB 2.0 Device
- 2 Internal USB 2.0 Host
- 1 Gigabit Ethernet 10/100/1000Base-T
- 1 Foreign Interface (FIH)
- 1 Hardware Integration Pocket
- 100-sheet multipurpose tray
- 2 x 250-sheet input trays
- 250-page output tray
- 100-sheet Automatic Document Feeder (ADF)



HP LaserJet Enterprise 700 MFP M725f As HP LaserJet Enterprise MFP M725dn,

- with built-in fax
- 1 x 500-sheet tray
- 1 x 500-sheet feeder, cabinet and stand.



HP LaserJet Enterprise 700 MFP M725z As HP LaserJet Enterprise MFP M725dn,

- with built-in fax
- 500-sheet inline stapler/stacker
- 3 x 500-sheet paper feeder and stand.



HP LaserJet Enterprise 700 MFP M725z+ As HP LaserJet Enterprise MFP M725dn,

- with built-in fax
- 500-sheet inline stapler/stacker
- 3500-sheet feeder and stand.

Recommended accessories





Support the productivity of arowing work aroups with simple, robust paper input accessories that enable media versatility, from A5, A4, legal and up to A3, and allow longer printing without reloading paper.



CF243A HP Laser let 1x500-sheet Feeder with Cabinet and Stand

Support the productivity of growing work groups with simple, robust paper input accessories that enable media ver satility, from A5, A4, legal and up to A3, and allow longer printing without reloading paper.



CF242A HP LaserJet 3x500-sheet Feeder and Stand

HP Laser let 3x500-sheet Paper Travs mean you spend less time loading paper and more time printing. Meet the printing needs of a high-volume printing environment with the 3x500-sheet paper feeder and stand.



CF245A HP LaserJet 3500-sheet **High-capacity Input Tray** Feeder and Stand

Support the productivity of growing work groups with this high-performance, robust input feeder and stand. The additional 3 500-sheet naner capacity allows users to spend more time focusing on business and less time reloading paper.



C8091A **HP Staple Cartridge Refill**

HP Staple Cartridge Refills give you more for your money and ensure you don't have to worry about frequent cartridge replacement. Fach refill contains 5000 staples.



CC487A HP LaserJet MFP Analog Fax Accessory 500

Improve workteam productivity and make information sharing more efficient. Simply add embedded analog fax functionality to your HP Laser let MEP¹ to send and receive documents quickly, easily and securely

Ordering information



HP LaserJet Enterprise 700 MFP M725dn (CF066A)

HP LaserJet Enterprise MFP M725dn: HP Black LaserJet Toner Cartridge (~10,000 pages); Printer documentation and software on CD-ROM; Installation guide, Support flyer, Warranty card: Power cord: 2x250-sheet travs



HP LaserJet Enterprise 700 MFP M725f (CF067A) HP LaserJet Enterprise MFP M725f: HP Black

Laser let Toner Cartridge (~10.000 pages); Printer documentation and software on CD-ROM; Installation guide, Support flyer, Warranty card: Power cord: Fax cable: 2x250-sheet trays; 1x500 sheet feeder; cabinet and stand: Built-in fax.



HP LaserJet Enterprise 700 MFP M725z (CF068A)

HP LaserJet Enterprise MFP M725z; HP Black Laser let Toner Cartridge (~10.000 pages); Printer documentation and software on CD-ROM; Installation guide, Support flyer, Warranty card: Power cord: Fax cable: 2x250-sheet trays; 3x500-sheet Paper feeder and stand; 500-sheet inline Stapler/Stacker; Built-in fax.



HP LaserJet Enterprise 700 MFP M725z+ (CF069A)

HP LaserJet Enterprise MFP M725z+: HP Black LaserJet Toner Cartridge (~10,000 pages); Printer documentation and software on CD-ROM; Installation guide, Support flyer, Warranty card: Power cord: Fax cable: 2x250-sheet trays; 1 x 3500-sheet Feeder and Stand; 500-sheet inline Stapler/Stacker; Built-in fax.

Accessories, Supplies and Support

Accessories				
CF239A	HP LaserJet 500-sheet Feeder and Tray			
CF243A	HP LaserJet 1x500-sheet Feeder with Cabinet and Stand			
CF242A	HP LaserJet 3x500-sheet Feeder and Stan			
CF245A	HP LaserJet 3500-sheet High-capacity Input Tray Feeder and Stanc			
C8091A	HP Staple Cartridge Refill			
CC487A	HP LaserJet MFP Analog Fax Accessory 500			
L2718A	HP 100 ADF Roller Replacement Kit			
Connect	ivity			
J8021A	HP Jetdirect ew2500 802.11b/g Wireless Print Server			
J8026A	HP Jetdirect 2700w USB Wireless Print Server			

Supplies

HP 14A Black LaserJet Toner Cartridge CF214A Average cartridge yields 10,000 standard pages. Declared yield based on ISO/IEC 19752 and continuous printing.

CF214X HP 14X Black LaserJet Toner Cartridge Average cartridge yields 17,500 standard pages. Declared yield based on ISO/IEC 19752 and continuous printing.

CF254A HP LaserJet CF254A 220V Maintenance/Fuser Kit 200.000 pages

Service & support

U7A05E - HP 3 year Next Business Day LaserJet M725 MFP Hardware Support

U7A06E - HP 4 year Next Business Day LaserJet M725 MFP Hardware Support

U7A07E - HP 5 year Next Business Day LaserJet M725 MFP Hardware Support

U7A09E - HP 3 year 4 hour 13x5 LaserJet M725 MFP Hardware Support

U7Y72PE - HP 1 year Post Warranty Next Business Day LaserJet M725 MFP Hardware Support

U7Y73PE - HP 2 year Post Warranty Next Business Day LaserJet M725 MFP Hardware Support

U7Y75PE - HP 1 year Post Warranty 4 hour 13x5 LaserJet

M725 MFP Hardware Support

For a complete list of supplies, accessories and services, please refer to http://www.hp.com For workflow, device management and other solutions, please visit the Global Solutions catalog: www.hp.com/go/gsc

Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies.

Count on dependable support to create the best image possible. We can help you enhance your printing and imaging environment, protect your IT investment, and grow your business—with expert support that's affordable, per sonal, and tailored to your needs through HP Care Pack Services.

Technical specifications

Print technology	Laser						
Print speed	First page out: black: As fast as 10 sec						
	A4 black: Up to 41 ppm						
		on the system configuration, software application, drive					
			ation see np.com/go/printerclaims. Exact	speed varies depending on the system configuration, software application,			
Processor	driver, and document complexity. 800 MHz						
Memory	1 GB. Expandable to 1.5 GB through 512 MB industry-standard DIMM						
Hard disk	Standard, embedded HP High-Performance Secure Hard Disk, minimum 320 GB; AES 256 hardware encryption or greater; Secure erase capabilities (Secure File Erase-Temporary Job Files, Secure Erase-Jot Data, Secure ATA Erase-Disk)						
Print	Data, Secure AIA Erase-Disk) Quality HP ProRes 1200 (1200 x 1200 dpi), HP FastRes 1200 (1200 dpi quality), HP Resolution Enhancement technology, 600 x 600 dpi, 300 x300 dpi						
Print	Quality HP Prokes 1200 (1200 x 1200 dpi), HP rastres 1200 (1200 dpi quality), HP kesolution Ennancement technology, 600 x 600 dpi, 300 x300 dpi Resolution Black: Up to 1200 x 1200 dpi						
	Printer languages HP PCL 6; HP PCL 5; HP PCstscript Level 3 emulation; PDF						
	Typefaces/Fonts 105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale						
	Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP Laser Jet Fonts and IPC						
	Emulation available at hp.com/go/laserjetfonts						
	Duty cycle (monthly, A4) Up to 200,000 pages Recommended monthly page volume 5000 to 20,000						
	Recommended infinity page volume source 20,000 to 20,000 Print margins (mm) Top: 2 mm. Left: 2 mm. Right: 2 mm. Bottom: 2 mm						
	Maximum print area 308 x 465.9 mm						
Fax	M725dia: Optional; M725f; Yes; M725z; Yes; M725z+ Yes;						
	Modem speed 33.6 kbps						
	Telecom compliance Fax Telecom: ES 203 021; R&TTE Directive 1999/5/EC (Annex II) with CE Marking (Europe); FCC Part 68; other Telecom approvals as required by individual countries						
	Fax memory Up to 100 pages						
	Fax resolution Standard: 204 x 98 dpi. Fine: 204 x 196 dpi, 256 levels of grey. Superfine: 300 x 300 dpi, 256 levels of grey. Photo: 300 x 300 dpi (400 x 400 dpi for received faxes only)						
Disital condina	Quick dialing Up to 100 numbers (each can contain 100 numbers) File formats Digital Send: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A; Scan to easy access USB: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A; Print from easy access USB: PDF, PS, Print Ready files (.prn,						
Digital sending	File formats	Digital Send: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A; Si .pcl, .cht)	an to easy access USB: PDF, JPEG, TIFF, M.	iner, APS, PDF/A; Print from easy access USB: PDF, PS, Print Ready files (.prn,			
	.p.q., (.nt) Features Standard: Scan to E-mail; Save to Network Folder; Save to USB drive; Send to FTP; Send to LAN Fax; Send to Internet Fax; Local Address Book; SMTP over SSL. Optional:						
	· catales			to printer; Authentication; Digital fax (send to LAN, Internet); OCR; Local			
		Address Book					
Scan	Scan Speed (A4)	Up to 50 ppm (black and white), up to 30 ppm (co	lour)				
	Scan Speed Duplex (A4) Up to 19 ipm (black and white), up to 14 ipm (colour)						
	Type Flatbed, ADF. Colour scanning:Yes						
	Scan resolution Optical: Up to 600 dpi						
	Bit depth 24-bit Grey scale levels 256						
	urey scale tevets 256 Scannable area Maximum media size: 297 x 420 mm						
Сору	Copy speed	A4 black: Up to 41 cpm					
сору	Copy resolution	600 x 600 dpi					
	Multiple copies	Up to 9999 copies					
	Reduce/enlarge	25 to 400%					
Media handling	Input:	Capacity	Weight	Size			
	Tray 1	sheets: 100; envelopes: 10; labels: 100;	60 to 199 g/m²	A4; A5; B4 (JIS); B5 (JIS); 76.2 × 127 to 312 × 469.9			
	Trou 2	transparencies: 100; postcards: 10 sheets: 250	60 to 120 g/m²	mm A4; A5;, B4 (JIS); B5 (JIS); 148 x 210 to 297 x 363 mm			
	Tray 2 Tray 3	Sileets. 200	60 to 120 g/m ²	A3; A4; A5; B4 (JIS); B5 (JIS); 148 x 210 to 297 x 305 mm			
	indy 5		66 to 120 g/m	mm			
	ADF	sheets: 100	45 to 199 g/m²	A3; A4; A4-R; A5; A6; B4 (JIS); B5 (JIS); B6 (JIS); 10 ×			
				15 cm; 13 x 18 cm			
	Output: Envelopes: Up to 50 envelopes						
	Duplex printing: Automatic (sta						
Media types		plain, preprinted, prepunched, recycled, rough, tough p					
Interface and connectivity	Standard: 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/1/100/1 network; 1 Foreign Interface; 1 Hardware Integration Pocket; 2 Internal USB Host						
-	Optional: HP Jetdirect ew2500 802.11b/g Wireless Print Server JB021A; HP Jetdirect 2700w USB Wireless Print Server JB026A						
Operating systems compatibility	Windows 8, Windows 7, Windows Vista, Windows XP (SP2+), Windows Server 2003 (SP1+), Windows Server 2008 (32/64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2012 (64-bit), Monore						
	v10.6, OS X Lion, OS X Mountain Lion; For the latest operating system support see: Citrix® and Windows Terminal Services (hp.com/go/upd); Novell® (novell.com/ipinit); Linux (hplip.net); UNIX® (hp.com/go/upd); Novell® (novell.com/ipinit); Linux (hplip.net); UNIX® (hp.com/go/upd); Novell® (novell.com/ipinit); Linux (hplip.net); UNIX®						
	(np.com/go/unix , np.com/go/unixmodelscripts, np.com/go/jetarecturinx_software); SAP device types (np.com/go/sap/arvers, np.com/go/sap/print); HP ePrint Mobile Univer (np.com/go/geprintmobiledriver). Recent printer drivers for all supported operating systems are available at hp.com/go/ji/HPTM272_software						
	Windows 8, Windows 7, Windows Vista, Windows XP (SP2+), Windows Server 2003 (SP1+), Windows Server 2008, Windows Server 2008 R2, Windows Server 2012 (64-bit); 200 MB available hard disk						
Minimum system requirements	windows s, windows s, windows set with a windows are set and s						
Minimum system requirements			spect operating system requirements, CD-ROM/DVO-ROM or Internet, see apple.com				
Minimum sys tem requirements	space; operating system comp						
	space; operating system comp hardware system requirement:		ation driver & Installer on Web), Note: No	Mac Software inbox			
Standard software	space; operating system comp hardware system requirement: Windows Installer, HP PCL 6 dis	s, CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emu		Mac Software inbox e Home menu); Easy Access USB; Hardware Integration Pocket			
Standard software Control panel	space; operating system comp hardware system requirement Windows Installer, HP PCL 6 dis 20.3 cm touchscreen, LCD (colo	s, CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emul sur graphics); rotating (adjustable angle) display; illumin	ated Home button (for quick return to the	e Home menu); Easy Access USB; Hardware Integration Pocket			
Standard software Control panel	space; operating system comp hardware system requirement Windows Installer, HP PCL 6 dis 20.3 cm touchscreen, LCD (colo Requirements:Input voltage: 2	c, CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emul ur graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consump	ated Home button (for quick return to the tion:890 watts (active print/copy), 39 wa				
Standard software Control panel	space; operating system comp hardware system requirement Windows Installer, HP PCL 6 dis 20.3 cm touchscreen, LCD (cold Requirements:Input voltage: 2 (TEC): 4.39 kWh/Week. Power	c, CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emul ur graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consump	ated Home button (for quick return to the tion:890 watts (active print/copy), 39 wa	e Home menu); Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption			
Standard software Control panel Power	space: operating system comp hardware system requirement: Windows Installer, HP PCL 6 di 20.3 cm touchscreen, LCD (colo Requirements:Input voltage: 2 (TEC): 4.39 KWh/Week. Power subject to change, see hp.com, Out of package: M725dn: 614	c, CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emul ury graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consump requirements are based on the country/region where th support for current information. x 649 x 609 mm; M725f: 745 x 681 x 1160 mm; M72	ated Home button (for quick return to the tion:890 watts (active print/copy), 39 wa e printer is sold. Do not convert operatin 252: 745 x 681 x 1192 mm; M7252+: 74	e Home menu); Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption			
Standard software Control panel Power	space; operating system comp hardware system requirement: Windows Installer, HP PCL 6 die 20.3 cm touchscreen, LCD (colo Requirements:Input voltage: 2 (TEC): 4.39 kWh/Week. Power- subject to change, see hp.com, Out of package: M725dn : 614 856 x 760 x 1522 mm; M725	c, CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emui ur graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/ - 10%), 50/60 Hz (+/ - 2 Hz). Consump equirements are based on the country/region where th support for current information. x 649 x 609 mm; M7257: 745 x 681 x 1160 mm; M7 i: 856 x 760 x 1553 mm; M7252+: 856 x 760 x 1553 nf	ated Home button (for quick return to the titon:890 watts (active print/copy), 39 wa te printer is sold. Do not convert operating 252: 745 x 681 x 1192 mm; M7252+: 74 mm;	e Home menu); Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption g voltages; this will damage the printer and void the product warranty. Values 15 x 681 x 1192 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f:			
Standard software Control panel Po wer Dimensions (w x d x h)	space; operating system comp hardware system requirement: Windows Installer, HP PCL 6 die 20.3 cm touchscreen, LCD (colo Requirements:Input voltage: 2 (TEC): 4.39 kWh/Week. Power- subject to change, see hp.com, Out of package: M725dn : 614 856 x 760 x 1522 mm; M725	c, CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emul ury graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consump requirements are based on the country/region where th support for current information. x 649 x 609 mm; M725f: 745 x 681 x 1160 mm; M72	ated Home button (for quick return to the titon:890 watts (active print/copy), 39 wa te printer is sold. Do not convert operating 252: 745 x 681 x 1192 mm; M7252+: 74 mm;	e Home menu); Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption g voltages; this will damage the printer and void the product warranty. Values 15 x 681 x 1192 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f:			
Standard software Control panel Power Dimensions (w x d x h) Weight	space; operating system comp hardware system requirement: Windows Installer, HP PCL 6 die 20.3 cm touchscreen, LCD (colo Requirements:Input voltage: 2 (TEC): 4.39 kWh/Week. Power- subject to change, see hp.com, Out of package: M725dn : 614 856 x 760 x 1522 mm; M725	c, CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emul ur graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consump equirements are based on the country/region where th Support for current information. x 649 x 609 mm; M7255; 745 x 681 x 1160 mm; M7 is 856 x 760 x 1553 mm; M7252+: 856 x 760 x 1553 r 11 kg; M725f: 87.1 kg; M7252: 92.35 kg; M7252+: 10	ated Home button (for quick return to the titon:890 watts (active print/copy), 39 wa te printer is sold. Do not convert operating 252: 745 x 681 x 1192 mm; M7252+: 74 mm;	e Home menu); Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption g voltages; this will damage the printer and void the product warranty. Values 15 x 681 x 1192 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f:			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	space; operating system comp hardware system requirement: Windows Installer, HP PCL 6 die 20.3 cm touchscreen, LCD (col Requirements:Input voltage: 2. (TEC): 4.39 kWh/Week. Power subject to change, see hp.com, Out of package: M725dn: 614 856 x 760 x 1522 mm; M725g . Out of package: M725dn: 54. HP Web Jetadmin, HP Utility (M	c, CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emul ur graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz), Consump equirements are based on the country/region where th Support for current information. x 649 x 609 mm; M725f: 745 x 681 x 1160 mm; M77 i: 856 x 760 x 1553 mm; M725z+: 856 x 760 x 1553 r 11 kg; M725f: 87.1 kg; M725z: 92.35 kg; M725z+: 1(ac)	ated Home button (for quick return to the titon:890 watts (active print/copy), 39 wa e printer is sold. Do not convert operating 252: 745 x 681 x 1192 mm; M7252+: 74 mm; 22.42 kg; Packaged: M725dn: 68.6 kg; M	e Home menu); Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption g voltages; this will damage the printer and void the product warranty. Values 15 x 681 x 1192 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f:			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	space; operating system comp hardware system requirement: Windows Installer, HP PCL 6 die 20.3 cm touchscreen, LCD (col Requirements:Input voltage: 2. (TEC): 4.39 kWh/Week. Power subject to change, see hp.com, Out of package: M725dn: 614 856 x 760 x 1522 mm; M725g . Out of package: M725dn: 54. HP Web Jetadmin, HP Utility (M	c, CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emul ur graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 H2). Consump equirements are based on the country/region where th support for current information. x 649 x 609 mm; M725f: 745 x 681 x 1160 mm; M72 is 856 x 760 x 1553 mm; M725z+: 856 x 760 x 1553 r 11 kg; M725f: 87.1 kg; M725z: 92.35 kg; M725z+: 1(ac) x 55L/TLS, 802.1X authentication (EAP- PEAP; EAP-TLS)	ated Home button (for quick return to the titon:890 watts (active print/copy), 39 wa e printer is sold. Do not convert operating 252: 745 x 681 x 1192 mm; M7252+: 74 mm; 22.42 kg; Packaged: M725dn: 68.6 kg; M	e Home menu); Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption g voltages; this will damage the printer and void the product warranty. Values 15 x 681 x 1192 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 1725f: 105.4 kg; M725z: 113 kg; M725z+: 122 kg;			
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment	space: operating system comp hardware system requirement: Windows Installer, HP PCL 6 die 20.3 cm touchscreen, LCD (cold Requirements:Input voltage: 2 (TEC): 4.39 KWh/Week. Power subject to change, see hp.com, Out of package: M725dn : 614 856 x 760 x 1522 mm; M725 Out of package: M725dn : 54. HP Web Jetadmin, HP Utillty (M Management security: SMMP4: WJA-10 IPsec Configuration us	c, CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emul ur graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/ 10%), 50/60 Hz (+/ - 2 Hz). Consump equirements are based on the country/region where th support for current information. x 649 x 609 mm; M7255: 745 x 681 x 1160 mm; M7 is 856 x 760 x 1553 mm; M725z+: 856 x 760 x 1553 i 11 kg; M725f: 87.1 kg; M725z+: 92.35 kg; M725z+: 1(ad) , SSL/TLS, 802.1X authentication (EAP- PEAP, EAP-TLS ng IPsec Plug-in	ated Home button (for quick return to the tion:890 watts (active print/copy), 39 wa le printer is sold. Do not convert operating 252: 745 x 681 x 1192 mm; M7252+: 74 nm; 12.42 kg; Packaged: M725dn: 68.6 kg; M , IPP over TLS, IPsec/Firewall with Certific	e Home menu); Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption g voltages; this will damage the printer and void the product warranty. Values 15 x 681 x 1192 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 1725f: 105.4 kg; M725z: 113 kg; M725z+: 122 kg;			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management	space; operating system comp hardware system requirement Windows Installer, HP PCL 6 die 20.3 cm touchscreen, LCD (colo Requirements:Input voltage: 2 (TEC): 4.39 kWh/Week. Power subject to change, see hp.com, Out of package: M725dn: 614 856 x 760 x 1522 nm; M7255 Out of package: M725dn: 54. HP Web Jetadmin, HP Utility (M Management security: SNMPv: WJA-10 IPsec Configuration us Operating temperature: 10 to to 60°C. Storage humidity: 10	c) CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emul ur graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 H2). Consump equirements are based on the country/region where th support for current information. x 649 x 609 mm; M7255; 745 x 681 x 1160 mm; M72 it 856 x 760 x 1553 mm; M725z+: 856 x 760 x 1553 n 11 kg; M725f: 87.1 kg; M725z+: 856 x 760 x 1553 n c, 55L/TLS, 802.1X authentication (EAP- PEAP, EAP-TLS ng IPsec Plug-in 12.5%C. Recommended operating temperature: 10 to 3 to 90% RH	ated Home button (for quick return to the tion:890 watts (active print/copy), 39 wa le printer is sold. Do not convert operating 252: 745 x 681 x 1192 mm; M7252+: 74 nm; 12.42 kg; Packaged: M725dn: 68.6 kg; M , IPP over TLS, IPsec/Firewall with Certific	e Home menu); Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption g voltages; this will damage the printer and void the product warranty. Values 15 x 681 x 1192 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 1725f: 105.4 kg; M725z: 113 kg; M725z+: 122 kg; Eate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment	space; operating system comp hardware system requirement: Windows Installer, HP PCL 6 die 20.3 cm touchscreen, LCD (cold Requirements:Input voltage: 2 (TEC): 4.39 KWh/Week. Power subject to change, see hp. com, Out of package: M725dn : 54. HP Web Jetadmin, HP Utility (M Management security: SMMPv: WJA-10 IPsec Configuration us Operating temperature: 10 to: to 60%C. Storage humidity: 10 Acoustic Power Emissions: 6.8.	c, CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emui ur graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/ - 10%), 50/60 Hz (+/ - 2 Hz). Consump equirements are based on the country/region where th support for current information. x 649 x 609 mm; M7255: 745 x 681 x 1160 mm; M7 is 856 x 760 x 1553 mm; M725z+: 856 x 760 x 1553 n 11 kg; M725f: 87.1 kg; M725z+: 92.35 kg; M725z+: 1(ad , SSL/TLS, 802.1X authentication (EAP- PEAP, EAP-TLS ng IPsec Plug-in 12.5%C. Recommended operating temperature: 10 to 3 to 90% RH B(A)	ated Home button (for quick return to the tion:890 watts (active print/copy), 39 wa le printer is sold. Do not convert operating 252: 745 x 681 x 1192 mm; M7252+: 74 nm; 12.42 kg; Packaged: M725dn: 68.6 kg; M , IPP over TLS, IPsec/Firewall with Certific	e Home menu); Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption g voltages; this will damage the printer and void the product warranty. Values 15 x 681 x 1192 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 1725f: 105.4 kg; M725z: 113 kg; M725z+: 122 kg; Eate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	space; operating system comp hardware system requirement: Windows Installer, HP PCL 6 die 20.3 cm touchscreen, LCD (cold Requirements:Input voltage: 2 (TEC): 4.39 KWh/Week. Power- subject to change, see hp.com, Out of package: M725dn : 614 856 x 760 x 1522 mm; M725d Out of package: M725dn : 54. HP Web Jetadmin, HP Utility (M Management security: SNMPv: WJA-10 IPsec Configuration us Operating temperature: 10 to to 60°C. Storage humidity: 10 Acoustic Power Emissions: 5.8 Acoustic Pressure Emissions: 5.8	c) CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emul ur graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consump equirements are based on the country/region where th Support for current information. x 649 x 609 mm; M725f: 745 x 681 x 1160 mm; M7; is 856 x 760 x 1553 mm; M725z+: 856 x 760 x 1553 1 11 kg; M725f: 87.1 kg; M725z+: 92.35 kg; M725z+: 1(ac) x; SSL/TLS, 802.1X authentication (EAP- PEAP, EAP-TLS ng IPsec Plug-in 12.5°C. Recommended operating temperature: 10 to 3 to 90% RH B(A) 4 dB(A)	ated Home button (for quick return to the tion:890 watts (active print/copy), 39 wa le printer is sold. Do not convert operating 252: 745 x 681 x 1192 mm; M7252+: 74 nm; 22.42 kg; Packaged: M725dn: 68.6 kg; M I, IPP over TLS, IPsec/Firewall with Certific 2.59°C . Operating humidity: 20 to 80% RH	e Home menu); Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption g voltages; this will damage the printer and void the product warranty. Values 15 x 681 x 1192 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 1725f: 105.4 kg; M725z: 113 kg; M725z+: 122 kg; trate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for I. Operating humidity recommended: 30 to 70% RH. Storage temperature: 0			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management	space; operating system comp hardware system requirement Windows Installer, HP PCL 6 die 20.3 cm touchscreen, LCD (colo Requirements:Input voltage: 2 (TEC): 4.39 kWh/Week. Power subject to change, see hp.com, Out of package: M725dn: 614 856 x 760 x 1522 nm; M725 Out of package: M725dn: 64 HP Web Jetadmin, HP Utilty (M Management security: SNMPv: WJA-10 IPsec Configuration us Operating temperature: 10 to to 60°C. Storage humidity: 10 Acoustic Power Emissions: 5 Acoustic Pressure Emissions: 5 CISPR 22:2008 / EH 55022:20	c) CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emul ur graphics); rotating (adjustable angle) display; illumir 20 to 240 VAC (+7-10%), SO(60 Hz (+7-2 Hz). Consump equirements are based on the country/region where th Support for current information. x 649 x 609 mm; M725f; 745 x 681 x 1160 mm; M7; is 856 x 760 x 1553 mm; M725z+: 856 x 760 x 1553 i 11 kg; M725f; 87.1 kg; M725z: 92.35 kg; M725z+: 1(ac) ; SSL/TLS, 802.1X authentication (EAP- PEAP, EAP-TLS ng IPsec Plug-in L; SFC. Recommended operating temperature: 10 to 3 to 90% RH B(A) 4 dB(A) 10 (Class A); EN 61000-3-2 :2006 +A1:2009 +A2:2009;	ated Home button (for quick return to the trion:890 watts (active print/copy), 39 wa e printer is sold. Do not convert operating 252: 745 x 681 x 1192 mm; M7252+: 74 mm; j2: 42 kg; Packaged: M725dn: 68.6 kg; M j, IPP over TLS, IPsec/Firewall with Certific 2.5%C. Operating humidity: 20 to 80% RH EN 61000-3-3 :2008; EN 55024:1998+/	e Home menu); Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption g voltages; this will damage the printer and void the product warranty. Values 15 x 681 x 1192 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 1725f: 105.4 kg; M725z: 113 kg; M725z+: 122 kg; cate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for I. Operating humidity recommended: 30 to 70% RH. Storage temperature: 0			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	space; operating system comp hardware system requirement: Windows Installer, HP PCL 6 die 20.3 cm touchscreen, LCD (colo Requirements:Input voltage: 2 (TEC): 4.39 KWh/Week. Power subject to change, see hp. com, Out of package: M725dn : 614 856 x 760 x 1522 mm; M7253 . Out of package: M725dn : 614 HP Web Jetadmin, HP Utility (M Management security: SNMPv; WJA-10 IPsec Configuration us Operating temperature: 10 to 5 to 60% - Storage humidity: 10 Acoustic Power Emissions: 6.8 Acoustic Pressure Emissions: 6.8 Acoustic Pressure Emissions: 6.9 CISPR 22:2008 / EN 55022:20 approvals as required by indivi	 c, CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emulur graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/ 10%), SO/60 Hz (+/ 2 Hz). Consump equirements are based on the country/region where th support for current information. x 649 x 609 mm; M7255: 745 x 681 x 1160 mm; M72 x 649 x 609 mm; M7255: 745 x 681 x 1160 mm; M72 x 649 x 609 mm; M7252: 92.35 kg; M7252+: 1(ac) x 556 x 760 x 1553 nm; M7252: 92.35 kg; M7252+: 1(c) ac) x 5SL/TLS, 802.1X authentication (EAP- PEAP, EAP-TLS ng IPsec Plug-in 2.5% C. Recommended operating temperature: 10 to 3 to 90% RH B(A) d (Class A); EN 61000-3-2 :2006 +A1:2009 +A2:2009 ual countries. Regulatory standards: IEC 60950-1:200 	ated Home button (for quick return to the tion:890 watts (active print/copy), 39 wa le printer is sold. Do not convert operatin 252: 745 × 681 × 1192 mm; M7252+: 74 mm; D2:42 kg; Packaged: M725dn: 68.6 kg; M), IPP over TLS, IPsec/Firewall with Certific 2.5%C . Operating humidity: 20 to 80% RH EN 61000-3-3 :2008; EN 55024:1998+/4 5 * A1; EN60950-1: 2006 * A11:2009 * A1	Home menu); Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption g voltages; this will damage the printer and void the product warranty. Values 45 x 681 x 1192 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 1725f: 105.4 kg; M725z: 113 kg; M725z+: 122 kg; ::ate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for I. Operating humidity recommended: 30 to 70% RH. Storage temperature: 0 A1+A2; EMC Directive 2004/108/EC with CE Marking (Europe); other EMC ::2010 +A12::2011; IEC 60825-1:2007 (Class 1 Laser/Led Product); EN			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	space; operating system comp hardware system requirement: Windows Installer, HP PCL 6 die 20.3 cm touchscreen, LCD (colo Requirements:Input voltage: 2 (TEC): 4.39 KWh/Week. Power subject to change, see hp. com, Out of package: M725dn : 614 856 x 760 x 1522 mm; M7253 . Out of package: M725dn : 614 HP Web Jetadmin, HP Utility (M Management security: SNMPv; WJA-10 IPsec Configuration us Operating temperature: 10 to 5 to 60% - Storage humidity: 10 Acoustic Power Emissions: 6.8 Acoustic Pressure Emissions: 6.8 Acoustic Pressure Emissions: 6.9 CISPR 22:2008 / EN 55022:20 approvals as required by indivi	c) CD-ROM/DVD-ROM or Internet, see apple.com crete driver, Mac Software Link to Web (Postscript emul ur graphics); rotating (adjustable angle) display; illumin 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consump equirements are based on the country/region where th Support for current information. x 649 x 609 mm; M725f: 745 x 681 x 1160 mm; M7; is 856 x 760 x 1553 mm; M725z+: 856 x 760 x 1553 1 11 kg; M725f: 87.1 kg; M725z: 92.35 kg; M725z+: 1(ac) x; SSL/TLS, 802.1 X authentication (EAP- PEAP, EAP-TLS ng IPsec Plug-in i2.5°C. Recommended operating temperature: 10 to 3 to 90% RH B(A) 4 dB(A) 10 (Class A); EN 61000-3-2 :2006 +A1:2009 +A2:2009 fual countries. Regulatory standards: IEC 60950-1:200 ED Product); GS Certificate (Germany, Europe); IEC 624	ated Home button (for quick return to the tion:890 watts (active print/copy), 39 wa le printer is sold. Do not convert operatin 252: 745 × 681 × 1192 mm; M7252+: 74 mm; D2:42 kg; Packaged: M725dn: 68.6 kg; M), IPP over TLS, IPsec/Firewall with Certific 2.5%C . Operating humidity: 20 to 80% RH EN 61000-3-3 :2008; EN 55024:1998+/4 5 * A1; EN60950-1: 2006 * A11:2009 * A1	 Home menul; Easy Access USB; Hardware Integration Pocket tts (ready), 6.5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption g voltages; this will damage the printer and void the product warranty. Values 15 x 681 x 1192 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 1725f: 105.4 kg; M725z: 113 kg; M725z+: 122 kg; cate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for I. Operating humidity recommended: 30 to 70% RH. Storage temperature: 0 A1+A2; EMC Directive 2004/108/EC with CE Marking (Europe); other EMC 			

© Copyright 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors, or omissions contained herein.



Published in EMEA 04/13 4AA4-5715EEE