# HP LaserJet M2727 MFP series





If it's power and functionality you want, then this HP MFP is the device for you. Fast speeds of 26 ppm, consistently great print quality, networking, a new fax solution, and a host of additional features mean great improvements in productivity.



HP LaserJet M2727nf MFP



HP LaserJet M2727nfs MFP

The ideal tool for small and medium businesses and small workteams in larger enterprise companies who need a powerful HP MFP to create high volume multi-copy/multi-print jobs while saving time, space, and money.

#### Achieve more with a high-performance HP MFP that delivers very fast print and copy speeds.

Be more productive with print and copy speeds up to 26 ppm. Your first printed is ready when you are, in less than 10 seconds from PowerSave mode, thanks to No-wait Instant-on Technology, and copy jobs begin quickly too. The high depth-of-focus CCD scanner with instant-on LED illumination captures high quality images, 3-D objects and double page spreads without visible black lines at the binding.

Print demanding jobs with HP PCL 5, HP PCL 6, and HP postscript level 3 emulation print drivers.

### Get the functionality you need with this full-featured HP MFP which keeps up with your fast pace.

Enhance communications with a fax solution that includes private receive and FaxTel<sup>1</sup> and digital storage for up to 600 pages. Enjoy fewer interruptions with a 500-sheet maximum input capacity<sup>2</sup>. Get the job done faster with copy collation, two-sided printing and an electronic stapler<sup>3</sup>. Share resources with fast, reliable networking. Handle large, complex jobs easily with a quick return to the print job's application thanks to a 450 MHz processor and 64 MB memory, expandable to 320 MB.

#### Count on this highly reliable HP MFP for great results and easy, trouble-free printing.

Ensure easy printing and consistently great results enabled by intelligence built into Original HP LaserJet cartridges. Easily keep up to 15 HP laser devices operating smoothly with HP Easy Printer Care Software 2.0<sup>4</sup>. Experience expanded support for numerous operating systems, including Windows Vista. Get more from your printer with a USB 2.0 Hi-speed port which enables access to third-party solutions. Protect your MFP from theft with the Kensington Lock that is included with device.

- <sup>2</sup> The HP LaserJet M2727nf MFP comes standard with one 250-sheet input tray and the option for an additional 250-sheet tray (Q7556A)
- The HP LaserJet M2727nfs MFP comes standard with two 250-sheet input trays
- <sup>3</sup> Included on the HP LaserJet M2727nfs MFP only
- 4 Programme features and availability may vary by country
- For more information, visit www.hp.com/learn/suresupply.

<sup>&</sup>lt;sup>1</sup> A handset is required to use the FaxTel feature

Technical specifi	echnical specifications					Ordering information	
Print technology	Monochrome Laser			CB532A	HP LaserJet M2727nf MF		
Print speed	Up to 26 ppm. First page out black: < 10.0 sec Warm-up time: less than 38 sec min Exact speed varies depending on the system					power cord(s), HP LaserJe	
•	configuration, software program and document complexity.					Q7553A Black Prin Cartridge, Getting Started	
Processor	450 MHz. Motorola Coldfi	1Hz. Motorola Coldfire® V5e					
Memory	64 MB. Expandable to 320	MB through one 144-pin DDR2 DIMM slot				Guide, support flyer, CD	
Print	Quality	REt, HP FastRes, HP ProRes 1200, HP TrueRes				containing device softwar and electronic User's Guide	
	Resolution	Up to 1200 x 1200 dpi				control panel faceplate	
	Printer languages	HP PCL 6, HP PCL 5e, HP Postscript Level 3 emulation				Readiris PRO tex	
	Economical printing	Economode print quality setting prints text with less toner, two-sided printing and N-up printing				recognition software, AD	
	- ( // )	(saves paper)				input support, phone cord(s	
	Typefaces/fonts	45 scalable TrueType, 35 Postscript Top: 4 mm. Left: 4 mm. Right: 4 mm. Bottom: 4 mm				HP LaserJet M2727nfs MF	
r	Print margins (mm)				As HP LaserJet M2727r		
Fax	Modem speed	33.6 Kbps (3 sec per page) Telecom: ES 203 021, FCC Part 68, Industry Canada CS03, NOM-151-SCTI-1999 (Mexico),				MFP plus stapler and	
	Telecom compliance					additional 250-sheet inpu	
		PTC-200 (New Zealand), AS/ACIF S002: 2001 (Australia), IDA PSTN1 (Singapore), TPS002-01 (Malaysia), IG 0005-11 (Taiwan), HKTA 2011 (Hong Kong SAR), YD514, YD/T589, YD703,				tra	
		GB3382 (China)					
	Fax memory	Up to 600 pages					
	Fax resolution	Standard: 203 x 98 dpi. Fine: 203 x 196 dpi. Superfine: 300 x 300 dpi (no halftone)					
	Quick dialing	Up to 120 (119 group dials). 16					
Scan	Туре	Flatbed, ADF. Colour scanning: Yes					
	Scan resolution	Optical: Up to 1200 dpi. Enhanced: Up to 19200 dpi					
	Bit depth	24-bit					
	Grey scale levels	256					
	Twain version	TWAIN compatible Version 1.9					
	Scannable area	Minimum media size: No minimum. Maximum media size: 216 x 297 mm					
	Margins for scanned items	Left: 4. Top: 4. Right: 4. Bottom: 4					
Сору	Copy speed	Up to 26 cpm (single sheet on flatbed, multiple copies, ADF copy speed is up to 17.5 cpm)					
	Copy resolution	600 x 600 dpi					
	Multiple copies Reduce/enlarge	Up to 99 25 to 400%					
Media handling	Input:	Capacity	Weight	Size			
media nanaling	Tray 1	sheets: 50,	60 to 163 g/m <sup>2</sup>	A4, A5, A6, B5 (JIS), C5, DL, 16K,			
	ildy i	transparencies: 10	0	Postcard (JIS), Double Postcard (JIS);			
		envelopes: 10	,	76 x 127 to 216 x 356 mm			
	Tray 2	sheets: 250	60 to 120 g/m <sup>2</sup>	A5, B5 (JIS), A4; 148 x 210 to			
	,		5.	216 x 356 mm			
	Tray 3	sheets: 250	60 to 120 g/m <sup>2</sup>	A5, B5 (JIS), A4; 148 x 210 to			
	-		-	216 x 356 mm			
	ADF	sheets: 50	$60 \text{ to } 90 \text{ g/m}^2$	A4, A5, 127 x 127 to 216 x 381 mm			
	Output:	Sheets: Up to 125. Envelopes: Up to 10. Transparencies: Up to 10					
	Duplex printing:	Automatic (standard)					



# **Technical specifications**

## Ordering information

- Media types	Paper (bond, colour, heavy, letterhead, light, plain, preprinted, prepunched, recycled, rough), envelopes, transparencies, labels,		Accessories	
Interface and connectivity	cardstock 10/100Base-T Ethernet, Hi-Speed USB (compatible with USB 2.0 specifications). Optional: None		HP 64MB DDR2 144pin	
Operating systems compatibility	Windows® 2000; Windows® Server 2003; Certified for Windows Vista™; Windows® XP Home; Windows® XP Media Center;		SDRAM DIMM	
operating systems companying	Windows® XP Professional; Windows® XP Professional x64; Windows® XP Tablet PC; Mac OS X v10.3 or higher; Novell®	CB422A	HP 128MB DDR2 144pin	
	NetWare 3.2, 4.2, 5.x, 6; HP-UX 10.20, 11.x; RED HAT Linux 6.x or higher; SUSE Linux 6.x or higher; Solaris® 2.5x, 2.6, 7, 8,		SDRAM DIMM	
	9, 10 (SPARC®); AIX 3.2.5 or higher; MPE-iX; Citrix® MetaFrame®; Terminal Services. Latest drivers available from	CB423A	HP 256MB DDR2 144pin	
	http://www.hp.com		SDRAM DIMM	
Network operating systems compatibility	Via On Board 10/100 Ethernet connection, supports TCP/IP based solutions: Windows® 2000, Windows® XP Home,		Supplies	
	Windows® Professional, Windows® XP Professional x64, Windows® Server 2003, Windows Vista™ Ready, Windows Vista™-64; Novell® NetWare NDPS services via TCP/IP only on 3.2, 4.2, 5.x, 6.x; HP Gateway (TCP/IP raw only) and Novell®	Q7553A	HP LaserJet Q7553A Black	
	LPD gateway; Mac OS 10.3 or higher; Bonjour discovery supported; RED HAT Linux 6.x or higher; SUSE Linux 6.x or higher;		Print Cartridge with Smart	
	HP-UX 10.20, 11.x; Solaris® 2.5x, 2.6, 7, 8, 9, 10 (SPARC® systems only); IBM® AIX 3.2.5 or higher; MPE-iX; Citrix®		Printing Technology	
	MetaFrame®; Windows® Terminal Services		3,000 standard pages in	
Minimum system requirements	Windows® 2000, Windows® Server 2003: any Pentium® II processor or higher, 64 MB RAM, 250 MB hard disk space, SVGA		accordance with ISO/IEC	
, ,	800 x 600 with 16-bit colour display, Internet Explorer 5.5 or higher (full install), CD-ROM drive, USB port (print driver, scan	07550	19752	
	driver only); Windows® XP-32 Home, Windows® XP-32 Professional: any Pentium® II processor (Pentium® III or higher	Q7553X	HP LaserJet Q7553X Black Print Cartridge with Smart	
	recommended), 128 MB RAM, 250 MB hard disk space, SVGA 800 x 600 with 16 bit colour display, Internet Explorer 5.5 or		Printing Technology	
	higher (full install), CD-ROM drive, USB port; Windows® XPx64: any Pentium® III processor (Pentium® III or higher		7,000 standard pages in	
	recommended), 128 MB RAM, 250 MB hard disk space, SVGA 800 x 600 with 16-bit colour display, Internet Explorer 5.5 or		accordance with ISO/IEC	
	higher (full install), CD-ROM drive, USB port; Windows Vista™.32 Home, Windows Vista™.32 Professional: 1 GHz processor, 512 MB RAM, check user quide for minimum hard drive space, SVGA 800 x 600 with 16-bit colour display, Internet Explorer		19752	
	5.5 or higher (full install), CD-ROM drive, USB port; Windows Vista™-64: 1 GHz processor, 512 MB RAM , check user guide for		84 I' I'	
	minimum hard drive space, SVGA 800 x 600 with 16-bit colour display, Internet Explorer 5.5 or higher (full install), CD-ROM	CU10110	Media supplies	
	drive, USB port. Mac OS X v10.3 or higher; G3 (500 MHz), G4, G5, or Intel® processors; 512 MB RAM; 100 MB disk space;	CHP110	HP Office Paper 80 g/m²-A4/210 x 297	
	USB or network port; CD-ROM drive		mm/500 sht	
Standard software	HP Toolbox FX, HP LaserJet Scan, TWAIN 1.9 or WIA scanner drivers, HP LaserJet Fax, HP Fax Setup Wizard, Readiris PRO text	CHP810	HP Recycled Paper 80	
	recognition software (not installed with other software, separate installation required), printer drivers (HP PCL 6, HP Postscript		g/m <sup>2</sup> -A4/210 x 297	
	Level 3 emulation), installer/uninstaller, HP Director (Macintosh). Drivers on the web: Installer, print drivers, HP Send Fax, HP			
	Scan software, HP Toolbox FX for management and support, Readiris PRO text recognition software, HP Software Update, HP Web Jetadmin, Enterprise Installer	CHP210	HP Printing Paper 80	
Control panel	2-line LCD text display, alphanumeric buttons, navigational buttons plus 3 LEDs (Setup, left, enter, right, cancel), fax buttons plus 1		g/m²-A4/210 x 297	
	LED (start fax, phonebook, volume, resolution, redial, one touch keys, shift), copy buttons plus 2 LEDs (start copy, 2 sided,		mm/500 sht	
	reduce/enlarge, lighter/darker, collate, quality, paper, number of copies, current settings), 2 scan buttons (start scan, scan to).	Connectivity		
Power	Requirements: Input voltage 110 to 127 VAC (+/-10%), 50/60 Hz (+/-2 Hz), 4.5 amp; 220 to 240 VAC (+/-10%), 50/60	C6518A	HP USB Cable, 2m	
	Hz (+/- 2 Hz), 2.6 amp. Consumption: 410 watts maximum (active/printing), 410 watts maximum (active/copy or scan), 13	C6520A	HP USB Cable, 3m	
	watts maximum (ready/sleep), 0.1 watts maximum (off)	COJZUA		
Dimensions (w x d x h)	Out of package: M2727nf: 500 x 406 x 457 mm ; M2727nfs: 500 x 406 x 546 mm . Packaged: M2727nf: 596 x 496 x 595		Service & support	
we + 1.	mm; M2727nfs: 596 x 496 x 785 mm	H5471E H	P Care Pack, Unit Exchange,	
Weight	Out of package: M2727nf: 17.2 kg ; M2727nfs: 20.5 kg . Packaged: M2727nf: 22 kg ; M2727nfs: 25.91 kg	3 years		
Printer management	HP Toolbox FX, HP Web Jetadmin, embedded Web server (Mac only)	_ UD910E HP Care Pack, Next Business		
Operating environment	Operating temperature: 15 to 32.5° C. Recommended operating temperature: 15 to 32.5° C. Operating humidity: 10 to 80%		inge, 2 years D.Com Daala Nlout Duringer	
	RH. Operating humidity recommended: 10 to 80% RH. Storage temperature: -20 to 40° C. Storage humidity: 0 to 95% RH. Noise level per ISO 9296: sound power: lwAd 6.4 B(A) (printing at 27 ppm), 6.9 B(A) (ADF copy/print at 27 ppm), inaudible		H5478E HP Care Pack, Next Business Day On-Site response, 3 years	
	(ready). Sound pressure: LpAm 50.4 dB(A) (active/printing), 55.4 B(A) (active/copy or scan)		UD911E HP Care Pack, Next Business	
Certifications	CISPR 22: 2005/EN 55022: 2006-Class B; EN 61000-3-2: 2000+A2; EN 61000-3-3: 1995+A1; EN 55024: 1998+A1+A2;	Day On-Site response, 3 years		
cermications	FCC Title 47 CFR, Part 15 Class B 2/ICES-003, Issue 3; GB9254-1998. Regulatory standards: IEC 60950-1: 2001/EN H2649PE HP Ca			
	60950-1: 2001+A11; IEC 60825-1: 1993+A1: 1997+A2: 2001/EN 60825-1: 1994+A1: 2002+A2: 2001 (Class 1	C 60825-1: 1993+A1: 1997+A2: 2001/EN 60825-1: 1994+A1: 2002+A2: 2001 (Class 1 Next Business Day On Site response		
	Laser/LED Product); GB4943-1995. ENERGY STAR: Yes	year		
Warranty	One-year limited warranty		HP Care Pack, Post Warranty,	
			inge, 1 year	
		-	alata Itat af assaulta a	

ge, 1 year For a complete list of supplies, accessories and services, please refer to http://www.hp.com

http://www.hp.com/uk



© Copyright Hewlett-Packard Development Company, L.P. 2007. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

