HP LaserJet 5200 Printer series



Designed to deliver efficiency and versatility, this powerful wide-format A3+ monochrome laser printer is flexible and easily manageable to meet your office printing needs.



HP LaserJet 5200 Printer



HP LaserJet 5200tn Printer



HP LaserJet 5200dtn Printer Businesses and public sector organisations with small to medium-sized workteams who need to print oversized documents such as engineering designs, CAD/CAM drawings, marketing collateral proofs, and financial spreadsheets, and who also want to get the most value from their black-and-white printer by having A4 and wide-format A3 capabilities in a single device.

Get perfect results on media up to A3+ from this efficient monochrome HP LaserJet printer.

- Get outstanding image quality, crisp text, smooth greyscales and deep blacks with HP ProRes 1200 (1200 x 1200 dpi at full engine speed)
- Work efficiently with fast print speeds up to 35 ppm and a first page out in less than 10 seconds
- Process complex print jobs easily with a 460 MHz processor and expandable memory up to 512 MB RAM
- Rely on industry-leading networking* for easy sharing via the HP Jetdirect embedded print server or connect to a PC via
 a parallel or Hi-Speed USB 2.0 port.

Supporting a wide range of solutions and media sizes, this printer keeps pace with your business.

- CompactFlash™ support increases accessibility to a wide range of third-party solutions such as intelligent e-forms and barcode printing
- Use the available EIO slot to enhance productivity with the HP high-performance EIO hard disk
- A3+ printing capabilities expand your printable area, enabling you to produce marketing proofs, architectural plans, financial ledgers and spreadsheets easily
- Print more efficiently with an optional 500-sheet input tray** and a two-sided printing unit***.

Make your job easier with this simple and intuitive printer which is both easy to use and manage.

- HP Web Jetadmin (for IT professionals) or HP Easy Printer Care Software (for end users and office managers) help to remotely install, configure, update and manage your network peripherals
- The HP Universal Print Driver Series lets you employ one print driver giving end users basic access to most HP printers via HP PCL 5 or HP Postscript emulation driver versions
- Easily replace the HP all-in-one print cartridge that assures quality and reliability with its HP Smart printing technology****.
- * Networking is standard on HP LaserJet 5200tn, and 5200dtn printers. It is optional on HP LaserJet 5200 printer. ** The 500-sheet input tray comes standard on HP LaserJet 5200tn and 5200dtn printers. It is an optional accessory on HP LaserJet 5200
- ** The 500-s printer.

*** The two-sided printing unit is standard on the HP LaserJet 5200dtn. It is an optional accessory on HP LaserJet 5200, and 5200tn printers.

**** Using genuine HP supplies ensures availability of all HP printing features.



Drint to do al a au	Manachara	200F			075 101	
Print technology	Monochrome Laser			Q7543A	HP LaserJet 5200 Printe	
Print speed	A4: Up to 35 ppm. A3: Up to 18.5 ppm First page out: Less than 10 sec. (Instant-on Technology virtually eliminating warm-up time - from cold or warm start) Exact speed varies depending on the system configuration, software program and document complexity.				Q7545A Q7546A	HP LaserJet 5200tn Printe HP LaserJet 5200dtn Printe
Processor	460 MHz. MIP		shiguration, software program and c			Accessories
Memory	5200: 48 MB. 5200th: 64 MB. 5200dth: 128 MB. Expandable to 512 MB RAM via a single industry-standard 100-pin DDR				J6073G	HP High-Performance EIC
Meniory	DIMM slot					Hard Dis
	Optional, 20 GB HP High-performance EIO hard disk			Q7548A	HP LaserJet 500-sheet Inpu	
Print quality	Best/normal: Up to 1200 x 1200 dpi. Draft: Up to 600 x 600 dpi					Tray
Printer languages	HP PCL 6, HP P	CL 5e, HP Postscript Level 3 emu	lation		Q7549A	HP LaserJet Auto Duple
Economical printing		ves toner), return to powersave i ng (saves paper)	mode after print job with the instant-	on fuser technology (saves electricity), duplex		Uni
Typefaces/fonts	103 built-in scalable PCL, 93 internal PS					Supplies
Duty cycle	Up to 65,000 pages per month				Q7516A	HP LaserJet Q7516A Black
Print margins		3.4 mm. right: 4.9 mm. bottom	: 6 mm			Print Cartridge with Smart Printing Technology
Media handling	Input	Capacity	Weight	Size		12,000 pages according to
	Tray 1	Up to 100 sheets	60 to 199 g/m ²	A3, A4, A5, A6, B4, B5, B6, RA3,		ISO/IEC 19752
		·	-	8K, 16K, envelopes (Monarch, C5,		6
				DL, B5, #10), custom: 76.2 x 127		Connectivity
			(0. <u>100</u> (0	mm to 312 x 470 mm	J7934G	HP Jetdirect 620n Fast
	Tray 2	Up to 250 sheets	60 to 120 g/m ²	A3, A4, A5, B5, B4, custom: 76.2	170400	Ethernet Print Server
	Tray 3*	Up to 500 sheets	60 to 120 g/m ²	x 127 mm to 297 x 431.8 mm A3, A4, A5, B5, B4, custom: 76.2	J7942G	HP Jetdirect en3700 External Print Server (USB,
	nuy o	op to 500 sileets	00 10 120 g/ III	x 127 mm to 297 x 431.8 mm		10/100TX
	Output:	Up to 250 sheets. Up to 3	50 envelopes. Up to 250 transparen		J7951G	HP Jetdirect ew2400
	Duplex printing	: 5200: Automatic (option	al). 5200tn: Automatic (optional). 52	200dtn: Automatic (standard)	17,510	802.11g Wireless and Fast
Media types	Paper (plain, pr cardstock, vellu		d, bond, recycled, colour, rough, tou	ghpaper), transparencies, labels, envelopes,		Ethernet External Print Server
Interface and connectivity	5200: Hi-Speed USB 2.0 port, IEEE-1284 parallel port, one open EIO slot. 5200tn: Hi-Speed USB 2.0 port, IEEE-1284 parallel			J7960G	HP Jetdirect 625n Internal	
	port, one open EIO slot, HP Jetdirect Fast Ethernet embedded print server. 5200dtn: Hi-Speed USB 2.0 port, IEEE-1284 parallel			3770000	Print Server (EIO,	
	port, one open EIO slot, HP Jetdirect Fast Ethernet embedded print server. Optional: HP Jetdirect Internal Print Servers, HP					10/100/1000TX
	Jetdirect External Print Servers, HP Wireless Print Servers			J7961G	HP Jetdirect 635n	
Operating systems compatibility	Windows® 98, Me, 2000, XP Home, XP Professional, Server 2003; Mac OS X, 10.2, 10.3, 10.4, and higher Optional: Most recent printer drivers for all supported operating systems are available on hp.com/support/IJ5200					IPv6/IPsec Internal Print Server (EIO,
Network operating systems compatibility	Via HP Jetdirect print servers: Windows® 98, 2000, XP Home, XP Professional, Server 2003; NetWare; UNIX; AppleTalk; Linux; HP-UX; LocalTalk					10/100/1000TX
Minimum system requirements	Pentium® 90, 16 MB RAM (Windows® 98); Pentium 150, 32 MB RAM (Windows Me); 133 MHz processor, 64 MB RAM				Memory	
	(Windows 2000); 233 MHz processor, 64 MB RAM (Windows XP Home, XP Professional); 550 MHz processor, 128 MB RAM				Q7713A	HP 32 MB 100-pin DDR
	[Windows Server 2003 (standard edition)]; 220 MB available hard disk space, CD-ROM drive or Internet connection, IEEE-1284					DIMM
	compliant bidirectional parallel port, USB port. 160 MB available disk space, Mac OS X 10.2 or above, CD-ROM drive or				Q7715A	HP 64 MB 100-pin DDR
Software	Internet connect			right level 2 Freedoting Administrate of the series		DIMM
Software	Print drivers and installation software on CD-ROM (HP PCL 6, HP PCL 5e, HP Postscript Level 3 Emulation, Macintosh software, PostScript Printer Description)				Q7718A	HP 128 MB 100-pin DDR DIMM
	32 x 160 backlit graphical display; 8 buttons (Back arrow, Down arrow, Help, Menu, Pause job, Start, Status, Up arrow); 3 LEDs					
Control panel			Back arrow, Down arrow, Help, Mer	nu, Pause job, Start, Status, Up arrow); 3 LEDs	Q7719A	HP 256 MB 100-pin DDR
-	(Attention, Data	i, Ready)			Q7719A	
Printer management	(Attention, Data HP Embedded '	ı, Ready) Web Server, HP Web Jetadmin,	HP Easy Printer Care Software, HP U	Universal Print Driver Series	Q7719A Q7720A	HP 256 MB 100-pin DDR
Printer management	(Attention, Date HP Embedded Requirements: I	ı, Ready) Web Server, HP Web Jetadmin, nput voltage: 110 to 127 VAC (HP Easy Printer Care Software, HP (+/- 10%), 50/60 Hz (+/- 2 Hz); 22	Universal Print Driver Series 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2		HP 256 MB 100-pin DDR DIMM
Printer management	(Attention, Data HP Embedded Requirements: I Hz). Consumpti	ı, Ready) Web Server, HP Web Jetadmin, nput voltage: 110 to 127 VAC (ion: 5200: 550 watts maximum	HP Easy Printer Care Software, HP l +/- 10%), 50/60 Hz (+/- 2 Hz); 22 (printing), 27 watts (standby), 7 wa	Universal Print Driver Series 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 tts (powersave), 0.5 watts (off). 5200tn: 600		HP 256 MB 100-pin DDR DIMM HP 512 MB 100-pin DDR DIMM
Printer management	(Attention, Data HP Embedded Requirements: I Hz). Consumpti watts maximum	r, Ready) Web Server, HP Web Jetadmin, nput voltage: 110 to 127 VAC (ion: 5200: 550 watts maximum (printing), 27 watts (standby), 7	HP Easy Printer Care Software, HP I +/- 10%), 50/60 Hz (+/- 2 Hz); 22 (printing), 27 watts (standby), 7 wat 7.5 watts (powersave), 0.5 watts (off	Universal Print Driver Series 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2	Q7720A	HP 256 MB 100-pin DDR DIMM HP 512 MB 100-pin DDR DIMM Service & support
-	(Attention, Data HP Embedded Requirements: I Hz). Consumpti watts maximum 27 watts (stand Out of package	ı, Ready) Web Server, HP Web Jetadmin, nput voltage: 110 to 127 VAC (on: 5200: 550 watts maximum (printing), 27 watts (standby), . by), 7.5 watts (powersave), 0.5 e: 5200: 490 x 563 x 275 mm.	HP Easy Printer Care Software, HP I +/- 10%), 50/60 Hz (+/- 2 Hz); 22 (printing), 27 watts (standby), 7 wai 7.5 watts (powersave), 0.5 watts (off) watts (off) 5200tn: 490 x 600 x 405 mm. 520	Universal Print Driver Series 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 tts (powersave), 0.5 watts (off). 5200tn: 600). 5200dtn: 600 watts maximum (printing), 00dtn: 490 x 600 x 405 mm	Q7720A U3469A/I business d	HP 256 MB 100-pin DDR DIMM HP 512 MB 100-pin DDR DIMM Service & support E HP Care Pack, next ay on site, 3 years
Printer management Power Dimensions (w x d x h)	(Attention, Data HP Embedded Requirements: I Hz). Consumpti watts maximum 27 watts (stand Out of package Packaged: 520	i, Ready) Web Server, HP Web Jetadmin, nput voltage: 110 to 127 VAC (on: 5200: 550 watts maximum (printing), 27 watts (standby), j, 7.5 watts (powersave), 0.5 :: 5200: 490 x 563 x 275 mm. 0: 799 x 598 x 497 mm. 52001	HP Easy Printer Care Software, HP L +/- 10%), 50/60 Hz (+/- 2 Hz); 22 (printing), 27 wats (standby), 7 wat 7.5 watts (powersave), 0.5 watts (off watts (aff) 5200in: 490 x 600 x 405 mm. 520 in: 799 x 600 x 731 mm. 5200dtn:	Universal Print Driver Series 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 tts (powersave), 0.5 watts (off). 5200tn: 600). 5200dtn: 600 watts maximum (printing), 00dtn: 490 x 600 x 405 mm	Q7720A U3469A/I business d U3470A/I	HP 256 MB 100-pin DDR DIMM HP 512 MB 100-pin DDR DIMM Service & support E HP Care Pack, next ay on site, 3 years E HP Care Pack, 4h 13x5 on
Printer management Power Dimensions (w x d x h)	(Attention, Data HP Embedded Requirements: I Hz). Consumpti watts maximum 27 watts (stand Out of package Packaged: 520 Out of package	1, Ready) Web Server, HP Web Jetadmin, nput voltage: 110 to 127 VAC (on: 5200: 550 watts maximum (printing), 27 watts (standby), 7, by), 7.5 watts (powersave), 0.5 is: 5200: 490 x 563 x 275 mm. 0: 799 x 598 x 497 mm. 52001 is: 5200: 20.2 kg. 5200tn: 30.2	HP Easy Printer Care Software, HP (+/- 10%), 50/60 Hz (+/- 2 Hz); 22 (printing), 27 watts (standby), 7 wat 7.5 watts (powersave), 0.5 watts (off) watts (off) 5200h: 490 x 600 x 405 mm. 520 h: 799 x 600 x 731 mm. 5200dth: 2 kg. 5200dth: 33.1 kg	Universal Print Driver Series 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 tts (powersave), 0.5 watts (off). 5200tn: 600). 5200dtn: 600 watts maximum (printing), 00dtn: 490 x 600 x 405 mm	Q7720A U3469A/I business d U3470A/I site respor	HP 256 MB 100-pin DDR DIMM HP 512 MB 100-pin DDR DIMM Service & support E HP Care Pack, next ay on site, 3 years
Printer management Power Dimensions (w x d x h) Weight	(Attention, Data HP Embedded Requirements: I Hz). Consumpti watts maximum 27 watts (stand Out of package Packaged: 520 Out of package	r, Ready) Web Server, HP Web Jetadmin, nput voltage: 110 to 127 VAC (on: 5200: 550 watts maximum (printing), 27 watts (standby), 7, by), 7.5 watts (powersave), 0.5 s: 5200: 490 x 563 x 275 mm. 0: 799 x 598 x 497 mm. 52001 s: 5200: 20.2 kg. 5200tn: 30.2 0: 28.9 kg. 5200tn: 42.7 kg. 5	HP Easy Printer Care Software, HP (+/- 10%), 50/60 Hz (+/- 2 Hz); 22 (printing), 27 watts (standby), 7 wat 7.5 watts (powersave), 0.5 watts (off) watts (off) 5200h: 490 x 600 x 405 mm. 520 h: 799 x 600 x 731 mm. 5200dth: 2 kg. 5200dth: 33.1 kg 200dth: 51.6 kg	Universal Print Driver Series 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 tts (powersave), 0.5 watts (off). 5200hr: 600). 5200dtn: 600 watts maximum (printing),)0dtn: 490 x 600 x 405 mm 799 x 600 x 1026 mm	Q7720A U3469A/I business d U3470A/I site respor UC742A/I	HP 256 MB 100-pin DDR DIMM HP 512 MB 100-pin DDR DIMM Service & support E HP Care Pack, next ay on site, 3 years HP Care Pack, 4h 13x5 on isse, 3 years
Printer management Power	(Attention, Data HP Embedded Requirements: 1 Hz). Consumpti watts maximum 27 watts (stand Out of package Packaged: 520 Out of package Packaged: 520 Operating temp Recommended	, Ready) Web Server, HP Web Jetadmin, nput voltage: 110 to 127 VAC (ion: 5200: 550 watts maximum (printing), 27 watts (standby), 7 by), 7.5 watts (powersave), 0.5 e: 5200: 490 x 563 x 275 mm. 0: 799 x 598 x 497 mm. 52001 e: 5200: 20.2 kg. 5200tn: 32.5 0: 28.9 kg. 5200tn: 42.7 kg. perature: 10 to 32° C. Recomme operating humidity: 25 to 75%	HP Easy Printer Care Software, HP I +/- 10%), 50/60 Hz (+/- 2 Hz); 22 (printing), 27 watts (standby), 7 wai 7.5 watts (off) 5200tn: 490 x 600 x 405 mm. 520 nr. 799 x 600 x 731 mm. 5200dtn: 2 kg. 5200dtn: 33.1 kg 200dtn: 51.6 kg ended operating temperature: 10 to RH. Storage temperature: 0 to 40° C	Universal Print Driver Series 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 tts (powersave), 0.5 watts (off). 5200tn: 600). 5200dtn: 600 watts maximum (printing), 00dtn: 490 x 600 x 405 mm 799 x 600 x 1026 mm 32° C. Operating humidity: 20 to 80% RH. C. Storage humidity: 10 to 80% RH. Noise	Q7720A U3469A/I business d U3470A/I site respor UC742A/I	HP 256 MB 100-pin DDR DIMM HP 512 MB 100-pin DDR DIMM Service & support E HP Care Pack, next ay on site, 3 years E HP Care Pack, 4h 13x5 on se, 3 years E HP Care Pack, installation &
Printer management Power Dimensions (w x d x h) Weight Operating environment	(Attention, Data HP Embedded Requirements: 1 Hz). Consumpti watts maximum 27 watts (stand Out of package Packaged: 520 Out of package Packaged: 520 Operating temp Recommended level per ISO 9	I, Ready) Web Server, HP Web Jetadmin, nput voltage: 110 to 127 VAC (on: 5200: 550 watts maximum (printing), 27 watts (standby), 7 by), 7.5 watts (powersave), 0.5 5: 5200: 490 x 563 x 275 mm. 0: 799 x 598 x 497 mm. 52001 5: 5200: 20.2 kg. 5200tn: 30.2 0: 28 vg. 5200tn: 42.7 kg. 5: serature: 10 to 32° C. Recomme operating humidity: 25 to 75% 296: Sound power: LwAd 6.84	HP Easy Printer Care Software, HP I +/- 10%), 50/60 Hz (+/- 2 Hz); 22 (printing), 27 watts (standby), 7 wai 7.5 watts (powersave), 0.5 watts (off watts (off) 5200tn: 490 x 600 x 405 mm. 520 n: 799 x 600 x 731 mm. 5200dtn: 2 kg. 5200dtn: 33.1 kg 200dtn: 51.6 kg unded operating temperature: 10 to 2 RH. Storage temperature: 0 to 40° C B(A). Sound pressure: LpAm 54 dB(A	Universal Print Driver Series 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 tts (powersave), 0.5 watts (off). 5200tn: 600). 5200dtn: 600 watts maximum (printing), 00dtn: 490 x 600 x 405 mm 799 x 600 x 1026 mm 32° C. Operating humidity: 20 to 80% RH. 2. Storage humidity: 10 to 80% RH. Noise A)	Q7720A U3469A/I business d U3470A/I site respor UC742A/I network co printer	HP 256 MB 100-pin DDR DIMM HP 512 MB 100-pin DDR DIMM Service & support E HP Care Pack, next ay on site, 3 years E HP Care Pack, 4h 13x5 on ise, 3 years E HP Care Pack, installation & onfiguration for 1 network
Printer management Power Dimensions (w x d x h) Weight	(Attention, Data HP Embedded Requirements: 1 Hz). Consumpti watts maximum 27 watts (stand Out of package Packaged: 520 Out of package Packaged: 520 Operating temp Recommended level per ISO 9: Safety certificat (GOST-R50377	I, Řeady) Web Server, HP Web Jetadmin, nput voltage: 110 to 127 VAC (on: 5200: 550 watts maximum (printing), 27 watts (standby), 7. by, 7.5 watts (powersave), 0.5 s: 5200: 490 x 563 x 275 mm. 0: 799 x 598 x 497 mm. 52001 s: 5200: 20.2 kg. 5200tn: 30.2 0: 28.9 kg. 5200tn: 42.7 kg. 5; berature: 10 to 32° C. Recomme operating humidity: 25 to 75% 296: Sound power: LwAd 6.84 ions: EU (CE Mark-Low Voltage	HP Easy Printer Care Software, HP I +/- 10%), 50/60 Hz (+/- 2 Hz); 22 (printing), 27 watts (standby), 7 wat 7.5 watts (powersave), 0.5 watts (off watts (off) 5200tn: 490 x 600 x 405 mm. 520 In: 799 x 600 x 731 mm. 5200dtn: 1 kg. 5200dtn: 33.1 kg 200dtn: 51.6 kg anded operating temperature: 10 to a RH. Storage temperature: 10 to 40° C B(A). Sound pressure: LpAm 54 dB(A Directive 73/23/EEC), Germany (TL	Universal Print Driver Series 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 tts (powersave), 0.5 watts (off). 5200tn: 600). 5200dtn: 600 watts maximum (printing), 00dtn: 490 x 600 x 405 mm 799 x 600 x 1026 mm 32° C. Operating humidity: 20 to 80% RH. C. Storage humidity: 10 to 80% RH. Noise	Q7720A U3469A/I business d U3470A/I site respor UC742A/I network co printer For a com accessorie	HP 256 MB 100-pin DDR DIMM HP 512 MB 100-pin DDR DIMM Service & support HP Care Pack, next ay on site, 3 years HP Care Pack, 4h 13x5 on ise, 3 years HP Care Pack, installation & onfiguration for 1 network plete list of supplies, s and services, please refer
Printer management Power Dimensions (w x d x h) Weight Operating environment	(Attention, Data HP Embedded Requirements: 1 Hz). Consumpti watts maximum 27 watts (stand Out of package Packaged: 520 Out of package Packaged: 520 Operating temp Recommended level per ISO 9 Safety certificat (GOST-R50377 Product EMC certificati 1995/A1; EN	I, Řeady) Web Server, HP Web Jetadmin, nput voltage: 110 to 127 VAC (ion: 5200: 550 watts maximum (printing), 27 watts (standby), . by), 7.5 watts (poversave), 0.5 5200: 490 x 563 x 275 mm. 0: 799 x 598 x 497 mm. 52001 :: 5200: 20.2 kg. 5200tn: 30.2 0: 28.9 kg. 5200tn: 42.7 kg. 5' perature: 10 to 32° C. Recomme operating humidity: 25 to 75% 296: Sound power: LwAd 6.84 ions: EU (CE Mark-Low Voltage), South Africa (IEC 60950-1, IE pens: EMC: CISPR 22: 1993/A1, 55024: 1998/A1, A2; FCC Titl	HP Easy Printer Care Software, HP I +/- 10%), 50/60 Hz (+/- 2 Hz); 22 (printing), 27 watts (standby), 7 wat 7,5 watts (powersave), 0.5 watts (off watts (off) 5200tn: 490 x 600 x 405 mm. 520 nr: 799 x 600 x 731 mm. 5200dtn: 2 kg. 5200dtn: 33.1 kg 200dtn: 51.6 kg ended operating temperature: 10 to 16 RH. Storage temperature: 0 to 40° C B(A). Sound pressure: LpAm 54 dB(A Directive 73/23/EEC), Germany (TL 5C60825-1); FDA-21 CFR Chapter 1 . A2; EN 55022: 1994/A1, A2 Cla	Universal Print Driver Series 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 tts (powersave), 0.5 watts (off). 5200tn: 600). 5200dtn: 600 watts maximum (printing), 00dtn: 490 x 600 x 405 mm 799 x 600 x 1026 mm 32° C. Operating humidity: 20 to 80% RH. 2. Storage humidity: 10 to 80% RH. Noise A) JV-EN60950-1, IEC 60825-1), Russia Subchapter J for lasers); Class 1 Laser/LED ss B; EN 61000-3-2: 2000; EN 61000-3-3: 3, Issue 4/GB9254-1998, GB17625.1-2003;	Q7720A U3469A/I business d U3470A/I site respor UC742A/I network co printer For a com accessorie	HP 256 MB 100-pin DDR DIMM HP 512 MB 100-pin DDR DIMM Service & support HP Care Pack, next ay on site, 3 years HP Care Pack, 4h 13x5 on ise, 3 years HP Care Pack, installation & onfiguration for 1 network

* optional with 5200, standard with 5200tn/5200dtn

http://www.hp.com/uk/



© 2006 Copyright Hewlett Packard Development Company, L.P. The information contained herein is subject to changes without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing contained herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

