# HP LaserJet Tank MFP 2604 Printer series







## Get high-quality printing with ultra-low cost per page.

- Engineered for high-volume printing pre-filled with 5,000 pages of toner in the tank.
- Help to save on refills with ultra high yield HP Toner Reload Kit.
- Deliver exceptional quality with sharp text and bold blacks, page after page.

## Easy toner refill in 15 sec with Original HP Toner<sup>2</sup> Easily refill Original HP Toner in 15 seconds.<sup>2</sup>

- Less downtime with 2,500 and 5,000 page HP Toner refill options. 1
- The Original HP Toner Reload Kit has an unique design, made with over 75% less plastic.<sup>3</sup>

#### Full features for powerful productivity.

- Speed through multipage documents with automatic two-sided printing.
- Print, scan, and share anytime, anywhere with HP Smart app.<sup>4</sup>
- Low maintenance with long-life up to 50,000 page imaging drum.<sup>5</sup>

## Product walkaround

### LaserJet Tank MFP 2604sdw shown

- 1. 40-sheet auto document feeder
- 2. Sharp text and consistent printing
- 3. Automatic two-sided printing
- 4. HP Smart Advance
- 5. Pre-filled with up to 5000 pages of Original HP Toner
- 6. Up to 50,000 pages Imaging Drum
- 7. Dual-band Wi-Fi® with self reset & Bluetooth LE
- 8. Built-in Fast Ethernet
- 9. Print speed up to 22 ppm (A4)
- 10. HP WOLF Security Essential
- 11. 250-sheet input tray
- 12. Smart-guided buttons



## Series at a glance





Model	HP LaserJet Tank MFP 2604dw Printer	HP LaserJet Tank MFP 2604sdw Printer	
Product number	381V0A	381V1A	
Functions	Print, co	Print, copy, scan	
Print speed	Black (A4, normal): Up to 22 ppm	Black (A4, normal): Up to 22 ppm; Black (A4, duplex): Up to 14 ipm	
Connectivity		Hi-Speed USB (compatible with USB 2.0 specifications); Ethernet 10/100 Base-TX; 802.11a/b/g/n (2.4/5 GHz) Wi-Fi radio + BLE	
Recommended monthly page volume	250-	2500	

## Configurable Items, Accessories, Supplies and Support

Supplies	W1530A HP 153A Black Original Laser Jet Tank Toner Reload Kit (~2,500 pages)		
	W1530X HP 153X Black Original LaserJet Tank Toner Reload Kit (~5,000 pages)		
Service and Support	U04TNE 3 years Standard Exchange (available in All EMEA countries Except Adriatic, Africa, CIS, EEM, Israel, Middle East, Russia, South Africa, Turkey) U04TKE 3 years Next Business Day Exchange (available in Austria, Belgium, Czech Rep, Denmark, Finland, France, Germany, Greece, Ireland, Italy, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Spain, Sweden, Switzerland, UK) U04TSE 3 years Return to Depot (available in Adriatic, Africa, CIS, FEM, Israel, Middle Fast, Russia, South Africa, Turkey)		

## **Technical specifications**

rechnical specifications				
Model	HP LaserJet Tank MFP 2604dw Printer	HP LaserJet Tank MFP 2604sdw Printer		
Product number	381V0A	381V1A		
Control panel	Icon LCD; 3 lights (Media, Lid open, Wifi); 10 buttons (WiFi, Down, Menu, Up, Copy, ID copy, Info, Resume, Cancel, Power)	Icon LCD; 2 lights (Media, Lid open); 10 buttons (WiFi, Down, Menu, Up, Copy, ID copy, Info, Resume, Cancel, Power)		
Print				
Print technology	Laser			
Print speed <sup>1</sup>	Black (A4, normal) Up to 22 ppm; Black (A4, duplex): Up to 14 ipm			
First page out <sup>2</sup>	Black (A4, ready): As fast as 8 sec; Black (A4, sleep): As fast as 8.4 sec			
Print resolution	<b>Black (best)</b> : Up to 600 x 600 dpi ; <b>Technology</b> : 600 x 600 dpi; 600 x 400 dpi			
Monthly duty cycle	Up to 25,000 pages A4; Recommended monthly page volume: 250-2500			
Printer smart software features <sup>3,4</sup>	Automatic duplex printing, HP Auto-On/Auto-Off, HP Smart App			
Standard print languages	PCLmS; URF; PWG			
Print area	Print margins Top: 2 mm, Bottom: 2 mm, Left: 2 mm, Right: 2 mm; Maximum print	area: 215.9 x 355.6 mm		
Duplex printing	Automatic			
Сору				
Copy speed	Black (A4): Up to 14 cpm	Black (A4): DM-EMEA: Up to 14 cpm; DM-NA/AP: Up to 22 cpm		
Scan		I		
Scan speed <sup>5</sup>		Normal (A4): Up to 19 ppm (b&w), up to 10 ppm (color)		
Scan file format	JPEG, RAW(BMP), PNG, TIFF, PDF			
Scanner specifications		s); <b>Scan input modes</b> : HP Smart App; and user applications via Twain; <b>Twain version</b> : n; <b>Optical scan resolution</b> : Up to 600 dpi		
Recommended monthly scan volume	150 to 1500			
Scannable area	Maximum media size (flatbed): 216 x 297 mm; Minimum media size (ADF): 148 x 210 mm Maximum media size (ADF): 216 x 356 mm			
Bit depth/ Grey scale levels	24-bit / 256			
Processor speed	500 MHz			
Connectivity	The second of th			
Standard	Hi-Speed USB (compatible with USB 2.0 specifications; Ethernet 10/100 Base-TX; 8	802.11a/b/g/n (2.4/5 GHz) Wi-Fi radio + BLE		
Wireless	built-in WiFi 802.11b/g/n (2.4/5GHz)			
Mobile printing capability	HP Smart App; Apple AirPrint™; Mopria™ Certified; Wi-Fi® Direct Printing			
Supported network protocols	TCP/IP: IPv4; IPv6; LPD; SLP; Bonjour; WS-Discovery; BOOTP/DHCP/AutoIP; SNMP v	TCP/IP: IPv4; IPv6; LPD; SLP; Bonjour; WS-Discovery; BOOTP/DHCP/AutoIP; SNMP v 1/2/3;HTTP/HTTPS; UDP; IPP		
Network capabilities	Ethernet 10/100Base-TX; built-in WiFi 802.11b/g/n (2.4/5GHz)			
Memory	Standard: 64 MB; Maximum: 64 MB SDRAM			
Media handling				
Number of paper trays	Standard: 1 ; Maximum: 1 Input Tray			
Media types	Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope			
Media size	Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; No.10 Env; C5 Env; DL Env; B5 Env; B5 (JIS); B6 (JIS); 216mm x 340mm; Custom; ADF: A4, Letter, Legal			
Media handling	Standard input: 250-sheet input tray Optional input: Not applicable	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard, 40 sheets		
Media weight	60 to 163 g/m²; <b>ADF</b> : 60 to 90 g/m²			
Input capacity	Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets	Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets		
0	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets			
Output capacity	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does no	or support transparency <b>Maximum.</b> Op to 100 sneets		
Compatible operating systems	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does no Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; n			
	Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; r	nacOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit;		
Compatible operating systems	Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows	macOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  d disk space, Internet connection, Microsoft® Internet Explorer or Edge.;		
Compatible operating systems  Compatible network operating systems	Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available har Mac: Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c	macOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  d disk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required  om		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management	Windows 11; Windows 10; Windows 7; mac0S 10.15 Catalina; mac0S 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available harr Mac Apple® mac0S v10.15 Catalina, mac0S v11 Big Sur, mac0S v12 Montterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protecte default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account lock	macOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; on the space of the spa		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management	Windows 11; Windows 10; Windows 7; mac0S 10.15 Catalina; mac0S 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available harr Mac Apple® mac0S v10.15 Catalina, mac0S v11 Big Sur, mac0S v12 Montterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protecte default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPV1, SNMPV2,	macOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; on the space of the spa		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight	Windows 11; Windows 10; Windows 7; mac0S 10.15 Catalina; mac0S 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available harr Mac Apple® mac0S v10.15 Catalina, mac0S v11 Big Sur, mac0S v12 Montterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protecte default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPV1, SNMPV2, Active FW update, Admin password by default, Cipher & TLS selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)	macOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; on the space of the spa		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight  Printer dimensions (W × D × H)	Windows 11; Windows 10; Windows 7; mac0S 10.15 Catalina; mac0S 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available harr Mac Apple® mac0S v10.15 Catalina, mac0S v11 Big Sur, mac0S v12 Montterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protecte default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account lock	macOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; on the space of the spa		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight  Printer dimensions (W x D x H)  Printer weight	Windows 11; Windows 10; Windows 7; mac0S 10.15 Catalina; mac0S 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available harr Mac Apple® mac0S v10.15 Catalina, mac0S v11 Big Sur, mac0S v12 Montterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protecte default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPV1, SNMPV2, Active FW update, Admin password by default, Cipher & TLS selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)	macOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; as HD; Internet required om  ed EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, cout; Secure Wi-Fi setup		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight  Printer dimensions (W × D × H)	Windows 11; Windows 10; Windows 7; mac05 10.15 Catalina; mac05 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available harr Mac Apple® mac05 v10.15 Catalina, mac05 v11 Big Sur, mac05 v12 Monterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protecte default; OpenSSL version 1.1.1; Enable/disable Network ports; SMPV1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)  Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm	macOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  d disk space, Internet connection, Microsoft® Internet Explorer or Edge.; and HD; Internet required om ed EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, cout; Secure Wi-Fi setup  Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight  Printer dimensions (W x D x H)  Printer weight	Windows 11; Windows 10; Windows 7; mac0S 10.15 Catalina; mac0S 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available harr Mac Apple® mac0S v10.15 Catalina, mac0S v11 Big Sur, mac0S v12 Monterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protected default; OpenSSL version 1.1.1; Enable/disable Network ports; SMMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)  Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg	macOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  d disk space, Internet connection, Microsoft® Internet Explorer or Edge.; and HD; Internet required om ed EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, cout; Secure Wi-Fi setup  Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight  Printer dimensions (W x D x H)  Printer weight  Operating environment	Windows 11; Windows 10; Windows 7; mac05 10.15 Catalina; mac05 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available har Mac: Apple® mac05 v10.15 Catalina, mac05 v11 Big Sur, mac05 v12 Monterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protect default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account loci HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)  Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg  Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH  Temperature: -20 to 60°C  Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A)	MacOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  d disk space, Internet connection, Microsoft® Internet Explorer or Edge.; BB HD; Internet required  om  ed EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SMMPv3, Community password change; Secure defaults, Encrypted data at rest, cout; Secure Wi-Fi setup  Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm  9.5 kg		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight  Printer dimensions (W × D × H)  Printer weight  Operating environment  Storage conditions	Windows 11; Windows 10; Windows 7; mac05 10.15 Catalina; mac05 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available har Mac: Apple® mac05 v10.15 Catalina, mac05 v11 Big Sur, mac05 v12 Monterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protect default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account loci HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)  Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg  Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH  Temperature: -20 to 60°C  Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A)	MacOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  d disk space, Internet connection, Microsoft® Internet Explorer or Edge.; BHD; Internet required om ed EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SMMPv3, Community password change; Secure defaults, Encrypted data at rest, cout; Secure Wi-Fi setup  Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm  9.5 kg  ominal +/- 3Hz (min 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Auto Off/Manual On: 0.05w. Auto-Off/Wake on LAN: 0.5w:		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight  Printer dimensions (W x D x H)  Printer weight  Operating environment  Storage conditions  Acoustics	Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available harr Mac: Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protect default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)  Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg  Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH  Temperature: -20 to 60°C  Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A)  Requirements: 110V - 127V nominal @ +/-10% (min 99V, max 140V), 50 - 60Hz n Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz; Consumption: Active printing: 390w, Ready: 2.7w, Sleep: 0.51y4Kwh/week; Blue Angel: C	MacOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  d disk space, Internet connection, Microsoft® Internet Explorer or Edge.; BHD; Internet required om ed EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SMMPv3, Community password change; Secure defaults, Encrypted data at rest, cout; Secure Wi-Fi setup  Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm  9.5 kg  ominal +/- 3Hz (min 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Auto Off/Manual On: 0.05w. Auto-Off/Wake on LAN: 0.5w:		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight  Printer dimensions (W x D x H)  Printer weight  Operating environment  Storage conditions  Acoustics	Windows 11; Windows 10; Windows 7; mac05 10.15 Catalina; mac05 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available harr Mac: Apple® mac05 v10.15 Catalina, mac05 v11 Big Sur, mac05 v12 Monterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protected default; OpenSSL version 1.1.1; Enable/disable Network ports; SMMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TiLs selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)  Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg  Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH  Temperature: -20 to 60°C  Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A)  Requirements: 110V - 127V nominal @ +/-10% (min 99V, max 140V), 50 - 60Hz n Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz; Consumption: Active printing: 390w, Ready: 2.7w, Sleep: 0.51w, Manual Off: 0.05w Typical Electricity Consumption (TEC) <sup>6</sup> : Energy Star: 0.194Kwh/week; Blue Angel: C Power supply type: Internal (Built-in) power supply  HP Auto-On/Auto-Off Technology; Instant-on Technology  RCM (Australia), TUV and GS Mark (Germany), BSMI (Taiwan), CCC (China), BIS (India approvals, CE Marking, FCC, Energy Star; UL, Paraguay, Chile, Argentina, Indonesia, Electromagnetic emission standard: CISPR3:2:2015 & CISPR 35:2016 /EN5503:2:20 Electromagnetic emission standard: CISPR3:2:2015 & CISPR 35:2016 /EN5503:2:20 Electromagnetic emission standard: CISPR3:2:015 & CISPR 35:2016 /EN5503:2:20 Electromagnetic emission standard: CISPR3:2:015 & CISPR 35:2016 /EN5503:2:20	MacOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  d disk space, Internet connection, Microsoft® Internet Explorer or Edge.; BB HD; Internet required orm  ed EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SMMPV3, Community password change; Secure defaults, Encrypted data at rest, cout; Secure Wi-Fi setup  Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm  9.5 kg  Minimum 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w;  203Kwh/week;  Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w;  C(South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European Singapore, Philippines, etc. 2015 - Class B; EN 61000-3-2:2019; EN 61000-3-3:2013+A1:2019; EN 55035:2017;  TSI EN 301 489-17: V3.1.1; EN 300 328: V2.2.2 / EN301 893 V2.1.1 / EN300 440-1		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight  Printer dimensions (W x D x H)  Printer weight  Operating environment  Storage conditions  Acoustics  Power <sup>7</sup> Energy savings feature technology	Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hare Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protected default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account locid HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)  Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg  Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH  Temperature: -20 to 60°C  Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A)  Requirements: 110V - 127V nominal @ +/-10% (min 99V, max 140V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz; Consumption: Active printing: 390w, Ready; 2.7w, Sleep: 0.51w, Manual Off: 0.05w Typical Electricity Consumption (TEC)®: Energy Star: 0.194Kwh/week; Blue Angel: Consumption: Active printing: 390w, Ready; 2.7w, Sleep: 0.51w, Manual Off: 0.05w Typical Electricity Consumption (TEC)®: Energy Star: 0.194Kwh/week; Blue Angel: CEC Title 47 CFR, Part 15 Class B/ICES-003, Issue 6 Blue Angel: EPEAT® Silver registered Telecom compliance: Wireless: EU RED 2014/53/EU; ETSI EN 301 489-1 V2.2.3 / E	MacOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; BB HD; Internet required orm  ad EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SMMPV3, Community password change; Secure defaults, Encrypted data at rest, cout; Secure Wi-Fi setup  Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm  9.5 kg  Minimum 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w;  203Kwh/week;  Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w;  C(South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European Singapore, Philippines, etc.  215 - Class B; EN 61000-3-2:2019; EN 61000-3-3:2013+A1:2019; EN 55035:2017;  TSI EN 301 489-17: V3.1.1; EN 300 328: V2.2.2 / EN301 893 V2.1.1 / EN300 440-1		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight  Printer dimensions (W x D x H)  Printer weight  Operating environment  Storage conditions  Acoustics  Power <sup>7</sup> Energy savings feature technology  Certifications	Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available harr Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protecte default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account loci HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)  Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg  Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH  Temperature: -20 to 60°C  Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A)  Requirements: 110V - 127V nominal @ +/-10% (min 99V, max 140V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz; Consumption: Active printing: 390w, Ready; 27w, Sleep: 0.51w, Manual Off: 0.05w Typical Electricity Consumption (TEC)®: Energy Star: 0.194Kwh/week; Blue Angel: Consumption: Active printing: 390w, Ready; 27w, Sleep: 0.51w, Manual Off: 0.05w Typical Electricity Consumption (TEC)®: Energy Star: 0.194Kwh/week; Blue Angel: Center of the Consumption of the Co	MacOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  d disk space, Internet connection, Microsoft® Internet Explorer or Edge.; BB HD; Internet required orm  ed EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SMMPV3, Community password change; Secure defaults, Encrypted data at rest, cout; Secure Wi-Fi setup  Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm  9.5 kg  Minimum 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w;  203Kwh/week;  Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w;  C(South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European Singapore, Philippines, etc. 2015 - Class B; EN 61000-3-2:2019; EN 61000-3-3:2013+A1:2019; EN 55035:2017;  TSI EN 301 489-17: V3.1.1; EN 300 328: V2.2.2 / EN301 893 V2.1.1 / EN300 440-1		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight  Printer dimensions (W x D x H)  Printer weight  Operating environment  Storage conditions  Acoustics  Power <sup>7</sup> Energy savings feature technology  Certifications  Sustainable impact specifications	Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hare Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protected default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account locid HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)  Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg  Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH  Temperature: -20 to 60°C  Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A)  Requirements: 110V - 127V nominal @ +/-10% (min 99V, max 140V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz; Consumption: Active printing: 390w, Ready; 27w, Sleep: 0.51w, Manual Off: 0.05w Typical Electricity Consumption (TEC)®: Energy Star: 0.194Kwh/week; Blue Angel: Consumption: Active printing: 390w, Ready; 27w, Sleep: 0.51w, Manual Off: 0.05w Typical Electricity Consumption (TEC)®: Energy Star: 0.194Kwh/week; Blue Angel: Center of the Accident of the	MacOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  d disk space, Internet connection, Microsoft® Internet Explorer or Edge.; BB HD; Internet required orm  ed EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SMMPV3, Community password change; Secure defaults, Encrypted data at rest, cout; Secure Wi-Fi setup  Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm  9.5 kg  Minimum 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w;  203Kwh/week;  Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w;  C(South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European Singapore, Philippines, etc. 2015 - Class B; EN 61000-3-2:2019; EN 61000-3-3:2013+A1:2019; EN 55035:2017;  TSI EN 301 489-17: V3.1.1; EN 300 328: V2.2.2 / EN301 893 V2.1.1 / EN300 440-1		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight  Printer dimensions (W x D x H)  Printer weight  Operating environment  Storage conditions  Acoustics  Power <sup>7</sup> Energy savings feature technology  Certifications  Sustainable impact specifications  Blue Angel compliant	Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available harr Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c. Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protected default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account locid HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)  Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg  Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH  Temperature: -20 to 60°C  Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A)  Requirements: 110V - 127V nominal @ +/-10% (min 99V, max 140V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz; Consumption: Active printing: 390w, Ready; 2.7w, Sleep: 0.51w, Manual Off: 0.05w Typical Electricity Consumption (TEC)®: Energy Star: 0.194Kwh/week; Blue Angel: Consumption: Active printing: 390w, Ready; 2.7w, Sleep: 0.51w, Manual Off: 0.05w Typical Electricity Consumption (TEC)®: Energy Star: 0.194Kwh/week; Blue Angel: CC Title 47 CFR, Part 15 Class B/ICES-003, Issue 6 Blue Angel; EPEAT® Silver registered Telecom compliance: Wireless: EU RED 2014/53/EU; ETSI EN 301 489-1 V2.2.3 / EV2.1.1; FCC Title 47 CFR, Part 15 Subpart C & E / RSS 247 Issue 1, 2015 & RSS 102 Recyclable through HP Planet Partners; Contains post-consumer recycled plastic Yes, Blue Angel DE-UZ 219—only ensured when using Original HP supplies	MacOS 12 Monterey; Linux  Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing)  I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; BB HD; Internet required orm  ad EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SMMPV3, Community password change; Secure defaults, Encrypted data at rest, cout; Secure Wi-Fi setup  Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm  9.5 kg  Minimum 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w;  203Kwh/week;  Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w;  C(South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European Singapore, Philippines, etc.  215 - Class B; EN 61000-3-2:2019; EN 61000-3-3:2013+A1:2019; EN 55035:2017;  TSI EN 301 489-17: V3.1.1; EN 300 328: V2.2.2 / EN301 893 V2.1.1 / EN300 440-1		
Compatible operating systems  Compatible network operating systems  Minimum system requirements  Software included  Security management  Printer management  Dimensions and weight  Printer dimensions (W × D × H)  Printer weight  Operating environment  Storage conditions  Acoustics  Power <sup>7</sup> Energy savings feature technology  Certifications  Sustainable impact specifications  Blue Angel compliant  Country of origin	Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available har Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 C No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.c Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protected default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account locid HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)  Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg  Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH  Temperature: -20 to 60°C  Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A)  Requirements: 110V - 127V nominal @ +/-10% (min 99V, max 140V), 50 - 60Hz nominal +/- 312 (min 47Hz, max 63Hz; Consumption: Active printing: 390w, Ready: 2.7w, Sleep: 0.51w, Manual Off: 0.05w Typical Electricity Consumption (TEC)®: Energy Star: 0.194Kwh/week; Blue Angel: CPower supply type: Internal (Built-in) power supply  HP Auto-On/Auto-Off Technology; Instant-on Technology  RCM (Australia), TUV and GS Mark (Germany), BSMI (Taiwan), CCC (China), BIS (India approvals, CE Marking, FCC, Energy Star; UL, Paraguay, Chile, Argentina, Indonesia, Electromagnetic emission standard: CISPR32:2015 & CISPR 35:2016 /EN55032:20 FCC Title 47 CFR, Part 15 Class B/ICES-003, Issue 6 Blue Angel; EPEAT® Silver registered Telecom compliance: Wireless: EUR ED 2014/53/EU; ETSI EN 301 489-1 V2.2.3 / EV2.1.1; FCC Title 47 CFR, Part 15 Class B/ICES-003, Issue 6 Blue Angel; EPEAT® Silver registered Telecom compliance: Wireless: EUR ED 2014/53/EU; ETSI EN 301 489-1 V2.2.3 / EV2.1.1; FCC Title 47 CFR, Part 15 Subpart C & E / RSS 247 Issue 1, 2015 & RSS 102  Recycla	Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4 mm  9.5 kg  Minimum 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, 203Kwh/week;  Auto Off/Manual 0n: 0.05w, Auto-Off/Wake on LAN: 0.5w;  20 kg Ky Secure Displays (County Secure); Eastern European Singapore, Philippines, etc.  15 EN 301 489-17: V3.1.1; EN 300 328: V2.2.2 / EN301 893 V2.1.1 / EN300 440-1 Issue 5, 2015; IEC 62311:2007 / EN62311:2008  381V1A HP Laser Jet Tank MFP 2604sdw Printer; HP Black Original Laser Jet Tank Imaging Drum (introductory ~5000 page black toner yield provided); Power Cord; Setup Guide; Reference Guide; Regulatory/Support Flyers  381V1A HP Laser Jet Tank MFP 2604sdw Printer; HP Black Original Laser Jet Tank Imaging Drum (introductory ~5000 page black toner yield provided); Power Cord; Setup Guide; Reference Guide; Regulatory/Support Flyers		

#### Footnotes

- 1 Actual yield varies considerably based on content of printed pages and other factors. Average based on ISO/IEC 19752 and continuous printing. Additional printed pages require toner reload. For details see www.hp.com/go/learnaboutsupplies.
- <sup>2</sup> When used in accordance with instructions. Average reload time based on HP internal testing.
- <sup>3</sup> Over 75% plastic reduction is calculated by comparing the weight of the plastic in HP Neverstop Laser 103/143 A/AD and HP Laser NS 108 A/AD Toner Reload Kit and its packaging.
- 4 Requires the HP Smart app download. For details on local printing requirements see http://www.hp.com/go/mobileprinting. Certain features/software are available in English language only and differ between desktop and mobile applications. Subscription may be required; subscription may not be available in all countries. See details at HPSmart.com. Internet access required and must be purchased separately. HP account required for full functionality. List of supported operating systems available in app stores.

  The yield of imaging drum is approximately 50,000 single-sided pages (letter or A4 size paper). There are many factors that determine the actual drum useful life, such as temperature, humidity, type of paper, type of toner used
- and other variables. The imaging drum unit is replaceable through authorized service provider.

#### Technical specifications disclaimers

- 1 Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity
- <sup>2</sup> Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
- <sup>3</sup> HP Auto-On/Auto-Off Technology capabilities subject to printer and settings; May require a firmware upgrade.
- <sup>4</sup> Requires the HP Smart app download. For details on local printing requirements see http://www.hp.com/go/mobileprinting. Certain features/software are available in English language only and differ between desktop and mobile applications. Subscription may be required; Subscription may not be available in all countries. See details at: HPSmart.com; Internet access required and must be purchased separately. HP account required for full functionality. List of supported operating systems available in app stores.
- <sup>5</sup> Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.
- <sup>6</sup> Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device.
- 7 HP Black Original Laser Jet Tank Imaging Drum (introductory ~5,000 page black toner yield provided). For yield information included with your printer, see http://www.hp.com/go/toneryield. Yield values measured in accordance with ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors.

