

### Overview

#### HP EliteBook 840 14 inch G9 Notebook PC



#### Left

- |                                    |  |
|------------------------------------|--|
| 1. Internal Microphones (2)        | 8. Smartcard Reader (Optional)   |
| 2. Ambient Light Sensor (Optional) | 9. LED Indicator   |
| 3. Webcam                          | 10. Thunderbolt™ 4 with USB4 Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4) <sup>1</sup> |
| 4. Camera Shutter                  | 11. Thunderbolt™ 4 with USB4 Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4) <sup>1</sup> |
| 5. IR Camera (Optional)            | 12. SuperSpeed USB Type-A 5Gbps signaling rate (USB 3.2 Gen 1)   |
| 6. IR Camera LEDs (Optional)       | 13. HDMI 2.0b Port (Cable not included)  |

1. SuperSpeed USB 20Gbps is not available with Thunderbolt™ 4.

### Overview



#### Right

1. Power Button Key
2. Audio Combo Jack
3. SuperSpeed USB Type-A 5Gbps signaling rate (Charging) (USB 3.2 Gen 1)
4. Nano Security Lock Slot (Lock sold separately)
5. SIM Card Slot (Optional)
6. Touch Fingerprint Sensor (Select models)

### Overview

#### At a Glance

- Preinstalled with Windows 11 versions or FreeDOS
- New premium ultraslim design with precision-crafted all-metal chassis for a premium look and feel
- 12th Generation Intel® Core™ i5, i7 U series and i5, i7 P series Processors up to fourteen-core
- New 16:10 ratio screen reduces the need to scroll by showing more vertical content than 16:9
- Optional ultrabright displays with HP Eye Ease, ambient light and ambient color sensors
- New 5MP camera4 with HP Auto Frame8 allows you around a little without losing viewers' attention during video calls
- New DDR5 memory and PCI Gen4 SSDs provide fast access to your work.
- Choice of displays:
  - 35.6 cm (14") diagonal WUXGA IPS Anti-Glare LED-backlit, 250 nits, 45% NTSC
  - 35.6cm (14") diagonal WUXGA IPS Anti-Glare On-Cell LED-backlit touch, 250 nits, 45% NTSC
  - 35.6 cm (14") diagonal WUXGA IPS Anti-Glare LED-backlit non-touch 400 nits, 100% sRGB with HP Eye Ease
  - 35.6cm (14") diagonal WUXGA IPS Anti-Glare LED-backlit non-touch, 1000 nits, 100% sRGB with HP Sure View Reflect with HP Eye Ease
- Redesigned keyboard layout to include easy use of discrete PgUp/Dn, End, and Home keys
- Choose from 38Whr or 51Whr battery options
- HP Wolf Security for Business creates a hardware-enforced, always-on, resilient defense.9
- Larger Clickpad surface for easier, more intuitive input
- Connectivity with optional Intel® 5000 5G/WWAN available world-wide, and Thunderbolt™ Docking (Dock sold separately)
- Undergoes MIL-STD 810H tests1
- Supports fast charging (50% in 30 minutes) with no impact on battery recharge cycles3
- Designed to support all HP docking options including the HP Universal Dock G5

**NOTE: See important legal disclosures for all listed specs in their respective features sections.**

---

### Technical Specifications

#### PRODUCT NAME

HP EliteBook 840 G9 14 inch G9 Notebook PC

#### OPERATING SYSTEMS

##### Preinstalled

Windows 11 Pro  
 Windows 11 Pro Education <sup>1</sup>  
 Windows 11 Home – HP recommends Windows 11 Pro for Business<sup>1</sup>  
 Windows 11 Home Single Language – HP recommends Windows 11 Pro for Business<sup>1</sup>  
 Windows 11 Pro (Windows 11 Enterprise available with a Volume Licensing Agreement) <sup>1</sup>  
 Windows 10 Pro (available through downgrade rights from Windows 11 Pro) <sup>1,2</sup>  
 FreeDOS

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

2. This system is preinstalled with Windows 10 Pro software and also comes with a license for Windows 11 Pro software and provision for recovery software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

#### PROCESSORS

| Processor <sup>3,4,5,6,7</sup> | Cores | Number of P-cores | Number of E-cores | Threads | L3 Cache | Max Turbo Frequency |         | Base Frequency |         | Intel SIPP/vPro® Enterprise |
|--------------------------------|-------|-------------------|-------------------|---------|----------|---------------------|---------|----------------|---------|-----------------------------|
|                                |       |                   |                   |         |          | P-cores             | E-cores | P-cores        | E-cores |                             |
| Intel® Core™ i7-1280P          | 14    | 6                 | 8                 | 20      | 24MB     | 4.8 GHz             | 3.6 GHz | 1.8 GHz        | 1.3 GHz | X                           |
| Intel® Core™ i7-1270P          | 12    | 4                 | 8                 | 16      | 18MB     | 4.8 GHz             | 3.5 GHz | 2.2 GHz        | 1.6 GHz | X                           |
| Intel® Core™ i7-1260P          | 12    | 4                 | 8                 | 16      | 18MB     | 4.7 GHz             | 3.4 GHz | 2.1 GHz        | 1.5 GHz |                             |
| Intel® Core™ i5-1250P          | 12    | 4                 | 8                 | 16      | 12MB     | 4.4 GHz             | 3.3 GHz | 1.7 GHz        | 1.2 GHz | X                           |
| Intel® Core™ i5-1240P          | 12    | 4                 | 8                 | 16      | 12MB     | 4.4 GHz             | 3.3 GHz | 1.2 GHz        | 1.3 GHz |                             |
| Intel® Core™ i7-1265U          | 10    | 2                 | 8                 | 12      | 12MB     | 4.8 GHz             | 3.6 GHz | 1.8 GHz        | 1.3 GHz | X                           |
| Intel® Core™ i7-1255U          | 10    | 2                 | 8                 | 12      | 12MB     | 4.7 GHz             | 3.5 GHz | 1.7 GHz        | 1.2 GHz |                             |
| Intel® Core™ i5-1245U          | 10    | 2                 | 8                 | 12      | 12MB     | 4.4 GHz             | 3.3 GHz | 1.2 GHz        | 1.2 GHz | X                           |
| Intel® Core™ i5-1235U          | 10    | 2                 | 8                 | 12      | 12MB     | 4.4 GHz             | 3.3 GHz | 1.3 GHz        | 0.9 GHz |                             |

## Technical Specifications

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

5. Intel® Turbo Boost performance varies depending on hardware, software and overall system configuration. See [www.intel.com/technology/turboboost](http://www.intel.com/technology/turboboost) for more information.

6. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>

7. Intel vPro® requires Windows 10 Pro 64 bit or higher, a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN and/or Wi-Fi 6E WLAN and TPM 2.0. Some functionality requires additional 3rd party software in order to run. Features of vPro® Essentials and Enterprise vary. See <http://intel.com/vpro>

---

## CHIPSET

Chipset is integrated with processor

---

## GRAPHICS

### Integrated

Intel® Iris® X<sup>e</sup> Graphics<sup>8</sup>

### Supports

Support HD decode, DX12, HDMI 2.0b, HDCP 2.3<sup>9</sup>

8. Intel® Iris® X<sup>e</sup> Graphics capabilities require system to be configured with Intel® Core™ i5 or i7 processors and dual channel memory. Intel® Iris® X<sup>e</sup> Graphics with Intel® Core™ i5 or i7 processors and single channel memory will only function as UHD graphics.

9. HDMI cable sold separately

---

## DISPLAY

### Non-Touch

35.56 cm (14") diagonal WUXGA Bent, anti-glare UWVA, 250 nits, 45% NTSC for 5MP camera (1920 x 1200)<sup>10,11</sup>

35.56 cm (14") diagonal WUXGA Bent, anti-glare UWVA, 250 nits, 45% NTSC for 5MP+IR camera (1920 x 1200)<sup>10,11</sup>

35.56 cm (14") diagonal WUXGA Bent, anti-glare UWVA, 250 nits, 45% NTSC for WWAN (1920 x 1200)<sup>10,11</sup>

35.56 cm (14") diagonal WUXGA Bent, anti-glare UWVA, 250 nits, 45% NTSC for 5MP camera for WWAN (1920 x 1200)<sup>10,11</sup>

35.56 cm (14") diagonal WUXGA Bent, anti-glare UWVA, 250 nits, 45% NTSC for 5MP+IR camera for WWAN (1920 x 1200)<sup>10,11</sup>

35.56 cm (14") diagonal WUXGA Bent, anti-glare UWVA eDP1.2, micro-edge, 250 nits, 45% NTSC, Narrow Bezel (1920 x 1200)<sup>10,11</sup>

35.56 cm (14") diagonal WUXGA Bent, Low Blue Light, anti-glare UWVA eDP+PSR, 400 nits, 100% sRGB, Low Power, Ambient Light Sensor+Ambient Color Sensor for 5MP Camera (1920 x 1200) with HP Eye Ease<sup>10,11</sup>

35.56 cm (14") diagonal WUXGA Bent, Low Blue Light, anti-glare UWVA eDP+PSR, 400 nits, 100% sRGB, Low Power, Ambient Light Sensor+Ambient Color Sensor for 5MP+IR Camera (1920 x 1200) with HP Eye Ease<sup>10,11</sup>

35.56 cm (14") diagonal WUXGA Bent, Low Blue Light, anti-glare UWVA eDP+PSR, 400 nits, 100% sRGB, Low Power, Ambient Light Sensor+Ambient Color Sensor for 5MP+IR Camera for WWAN (1920 x 1200) with HP Eye Ease<sup>10,11</sup>

### Technical Specifications

35.56 cm (14") diagonal WUXGA Bent, Low Blue Light, anti-glare UWVA eDP1.3+PSR, 1000 nits, 100% sRGB with HP Sure View Reflect integrated privacy screen, Ambient Light Sensor+Ambient Color Sensor for 5MP camera (1920 x 1200) with HP Eye Ease <sup>10,11,12,13</sup>

35.56 cm (14") diagonal WUXGA Bent, Low Blue Light, anti-glare UWVA eDP1.3+PSR, 1000 nits, 100% sRGB with HP Sure View Reflect integrated privacy screen, Ambient Light Sensor+Ambient Color Sensor for 5MP+IR camera (1920 x 1200) with HP Eye Ease <sup>10,11,12,13</sup>

35.56 cm (14") diagonal WUXGA Bent, Low Blue Light, anti-glare UWVA eDP1.3+PSR, 1000 nits, 100% sRGB with HP Sure View Reflect integrated privacy screen, Ambient Light Sensor+Ambient Color Sensor for 5MP+IR camera for WWAN (1920 x 1200) with HP Eye Ease <sup>10,11,12,13</sup>

#### Touch

35.56 cm (14") diagonal WUXGA Bent, anti-glare UWVA, 250 nits, 45% NTSC for 5MP+IR camera Touch on Panel (1920 x 1200) <sup>10,11,13</sup>

35.56 cm (14") diagonal WUXGA Bent, anti-glare UWVA, 250 nits, 45% NTSC for 5MP+IR camera for WWAN Touch on Panel (1920 x 1200) <sup>10,11,13</sup>

#### DisplayPort™ 1.2

HDMI 2.0 Support resolution up to 4K @60 Hz <sup>9</sup>

#### Displays support

Supports dual display through the dock

#### Display Size (Diagonal)

14"

35.56 cm (14")

9. HDMI cable sold separately

10. HD content required to view HD images.

11. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

12. HP Sure View Reflect integrated privacy screen is an optional feature that must be configured at purchase and is designed to function in landscape orientation.

13. Actual brightness will be lower with touchscreen or Sure View.

---

### DOCKING (Sold Separately)

**Docking station model #1**

HP Thunderbolt Dock G2

**Docking station model #2**

HP USB-C Dock G5

**Docking station model #3**

HP USB-C/A Universal Dock G2

[For additional aftermarket options and docking specs please see page 41.](#)

---

## Technical Specifications

### STORAGE AND DRIVES

#### Primary M.2 Storage

2 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC <sup>14</sup>  
1 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC <sup>14</sup>  
512 GB PCIe® Gen4x4 NVMe™ M.2 SSD TLC <sup>14</sup>  
512 GB PCIe® Gen4x4 NVMe™ SED TLC OPAL2 <sup>14</sup>  
512 GB PCIe® NVMe™ Value M.2 SSD <sup>14</sup>  
256 GB PCIe® Gen4x4 NVMe™ M.2 SSD TLC <sup>14</sup>  
256 GB PCIe® Gen4x4 NVMe™ SED TLC OPAL2 <sup>14</sup>  
256 GB PCIe® NVMe™ Value M.2 SSD <sup>14</sup>

<sup>14</sup>. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

### MEMORY

#### Maximum Memory

64GB DDR5-4800 <sup>15</sup>

#### Memory

64GB DDR5-4800 (2x32GB) <sup>15</sup>  
32GB DDR5-4800 (2x16GB) <sup>15</sup>  
32GB DDR5-4800 (1x32GB) <sup>15</sup>  
16GB DDR5-4800 (2x8GB) <sup>15</sup>  
16GB DDR5-4800 (1x16GB) <sup>15</sup>  
8GB DDR5-4800 (1x8GB) <sup>15</sup>

#### Memory Slots

2 SODIMM  
DDR5 SODIMMS, system runs at 4800  
Supports Dual Channel Memory

<sup>15</sup>. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

### NETWORKING/COMMUNICATIONS

#### WLAN

Intel® AX211 Wi-Fi6E+BT5.3 M.2 160MHz CNVi World-Wide WLAN vPro <sup>16,17,18</sup>  
Intel® AX211 Wi-Fi6E+BT5.3 M.2 160MHz CNVi World-Wide WLAN non-vPro <sup>16,18</sup>

#### WWAN

Intel® 5000 5G Solution WWAN <sup>19,20</sup>  
Intel® XMM 7560 R+ LTE-Advanced Pro WWAN (Cat 16) <sup>19</sup>

#### NFC

Near Field Communication (NFC) module <sup>21</sup>  
HP Module with NXP NFC Controller NPC300 I2C NCI

#### Miracast

Native Miracast Support <sup>22</sup>



### Technical Specifications

16. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.

17. For full Intel® vPro™ functionality, Windows, a vPro supported processor, vPro enabled chipset, vPro enabled WLAN card and discrete TPM 2.0 are required. See <https://www.intel.com/content/www/us/en/architecture-and-technology/vpro/vpro-platform-general.html>

18. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.

19. WWAN module is an optional feature, requires factory configuration and requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

20. Intel 5G module is optional and must be configured at the factory. Module designed for 5G NR NSA (non-standalone) networks as carriers deploy Evolved-Universal Terrestrial Radio Access New Radio Dual Connectivity (ENDC) with both 100MHz of 5G NR and LTE channel bandwidth, using 256QAM 4x4 as defined by 3GPP. Module requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Data connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. Backwards compatible to 4G LTE and 3G HSPA technologies. 5G module planned to be available in select platforms and select countries, where carrier supported.

21. Sold separately or as an optional feature.

22. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

---

### AUDIO/MULTIMEDIA

#### Audio

Audio by Bang & Olufsen

2 Integrated stereo speakers

Discrete Amplifiers

Integrated dual array microphone

#### Speaker Power

1W/8ohm Per speaker

#### Camera

5 MP camera <sup>21</sup>

5 MP+IR camera <sup>21</sup>

#### Sensors

ALS (ambient light sensor)

Magnetometer

Hall Sensor

Gyro

Accelerometer

HP Tamper Lock <sup>23</sup>

21. Sold separately or as an optional feature.

23. HP Tamper Lock must be enabled by the customer or your administrator.



### Technical Specifications

#### KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

##### Keyboard

HP Premium Keyboard, spill resistant, Backlit keyboard and DuraKeys <sup>24</sup>

HP Premium Keyboard, spill resistant, Non-Backlit keyboard and DuraKeys

HP Premium Keyboard, spill resistant, Backlit keyboard and DuraKeys Privacy

##### Pointing Device

Clickpad with multi-touch gesture support, taps enabled as default

Microsoft Precision Touchpad Default Gestures Support

##### Function Keys

ESC: system information

F1 - Display Switching

F2 - Blank or Privacy

F3 - Brightness Down

F4 - Brightness Up

F5 - Audio Mute

F6 - Volume Down

F7 - Volume Up

F8 - Mic Mute

F9 - Blank or Backlit Toggle

F10 - Insert

F11 - Airplane Mode

F12 - HP Programmable Key

home

end

Power Button (with LED)

delete

##### Hidden Function Keys

Fn+R - Break

Fn+S - Sys Rq

Fn+C - Scroll Lock

[24. Backlit keyboard is an optional feature.](#)

---

### Technical Specifications

#### SOFTWARE AND SECURITY

##### Software

HP Quick Touch

HP Quick Drop <sup>25</sup>

HP Easy Clean <sup>26</sup>

HP PC Hardware Diagnostics Windows

myHP

HP Smart Support <sup>27</sup>

HP Connection Optimizer

HP Hotkey Support

HP Support Assistant <sup>28</sup>

HP Notifications

HP Privacy Settings

HP Power Manager

Buy Microsoft Office (Sold separately)

##### Manageability Features

HP Image Assistant Gen5 (download)

HP Manageability Integration Kit (download) <sup>29</sup>

HP Client Management Script Library (download)

HP Driver Packs (download)

HP Cloud Recovery <sup>30</sup>

HP Client Catalog (download)

**NOTE:** To enhance brightness, level go to the Intel® Graphics Command Center app, click on System and turn off the Display Power Savings function.

##### Security Management

**HP Wolf Security of Business <sup>31</sup> includes:**

HP Sure Click <sup>32</sup>

HP Sure Sense <sup>33</sup>

HP Sure Run Gen5 <sup>34</sup>

HP Sure Recover Gen5 <sup>35</sup>

HP Sure Start Gen7 <sup>36</sup>

HP Tamper Lock

HP Sure Admin <sup>37</sup>

HP Client Security Manager Gen7 <sup>38</sup>

##### BIOS

HP BIOSphere Gen6 <sup>39</sup>

HP Secure Erase <sup>40</sup>

Absolute Persistence Module <sup>41</sup>

HP DriveLock & Automatic DriveLock

BIOS Update via Network

HP Wake on WLAN

HP Fingerprint Sensor <sup>42</sup>

Secured-Core PC Enable <sup>43</sup>

TPM 2.0 Embedded Security Chip (Common Criteria EAL4+ Certified) (FIPS 140-2 Level 2 Certified)

## Technical Specifications

### Security

#### TPM

Model: Infineon SLB9672VU2.0

Version: 15.21

Revision: TPM 2.0

FIPS 140-2 Compliant: Yes

#### Smartcard Reader

Model number: Alcor AU9560

FIPS 201 Compliant: Yes

#### IPv6 Support

Yes

#### FirstNet Certified

Yes

#### Is the BIOS on this notebook ISO/IEC 19678:2015 (formerly NIST 800-147) compliant?: Yes

UEFI version: 2.7

Class: 3

25. HP Quick Drop requires Internet access and Windows 10 or higher PC preinstalled with HP QuickDrop app and either an Android device (phone or tablet) running Android 7 or higher with the Android HP QuickDrop app, and /or an iOS device (phone or tablet) running iOS 12 or higher with the iOS HP QuickDrop app.
26. HP Easy Clean requires Windows 10 RS3 and higher and will disable the keyboard, touchscreen, and clickpad only. Ports are not disabled. See user guide for cleaning instructions.
27. HP Smart Support automatically collects the telemetry necessary upon initial boot of the product to deliver device-level configuration data and health insights and is available preinstalled on select products, thru HP Factory Configuration Services; or it can be downloaded. For more information about how to enable HP Smart Support or for download, please visit <http://www.hp.com/smart-support>.
28. HP Support Assistance requires Windows and Internet Access.
29. HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.
30. HP Cloud Recovery is available for Z by HP, HP Elite and Pro desktops and laptops PCs with Intel® or AMD processors and requires an open, wired network connection. Note: You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Detail please refer to: <https://support.hp.com/us-en/document/c05115630>.
31. HP Wolf Security for Business requires Windows 10 or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features and OS requirement.
32. HP Sure Click requires Windows 10 Pro or higher or Enterprise. See [https://bit.ly/2PrLT6A\\_SureClick](https://bit.ly/2PrLT6A_SureClick) for complete details.
33. HP Sure Sense is available on select HP PCs with Windows 10 Pro, Windows 10 Enterprise, Windows 11 Pro, or Windows 11 Enterprise OS.
34. HP Sure Run Gen5 is available on select HP PCs and requires Windows 10 and higher.
35. HP Sure Recover Gen5 with Embedded Reimaging is an optional feature which requires Windows 10 and higher must be configured at purchase. You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Network based recovery using Wi-Fi is only available on PCs with Intel Wi-Fi Module
36. HP Sure Start Gen7 is available on select HP PCs and requires Windows 10 and higher
37. HP Sure Admin requires Windows 10 or higher, HP BIOS, HP Manageability Integration Kit from <http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store.

### Technical Specifications

- 38. HP Client Security Manager Gen7 requires Windows and is available on the select HP Elite and Pro PCs.
  - 39. HP BIOSphere Gen6 features may vary depending on the platform and configuration.
  - 40. HP Secure Erase for the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.
  - 41. Absolute firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit: <https://www.absolute.com/about/legal/agreements/absolute/>.
  - 42. HP Fingerprint sensor is an optional feature that must be configured at purchase.
  - 43. Secured-Core PC Enable requires an Intel® vPro®, AMD Ryzen™ Pro processor or Qualcomm® processor with SD850 or higher and requires 8 GB or more system memory. Secured-core PC is enabled from the factory.
-

### Technical Specifications

#### POWER

##### Power Supply

HP Smart 65 W USB Type-C adapter <sup>44</sup>

HP Smart 45 W USB Type-C adapter <sup>44</sup>

##### Battery

HP Long Life 3-cell, 38 Wh Polymer <sup>45,46</sup>

HP Long Life 3-cell, 51 Wh Polymer <sup>45,46</sup>

Compliant with UL 1642 Standard

##### Power Cord

3-wire plug - 1m

2-wire plug - 1m

##### Battery Life

Up to 10 hours (38Whr) 15W <sup>47</sup>

Up to 13 hours 30 minutes (51Whr) 28W <sup>47</sup>

Up to 14 hours (51Whr) 15W <sup>47</sup>

44. Availability may vary by country.

45. Battery is internal and not replaceable by customer. Serviceable by warranty.

46. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

47. MM18 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See [www.bapco.com](http://www.bapco.com) for additional details.

---

#### WEIGHTS & DIMENSIONS

##### Product Weight- 38 Whr <sup>48</sup>

Starting at 3.00 lb

Starting at 1.36 kg

##### Product Weight- 51 Whr <sup>48</sup>

Starting at 3.09 lb

Starting at 1.40 kg

##### Product Dimensions (W x D x H)

12.42 x 8.82 x 0.76 in

31.56 x 22.405 x 1.92 cm

48. Weight will vary by configuration. Does not include power adapter.

---

### Technical Specifications

#### PORTS/SLOTS

- 2 Thunderbolt™ 4 with USB4 Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4) <sup>49</sup>
- 2 Super Speed USB Type-A 5Gbps signaling rate (1 charging) (USB 3.2 Gen 1)
- 1 HDMI 2.0 <sup>9</sup>
- 1 Headphone/microphone combo jack
- 1 Nano Security Lock Slot (Lock sold separately)
- 1 Smartcard reader (Optional)
- 1 nano SIM card slot

[9. HDMI cable sold separately](#)

[49. SuperSpeed USB 20Gbps is not available with Thunderbolt™ 4.](#)

---

### Technical Specifications

#### **SERVICE AND SUPPORT**

1-year warranty and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty except for HP Long Life batteries which will follow the one or three year warranty of the platform. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.<sup>50</sup>

50. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit [www.hp.com/go/cpc](http://www.hp.com/go/cpc). HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

---



## Technical Specifications

### SYSTEM UNIT

**Stand-Alone Power Requirements (AC Power)** Type-C Adapter

Nominal Operating Voltage AC 20V

Average Operating Power

Integrated graphics Yes

Discrete Graphics N/A

Max Operating Power UMA<65W

### Temperature

Operating 32° to 95° F (0° to 35° C)

Non-operating 41° to 95° F (5° to 35° C) (writing optical)

### Relative Humidity

Operating 10% to 90%, non-condensing

Non-operating 5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature

### Shock

Operating 40 G, 2 ms, half-sine

Non-operating 200 G, 2 ms, half-sine

### Random Vibration

Operating 0.75 grams

Non-operating 1.50 grams

### Altitude (unpressurized)

Operating -50 to 10,000 ft (-15.24 to 3,048 m)

Non-operating -50 to 40,000 ft (-15.24 to 12,192 m)

### Planned Industry Standard Certifications

Regulatory Model Number HSN-I45C-4

UL Yes

CSA Yes

FCC Compliance Yes

ENERGY STAR® Certified <sup>51</sup>

EPEAT® EPEAT® Gold in the United States <sup>52</sup>

ICES Yes

Australia / Yes

NZ A-Tick Compliance Yes

CCC Yes

Japan VCCI Compliance Yes

KC Yes

BSMI Yes

CE Marking Compliance Yes

BNCI or BELUS Yes

CIT Yes

GOST Yes

Saudi Arabian Compliance (ICCP) Yes

SABS Yes

## Technical Specifications

51. Configurations of the HP EliteBook 840 G9 that are ENERGY STAR® qualified are identified as HP EliteBook 840 G9 ENERGY STAR on HP websites and on <http://www.energystar.gov>.

52. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit <http://www.epeat.net> for more information.

## DISPLAYS

Note: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

1. Actual brightness will be lower with touchscreen or HP Sure View.

|  |   |                         |
|--|---|-------------------------|
| <b>14.0 in WUXGA (1920 x 1200) Anti-Glare UWVA LED NTSC NB2X 250 eDP 1.2 w/o PSR 45 bent LCD Panel</b> | <b>Outline Dimensions (W x H x D)</b>                       | 307.590 x 199.550 (max) |
|  | <b>Active Area</b>  | 301.590 X 188.500 (typ) |
|  | <b>Weight</b>   | 300 (max)               |
|  | <b>Diagonal Size</b>  | 14                      |
|  | <b>Thickness</b>  | 3.0 / 5.0 (max)         |
|  | <b>Interface</b>  | eDP 1.2                 |
|  | <b>Surface Treatment</b>                                    | Anti-Glare              |
|  | <b>Touch Enabled</b>  | No                      |
|  | <b>Contrast Ratio</b>                                       | 1000:1 (typ)            |
|  | <b>Refresh Rate</b>   | 60 Hz                   |
|  | <b>Brightness</b>   | 250 nits                |
|  | <b>Pixel Resolution - Format</b>                            | 1920 x 1200 (WUXGA)     |
|  | <b>Backlight</b>  | WLED                    |
|  | <b>Pixel Resolution</b>                                     | RGB                     |
|  | <b>Color Gamut Coverage</b>                                 | NTSC 45%                |
|  | <b>Color Depth</b>  | 8 bits                  |
|  | <b>Viewing Angle</b>  | UWVA 89/89/89/89        |
|  | <b>Low Blue Light</b>                                       | No                      |
|  | <b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b> | 2.20 (max) / 2.70 (max) |

|  |                                       |                         |
|--|---------------------------------------|-------------------------|
| <b>14.0 in WUXGA (1920 x 1200) Anti-Glare UWVA LED NTSC NB2X 250 TOP eDP 1.2 w/o PSR 45 bent LCD Panel</b> | <b>Outline Dimensions (W x H x D)</b> | 307.590 x 199.550 (max) |
|  | <b>Active Area</b>                    | 301.590 x 188.500 (typ) |
|  | <b>Weight</b>                         | 300 (max)               |
|  | <b>Diagonal Size</b>                  | 14                      |
|  | <b>Thickness</b>                      | 3.0 / 5.0 (max)         |
|  | <b>Interface</b>                      | eDP 1.2                 |
|  | <b>Surface Treatment</b>              | Anti-Glare              |
|  | <b>Touch Enabled</b>                  | Yes <sup>1</sup>        |
|  | <b>Contrast Ratio</b>                 | 1000:1 (typ)            |
|  | <b>Refresh Rate</b>                   | 60 Hz                   |
|  | <b>Brightness</b>                     | 250 nits <sup>1</sup>   |
|  | <b>Pixel Resolution - Format</b>      | 1920 x 1200 (WUXGA)     |
|  | <b>Backlight</b>                      | WLED                    |
|  | <b>Pixel Resolution</b>               | RGB                     |

### Technical Specifications

|   |                         |
|---|-------------------------|
| <b>Color Gamut Coverage</b>                                 | NTSC 45%                |
| <b>Color Depth</b>  | 8 bits                  |
| <b>Viewing Angle</b>  | UWVA 89/89/89/89        |
| <b>Low Blue Light</b>                                       | No                      |
| <b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b> | 2.10 (max) / 2.60 (max) |

**14.0 in WUXGA (1920 x 1200) Anti-Glare UWVA WLED+LBL sRGB NB2X 400 eDP 1.4+PSR2 Low-Power 100 bent LCD Panel**

|   |                         |
|---|-------------------------|
| <b>Outline Dimensions (W x H x D)</b>                       | 307.590 x 199.550 (max) |
| <b>Active Area</b>  | 301.590 X 188.500 (typ) |
| <b>Weight</b>   | 210 (max)               |
| <b>Diagonal Size</b>  | 14                      |
| <b>Thickness</b>  | 2.0 / 3.8 (max)         |
| <b>Interface</b>  | eDP 1.4                 |
| <b>Surface Treatment</b>                                    | Anti-Glare              |
| <b>Touch Enabled</b>  | No                      |
| <b>Contrast Ratio</b>                                       | 1000:1 (typ)            |
| <b>Refresh Rate</b>   | 60 Hz                   |
| <b>Brightness</b>   | 400 nits                |
| <b>Pixel Resolution - Format</b>                            | 1920 x 1200 (WUXGA)     |
| <b>Backlight</b>  | WLED                    |
| <b>Pixel Resolution</b>                                     | RGB                     |
| <b>Color Gamut Coverage</b>                                 | sRGB 100%               |
| <b>Color Depth</b>  | 8 bits                  |
| <b>Viewing Angle</b>  | UWVA 89/89/89/89        |
| <b>Low Blue Light</b>                                       | Yes                     |
| <b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b> | 1.29 (max) / 1.66 (max) |

**14.0 in WUXGA (1920 x 1200) Anti-Glare UWVA WLED+LBL sRGB NB2Y 1000 eDP 1.3+PSR 100 PrivacyG4 Plus bent LCD Panel**

|                                       |                         |
|---------------------------------------|-------------------------|
| <b>Outline Dimensions (W x H x D)</b> | 307.600 x 199.550 (typ) |
| <b>Active Area</b>                    | 301.680 x 188.500 (typ) |
| <b>Weight</b>                         | 238 (max)               |
| <b>Diagonal Size</b>                  | 14                      |
| <b>Thickness</b>                      | 2.2 / 3.9 (max)         |
| <b>Interface</b>                      | eDP 1.3                 |
| <b>Surface Treatment</b>              | Anti-Glare              |
| <b>Touch Enabled</b>                  | No                      |
| <b>Contrast Ratio</b>                 | 1500:1 (typ)            |
| <b>Refresh Rate</b>                   | 60 Hz                   |
| <b>Brightness</b>                     | 1000 nits               |
| <b>Pixel Resolution - Format</b>      | 1920 x 1200 (WUXGA)     |
| <b>Backlight</b>                      | WLED                    |
| <b>Pixel Resolution</b>               | RGB                     |
| <b>Color Gamut Coverage</b>           | sRGB 100%               |
| <b>Color Depth</b>                    | 8 bits                  |

### Technical Specifications

|   |                  |
|---|------------------|
| <b>Viewing Angle</b>  | UWVA 85/85/85/85 |
| <b>Low Blue Light</b>   | Yes              |
| <b>Power Consumption (W, EBL@<br/>150nits max/ 200nits max)</b> | N/A              |

---

## Technical Specifications

**STORAGE AND DRIVES**

For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

|  |                                 |  |
|--|---------------------------------|--|
| <b>SSD 256GB 2280 PCIe-4x4<br/>NVMe Three Layer Cell</b> | <b>Form Factor</b>              | M.2 2280                                 |
|  | <b>Capacity</b>                 | 256GB                                    |
|  | <b>NAND Type</b>                | TLC                                      |
|  | <b>Height</b>                   | 0.09 in (2.3 mm)                         |
|  | <b>Width</b>                    | 0.87 in (22 mm)                          |
|  | <b>Weight</b>                   | 0.02 lb (10 g)                           |
|  | <b>Interface</b>                | PCIe NVMe Gen4X4                         |
|  | <b>Maximum Sequential Read</b>  | 4000 MB/s ±20%                           |
|  | <b>Maximum Sequential Write</b> | 2000 MB/s ±20%                           |
|  | <b>Logical Blocks</b>           | 500,118,192                              |
|  | <b>Operating Temperature</b>    | 32° to 158°F (0° to 70°C) [ambient temp] |
|  | <b>Features</b>                 | Pyrite 2.0; TRIM; L1.2                   |

|  |                                 |  |
|--|---------------------------------|--|
| <b>SSD 512GB 2280 PCIe-4x4<br/>NVMe Three Layer Cell</b> | <b>Form Factor</b>              | M.2 2280                                 |
|  | <b>Capacity</b>                 | 512GB                                    |
|  | <b>NAND Type</b>                | TLC                                      |
|  | <b>Height</b>                   | 0.09 in (2.3 mm)                         |
|  | <b>Width</b>                    | 0.87 in (22 mm)                          |
|  | <b>Weight</b>                   | 0.02 lb (10 g)                           |
|  | <b>Interface</b>                | PCIe NVMe Gen4X4                         |
|  | <b>Maximum Sequential Read</b>  | 6400 MB/s ±20%                           |
|  | <b>Maximum Sequential Write</b> | 3500 MB/s ±20%                           |
|  | <b>Logical Blocks</b>           | 1,000,215,215                            |
|  | <b>Operating Temperature</b>    | 32° to 158°F (0° to 70°C) [ambient temp] |
|  | <b>Features</b>                 | Pyrite 2.0; TRIM; L1.2                   |

|  |                                 |                  |
|--|---------------------------------|------------------|
| <b>SSD 1TB 2280 PCIe-4x4<br/>NVMe Three Layer Cell</b> | <b>Form Factor</b>              | M.2 2280         |
|  | <b>Capacity</b>                 | 1TB              |
|  | <b>NAND Type</b>                | TLC              |
|  | <b>Height</b>                   | 0.09 in (2.3 mm) |
|  | <b>Width</b>                    | 0.87 in (22 mm)  |
|  | <b>Weight</b>                   | 0.02 lb (10 g)   |
|  | <b>Interface</b>                | PCIe NVMe Gen4X4 |
|  | <b>Maximum Sequential Read</b>  | 6400 MB/s ±20%   |
|  | <b>Maximum Sequential Write</b> | 5000 MB/s ±20%   |

### Technical Specifications

|                              |  |
|------------------------------|--|
| <b>Logical Blocks</b>        | 2,000,409,264                            |
| <b>Operating Temperature</b> | 32° to 158°F (0° to 70°C) [ambient temp] |
| <b>Features</b>              | Pyrite 2.0; TRIM; L1.2                   |

|  |                                 |  |
|--|---------------------------------|--|
| <b>SSD 2TB 2280 PCIe-4x4 NVMe Three Layer Cell</b> | <b>Form Factor</b>              | M.2 2280                                 |
|  | <b>Capacity</b>                 | 2TB                                      |
|  | <b>NAND Type</b>                | TLC                                      |
|  | <b>Height</b>                   | 0.09 in (2.3 mm)                         |
|  | <b>Width</b>                    | 0.87 in (22 mm)                          |
|  | <b>Weight</b>                   | 0.02 lb (10 g)                           |
|  | <b>Interface</b>                | PCIe NVMe Gen4X4                         |
|  | <b>Maximum Sequential Read</b>  | 6400 MB/s ±20%                           |
|  | <b>Maximum Sequential Write</b> | 5000 MB/s ±20%                           |
|  | <b>Logical Blocks</b>           | 4,000,797,360                            |
|  | <b>Operating Temperature</b>    | 32° to 158°F (0° to 70°C) [ambient temp] |
|  | <b>Features</b>                 | Pyrite 2.0; TRIM; L1.2                   |

|   |                                 |  |
|---|---------------------------------|--|
| <b>256GB PCIe-4x4 2280 NVMe Self Encrypted OPAL2 Three Layer Cell Solid State Drive</b> | <b>Form Factor</b>              | M.2 2280                                 |
|   | <b>Capacity</b>                 | 256GB                                    |
|   | <b>NAND Type</b>                | TLC                                      |
|   | <b>Height</b>                   | 0.09 in (2.3 mm)                         |
|   | <b>Width</b>                    | 0.87 in (22 mm)                          |
|   | <b>Weight</b>                   | 0.02 lb (10 g)                           |
|   | <b>Interface</b>                | PCIe NVMe Gen4X4                         |
|   | <b>Maximum Sequential Read</b>  | 4000 MB/s ±20%                           |
|   | <b>Maximum Sequential Write</b> | 2000 MB/s ±20%                           |
|   | <b>Logical Blocks</b>           | 500,118,192                              |
|   | <b>Operating Temperature</b>    | 32° to 158°F (0° to 70°C) [ambient temp] |
|   | <b>Features</b>                 | TCG Opal 2.0; TRIM; L1.2                 |

|   |                    |                  |
|---|--------------------|------------------|
| <b>512GB PCIe-4x4 2280 NVMe Self Encrypted OPAL2 Three Layer Cell Solid State Drive</b> | <b>Form Factor</b> | M.2 2280         |
|   | <b>Capacity</b>    | 512GB            |
|   | <b>NAND Type</b>   | TLC              |
|   | <b>Height</b>      | 0.09 in (2.3 mm) |
|   | <b>Width</b>       | 0.87 in (22 mm)  |
|   | <b>Weight</b>      | 0.02 lb (10 g)   |
|   | <b>Interface</b>   | PCIe NVMe Gen4X4 |
| <b>Maximum Sequential Read</b>  | 6400 MB/s ±20%     |                  |

### Technical Specifications

|                                 |  |
|---------------------------------|--|
| <b>Maximum Sequential Write</b> | 3500 MB/s ±20%                           |
| <b>Logical Blocks</b>           | 1,000,215,215                            |
| <b>Operating Temperature</b>    | 32° to 158°F (0° to 70°C) [ambient temp] |
| <b>Features</b>                 | TCG Opal 2.0; TRIM; L1.2                 |

|                                       |                                 |  |
|---------------------------------------|---------------------------------|--|
| <b>SSD 256GB 2280 PCIe NVMe Value</b> | <b>Form Factor</b>              | M.2 2280                                 |
|                                       | <b>Capacity</b>                 | 256 GB                                   |
|                                       | <b>NAND Type</b>                | TLC                                      |
|                                       | <b>Height</b>                   | 0.09 in (2.3 mm)                         |
|                                       | <b>Width</b>                    | 0.87 in (22 mm)                          |
|                                       | <b>Weight</b>                   | 0.02 lb (10 g)                           |
|                                       | <b>Interface</b>                | PCIe NVMe Gen3X4                         |
|                                       | <b>Maximum Sequential Read</b>  | 1500 MB/s ±20%                           |
|                                       | <b>Maximum Sequential Write</b> | 750 MB/s ±20%                            |
|                                       | <b>Logical Blocks</b>           | 500,118,192                              |
|                                       | <b>Operating Temperature</b>    | 32° to 158°F (0° to 70°C) [ambient temp] |
| <b>Features</b>                       | Pyrite 2.0; TRIM; L1.2          |  |

|                                       |                                 |  |
|---------------------------------------|---------------------------------|--|
| <b>SSD 512GB 2280 PCIe NVMe Value</b> | <b>Form Factor</b>              | M.2 2280                                 |
|                                       | <b>Capacity</b>                 | 512 GB                                   |
|                                       | <b>NAND Type</b>                | TLC                                      |
|                                       | <b>Height</b>                   | 0.09 in (2.3 mm)                         |
|                                       | <b>Width</b>                    | 0.87 in (22 mm)                          |
|                                       | <b>Weight</b>                   | 0.02 lb (10 g)                           |
|                                       | <b>Interface</b>                | PCIe NVMe Gen3X4                         |
|                                       | <b>Maximum Sequential Read</b>  | 1500 MB/s ±20%                           |
|                                       | <b>Maximum Sequential Write</b> | 750 MB/s ±20%                            |
|                                       | <b>Logical Blocks</b>           | 1,000,215,215                            |
|                                       | <b>Operating Temperature</b>    | 32° to 158°F (0° to 70°C) [ambient temp] |
| <b>Features</b>                       | Pyrite 2.0; TRIM; L1.2          |  |



### Technical Specifications

#### NETWORKING/COMMUNICATIONS

|  |   |
|--|---|
| <p><b>Intel® AX211 Wi-Fi 6E + Bluetooth® 5.3 M.2 160MHz CNVi World-Wide WLAN vPro®<sup>1</sup></b></p> | <p><b>Wireless LAN Standards</b></p> <ul style="list-style-type: none"> <li>IEEE 802.11a</li> <li>IEEE 802.11b</li> <li>IEEE 802.11g</li> <li>IEEE 802.11n</li> <li>IEEE 802.11ac</li> <li>IEEE 802.11ax</li> <li>IEEE 802.11d</li> <li>IEEE 802.11e</li> <li>IEEE 802.11h</li> <li>IEEE 802.11i</li> <li>IEEE 802.11k</li> <li>IEEE 802.11r</li> <li>IEEE 802.11v</li> </ul> |
| <p><b>Interoperability</b></p>   | <p>Wi-Fi certified</p>  |
| <p><b>Frequency Band</b></p>   | <ul style="list-style-type: none"> <li>•802.11b/g/n/ax<br/>2.402 – 2.482 GHz</li> <li>•802.11a/n/ac/ax<br/>4.9 – 4.95 GHz (Japan)</li> <li>5.15 – 5.25 GHz</li> <li>5.25 – 5.35 GHz</li> <li>5.47 – 5.725 GHz</li> <li>5.825 – 5.850 GHz</li> <li>5.955 – 6.415 GHz</li> <li>6.435 – 6.515 GHz</li> <li>6.535 – 6.875 GHz</li> <li>6.895 – 7.115 GHz</li> </ul>               |
| <p><b>Data Rates</b></p>   | <ul style="list-style-type: none"> <li>• 802.11b: 1, 2, 5.5, 11 Mbps</li> <li>• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11n: max 300Mbps</li> <li>• 802.11ac : 1733Mbps</li> <li>• 802.11ax : max 2.4Gbps</li> </ul>  |
| <p><b>Modulation</b></p>   | <p>Direct Sequence Spread Spectrum<br/>OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM</p>  |
| <p><b>Security<sup>2</sup></b></p>   | <ul style="list-style-type: none"> <li>• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• WPA3 certification</li> <li>• IEEE 802.11i</li> <li>• WAPI</li> </ul>     |
| <p><b>Network Architecture Models</b></p>  | <p>Ad-hoc (Peer to Peer)<br/>Infrastructure (Access Point Required)</p>   |
| <p><b>Roaming</b></p>  | <p>IEEE 802.11 compliant roaming between access points</p>  |
| <p><b>Output Power<sup>3</sup></b></p>   | <ul style="list-style-type: none"> <li>• 802.11b : +17dBm minimum</li> <li>• 802.11g : +16dBm minimum</li> <li>• 802.11a : +17dBm minimum</li> <li>• 802.11n HT20(2.4GHz) : +14dBm minimum</li> <li>• 802.11n HT40(2.4GHz) : +13dBm minimum</li> </ul>  |

### Technical Specifications

- 802.11n HT20(5GHz) : +14dBm minimum
- 802.11n HT40(5GHz) : +13dBm minimum
- 802.11ac VHT80(5GHz) : +10dBm minimum
- 802.11ac VHT160(5GHz) : +10dBm minimum
- 802.11ax HE40(2.4GHz) : +12dBm minimum
- 802.11ax HE80(5GHz) : +10dBm minimum
- 802.11ax HE160(5GHz) : +10dBm minimum

#### Power Consumption

- Transmit mode 2.0 W
- Receive mode 1.6 W
- Idle mode (PSP) 180 mW (WLAN Associated)
- Idle mode 50 mW (WLAN unassociated)
- Connected Standby 10mW
- Radio disabled 8 mW

#### Power Management

ACPI and PCI Express compliant power management  
802.11 compliant power saving mode

#### Receiver Sensitivity<sup>4</sup>

- 802.11b, 1Mbps : -93.5dBm maximum
- 802.11b, 11Mbps : -84dBm maximum
- 802.11a/g, 6Mbps : -86dBm maximum
- 802.11a/g, 54Mbps : -72dBm maximum
- 802.11n, MCS07 : -67dBm maximum
- 802.11n, MCS15 : -64dBm maximum
- 802.11ac, MCS0(VHT80) : -84dBm maximum
- 802.11ac, MCS9(VHT80) : -59dBm maximum
- 802.11ac, MCS9(VHT160) : -58.5dBm maximum
- 802.11ax, MCS11(HE40): -57dBm maximum
- 802.11ax, MCS11(HE80): -54dBm maximum
- 802.11ax, MCS11(HE160): -53.5dBm maximum

#### Antenna type

High efficiency antenna with spatial diversity, mounted in the display enclosure  
Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications

#### Form Factor

PCI-Express M.2 MiniCard

#### Dimensions

1. Type 2230 : 2.3 x 22.0 x 30.0 mm

#### Weight

1. Type 2230 : 2.8g

#### Operating Voltage

3.3v +/- 9%

#### Temperature

**Operating** 14° to 158° F (-10° to 70° C)  
**Non-operating** -40° to 176° F (-40° to 80° C)

#### Humidity

**Operating** 10% to 90% (non-condensing)  
**Non-operating** 5% to 95% (non-condensing)

#### Altitude

**Operating** 0 to 10,000 ft (3,048 m)  
**Non-operating** 0 to 50,000 ft (15,240 m)

#### LED Activity

LED Amber – Radio OFF; LED White – Radio ON

#### HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Technology

##### Bluetooth Specification

4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant

##### Frequency Band

2402 to 2480 MHz

##### Number of Available Channels

Legacy : 0~79 (1 MHz/CH)  
BLE : 0~39 (2 MHz/CH)

##### Data Rates and Throughput

Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps  
BLE : 1 Mbps data rate; throughput up to 0.2 Mbps  
Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels

## Technical Specifications

|  |  |
|--|--|
|  | Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)  |
| <b>Transmit Power</b>                  | The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 9.5 dBm for BR and EDR.  |
| <b>Power Consumption</b>               | Peak (Tx): 330 mW<br>Peak (Rx): 230 mW<br>Selective Suspend: 17 mW   |
| <b>Bluetooth Software Supported</b>    | Microsoft Windows Bluetooth Software   |
| <b>Link Topology</b>                   |  |
| <b>Power Management</b>                | Microsoft Windows ACPI, and USB Bus Support  |
| <b>Certifications</b>                  | FCC (47 CFR) Part 15C, Section 15.247 & 15.249   |
| <b>Power Management Certifications</b> | ETS 300 328, ETS 300 826<br>Low Voltage Directive IEC950<br>UL, CSA, and CE Mark   |
| <b>Bluetooth Profiles Supported</b>    | BT4.1-ESR 5/6/7 Compliance<br>LE Link Layer Ping<br>LE Dual Mode<br>LE Link Layer<br>LE Low Duty Cycle Directed Advertising<br>LE L2CAP Connection Oriented Channels<br>Train Nudging & Interlaced Scan<br>BT4.2 ESR08 Compliance<br>LE Secure Connection- Basic/Full<br>LE Privacy 1.2 –Link Layer Privacy<br>LE Privacy 1.2 –Extended Scanner Filter Policies<br>LE Data Packet Length Extension<br>FAX Profile (FAX)<br>Basic Imaging Profile (BIP)2<br>Headset Profile (HSP)<br>Hands Free Profile (HFP)<br>Advanced Audio Distribution Profile (A2DP)<br>BT5.2<br>ESR9/10 Compliance<br>LE Advertisement Extensions<br>Channel Selection Algo<br>Limited High Duty Cycle Non-Connectable Advertising<br>2Mbps LE<br>LE Long Range |

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

### Technical Specifications

|  |   |   |
|--|---|---|
| <p><b>Intel® AX211 Wi-Fi 6E + Bluetooth® 5.3 M.2 160MHz CNVi World-Wide WLAN non-vPro®<sup>1</sup></b></p> | <p><b>Wireless LAN Standards</b></p>      | <p>IEEE 802.11a<br/>           IEEE 802.11b<br/>           IEEE 802.11g<br/>           IEEE 802.11n<br/>           IEEE 802.11ac<br/>           IEEE 802.11ax<br/>           IEEE 802.11d<br/>           IEEE 802.11e<br/>           IEEE 802.11h<br/>           IEEE 802.11i<br/>           IEEE 802.11k<br/>           IEEE 802.11r<br/>           IEEE 802.11v</p>     |
|  | <p><b>Interoperability</b></p>            | <p>Wi-Fi certified</p>  |
|  | <p><b>Frequency Band</b></p>              | <ul style="list-style-type: none"> <li>• 802.11b/g/n/ax<br/>2.402 – 2.482 GHz</li> <li>• 802.11a/n/ac/ax<br/>4.9 – 4.95 GHz (Japan)<br/>5.15 – 5.25 GHz<br/>5.25 – 5.35 GHz<br/>5.47 – 5.725 GHz<br/>5.825 – 5.850 GHz<br/>5.955 – 6.415 GHz<br/>6.435 – 6.515 GHz<br/>6.535 – 6.875 GHz<br/>6.895 – 7.115 GHz</li> </ul>   |
|  | <p><b>Data Rates</b></p>                  | <ul style="list-style-type: none"> <li>• 802.11b: 1, 2, 5.5, 11 Mbps</li> <li>• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11n: max 300Mbps</li> <li>• 802.11ac : 1733Mbps</li> <li>• 802.11ax : max 2.4Gbps</li> </ul>  |
|  | <p><b>Modulation</b></p>                  | <p>Direct Sequence Spread Spectrum<br/>           OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM</p>   |
|  | <p><b>Security<sup>2</sup></b></p>        | <ul style="list-style-type: none"> <li>• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• WPA3 certification</li> <li>• IEEE 802.11i</li> <li>• WAPI</li> </ul> |
|  | <p><b>Network Architecture Models</b></p> | <p>Ad-hoc (Peer to Peer)<br/>           Infrastructure (Access Point Required)</p>  |
|  | <p><b>Roaming</b></p>                     | <p>IEEE 802.11 compliant roaming between access points</p>  |
|  | <p><b>Output Power<sup>3</sup></b></p>    | <ul style="list-style-type: none"> <li>• 802.11b : +17dBm minimum</li> <li>• 802.11g : +16dBm minimum</li> <li>• 802.11a : +17dBm minimum</li> <li>• 802.11n HT20(2.4GHz) : +14dBm minimum</li> <li>• 802.11n HT40(2.4GHz) : +13dBm minimum</li> <li>• 802.11n HT20(5GHz) : +14dBm minimum</li> <li>• 802.11n HT40(5GHz) : +13dBm minimum</li> </ul>                      |

## Technical Specifications

|  |  |
|--|--|
|  | <ul style="list-style-type: none"> <li>• 802.11ac VHT80(5GHz) : +10dBm minimum</li> <li>• 802.11ac VHT160(5GHz) : +10dBm minimum</li> <li>• 802.11ax HE40(2.4GHz) : +12dBm minimum</li> <li>• 802.11ax HE80(5GHz) : +10dBm minimum</li> <li>• 802.11ax HE160(5GHz) : +10dBm minimum</li> </ul>   |
| <b>Power Consumption</b>   | <ul style="list-style-type: none"> <li>• Transmit mode 2.0 W</li> <li>• Receive mode 1.6 W</li> <li>• Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>• Idle mode 50 mW (WLAN unassociated)</li> <li>• Connected Standby 10mW</li> <li>• Radio disabled 8 mW</li> </ul>  |
| <b>Power Management</b>  | ACPI and PCI Express compliant power management<br>802.11 compliant power saving mode  |
| <b>Receiver Sensitivity<sup>4</sup></b>  | <ul style="list-style-type: none"> <li>• 802.11b, 1Mbps : -93.5dBm maximum</li> <li>• 802.11b, 11Mbps : -84dBm maximum</li> <li>• 802.11a/g, 6Mbps : -86dBm maximum</li> <li>• 802.11a/g, 54Mbps : -72dBm maximum</li> <li>• 802.11n, MCS07 : -67dBm maximum</li> <li>• 802.11n, MCS15 : -64dBm maximum</li> <li>• 802.11ac, MCS0(VHT80) : -84dBm maximum</li> <li>• 802.11ac, MCS9(VHT80) : -59dBm maximum</li> <li>• 802.11ac, MCS9(VHT160) : -58.5dBm maximum</li> <li>• 802.11ax, MCS11(HE40) : -57dBm maximum</li> <li>• 802.11ax, MCS11(HE80) : -54dBm maximum</li> <li>• 802.11ax, MCS11(HE160) : -53.5dBm maximum</li> </ul> |
| <b>Antenna type</b>  | High efficiency antenna with spatial diversity, mounted in the display enclosure<br>Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications  |
| <b>Form Factor</b>   | PCI-Express M.2 MiniCard   |
| <b>Dimensions</b>  | 1. Type 2230: 2.3 x 22.0 x 30.0 mm   |
| <b>Weight</b>  | 1. Type 2230: 2.8g   |
| <b>Operating Voltage</b>   | 3.3v +/- 9%  |
| <b>Temperature</b>   | <b>Operating</b> 14° to 158° F (-10° to 70° C)<br><b>Non-operating</b> -40° to 176° F (-40° to 80° C)  |
| <b>Humidity</b>  | <b>Operating</b> 10% to 90% (non-condensing)<br><b>Non-operating</b> 5% to 95% (non-condensing)  |
| <b>Altitude</b>  | <b>Operating</b> 0 to 10,000 ft (3,048 m)<br><b>Non-operating</b> 0 to 50,000 ft (15,240 m)  |
| <b>LED Activity</b>  | LED Amber Radio OFF; LED Off – Radio ON  |
| <b>HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Technology</b> |  |
| <b>Bluetooth Specification</b>   | 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant  |
| <b>Frequency Band</b>  | 2402 to 2480 MHz   |
| <b>Number of Available Channels</b>  | Legacy: 0~79 (1 MHz/CH)<br>BLE: 0~39 (2 MHz/CH)  |
| <b>Data Rates and Throughput</b>   | Legacy: 3 Mbps data rate; throughput up to 2.17 Mbps<br>BLE: 1 Mbps data rate; throughput up to 0.2 Mbps<br>Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels<br>Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)   |

## Technical Specifications

|  |  |
|--|--|
| <b>Transmit Power</b>                  | The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 9.5 dBm for BR and EDR.  |
| <b>Power Consumption</b>               | Peak (Tx): 330 mW<br>Peak (Rx): 230 mW<br>Selective Suspend: 17 mW   |
| <b>Bluetooth Software Supported</b>    | Microsoft Windows Bluetooth Software   |
| <b>Link Topology</b>                   |  |
| <b>Power Management</b>                | Microsoft Windows ACPI, and USB Bus Support  |
| <b>Certifications</b>                  | FCC (47 CFR) Part 15C, Section 15.247 & 15.249   |
| <b>Power Management Certifications</b> | ETS 300 328, ETS 300 826<br>Low Voltage Directive IEC950<br>UL, CSA, and CE Mark   |
| <b>Bluetooth Profiles Supported</b>    | BT4.1-ESR 5/6/7 Compliance<br>LE Link Layer Ping<br>LE Dual Mode<br>LE Link Layer<br>LE Low Duty Cycle Directed Advertising<br>LE L2CAP Connection Oriented Channels<br>Train Nudging & Interlaced Scan<br>BT4.2 ESR08 Compliance<br>LE Secure Connection- Basic/Full<br>LE Privacy 1.2 –Link Layer Privacy<br>LE Privacy 1.2 –Extended Scanner Filter Policies<br>LE Data Packet Length Extension<br>FAX Profile (FAX)<br>Basic Imaging Profile (BIP)2<br>Headset Profile (HSP)<br>Hands Free Profile (HFP)<br>Advanced Audio Distribution Profile (A2DP)<br>BT5.2<br>ESR9/10 Compliance<br>LE Advertisement Extensions<br>Channel Selection Algo<br>Limited High Duty Cycle Non-Connectable Advertising<br>2Mbps LE<br>LE Long Range |

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

## Technical Specifications

**Intel(R) 5G Solution  
5000<sup>1</sup>****Technology/Operating  
bands**

## WCDMA/HSPA+ operating bands:

Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)

Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)

Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)

Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)

Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)

## LTE FDD/TDD operating bands:

Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)

Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)

Band 3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL)

Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)

Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)

Band 7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL)

Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)

Band 12: 699 to 716 MHz (UL), 729 to 746 MHz (DL)

Band 13: 777 to 787 MHz (UL), 746 to 756 MHz (DL)

Band 14: 788 to 798 MHz (UL), 758 to 768 MHz (DL)

Band 17: 704 to 716 MHz (UL), 734 to 746 MHz (DL)

Band 18: 815 to 830 MHz (UL), 860 to 875 MHz (DL)

Band 19: 830 to 845 MHz (UL), 875 to 890 MHz (DL)

Band 20: 832 to 862 MHz (UL), 791 to 821 MHz (DL)

Band 25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL)

Band 26: 814 to 849 MHz (UL), 859 to 894 MHz (DL)

Band 28: 703 to 748 MHz (UL), 758 to 803 MHz (DL)

Band 29: 717 to 728 MHz (DL)

Band 30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL)

Band 32: 1452 to 1496 MHz (DL)

Band 34: 2010 to 2025 MHz (UL/DL)

Band 38: 2570 to 2620 MHz (UL/DL)

Band 39: 1880 to 1920 MHz (UL/DL)

Band 40: 2300 to 2400 MHz (UL/DL)

Band 41: 2496 to 2690 MHz (UL/DL)

Band 42: 3400 to 3600 MHz (UL/DL)

Band 43: 3400 to 3800 MHz (UL/DL)

Band 46: 5150 to 5925 MHz (DL)

Band 48: 3550 to 3700 MHz (UL/DL)

Band 66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL)

Band 71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)

## 5GNR Sub 6GHZ

n1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)

n2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)

n3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL)

n5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)

n7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL)

n8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)

n20: 832 to 862 MHz (UL), 791 to 821 MHz (DL)

n25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL)

n28: 703 to 748 MHz (UL), 758 to 803 MHz (DL)

n38: 2570 to 2620 MHz (UL/DL)

n40: 2300 to 2400 MHz (UL/DL)

n41: 2496 to 2690 MHz (UL/DL)

n48: 3550 to 3700 MHz (UL/DL)

n66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL)

n71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)

n77: 3300 to 4200 MHz (UL/DL)

n78: 3300 to 3800 MHz (UL/DL)

n79: 4400 to 5000 MHz (UL/DL)



### Technical Specifications

|  |  |
|--|--|
| <b>Wireless protocol standards</b>             | 5G NR Air Interface<br>3GPP Rel15 5G NR sub-6<br>LTE Rel14<br>20 layers and 2 Gbps downlink (DL) throughput – 4 × 4 MIMO across 5x CA<br>200 Mbps/uplink (UL) throughput – 40 MHz ULCA and 256 QAM WCDMA R99,<br>3GPP Release 5, 6, 7 and 8 UMTS Specification |
| <b>GPS</b>                                     | Standalone, A-GPS (MS-A, MS-B)   |
| <b>GPS bands</b>                               | GPS: L1 (1575.42MHz)<br>GLONASS: L1 (1602MHz)<br>BeidouB1(1561.098MHz)<br>Galileo E1 (1575.42)<br>QZSS(1575.42 MHz)  |
| <b>Maximum data rates</b>                      | SA 5G/NR sub-6 Peak: DL4.67Gbps/ UL 1.25Gbps<br>5G NSA sub 6G : DL: 3.8 Gbps/UL 700Mbps<br>LTE: ue-CategoryDL 19, (DL : 1.6 Gbps )<br>ue-CategoryUL 13 , (UL: 150Mbps)<br>DC-HSPA+: 42 Mbps (Download), 11.5 Mbps (Upload)                                     |
| <b>Maximum output power</b>                    | LTE: 23 dBm in all band except B41<br>LTE B41 HPUE = 26dBm<br>NR: 23 dBm in all band except n41, n77, n78 and n79<br>LTE n41, n77, n78 and n79 HPUE = 26dBm<br>HSPA+: 23.5 dBm   |
| <b>Maximum power consumption</b>               | 5G Sub 6 : 2500 mA<br>LTE: 1,300 mA (peak); 1100 mA (average)<br>HSPA+: 1,100 mA (peak); 800 mA (average)  |
| <b>Form Factor</b>                             | M.2, 3042-S3 Key B   |
| <b>Weight</b>                                  | 8 g  |
| <b>Dimensions (Length x Width x Thickness)</b> | 52 mm × 30 mm × 2.6 mm   |

1. 5G module is an optional feature that must be configured at purchase. AT&T and T-Mobile networks supported in the U.S. Module designed for 5G networks as carriers deploy Evolved-Universal Terrestrial Radio Access New Radio Dual Connectivity (ENDC) with both 100MHz of 5G NR and LTE channel bandwidth, using 256QAM 4x4 as defined by 3GPP, requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. 5G not available on all products, in all regions. Backwards compatible to 4G LTE and 3G HSPA technologies. 5G module planned to be available in select countries, where carrier supported.

### Technical Specifications

|   |  |   |
|---|--|---|
| <b>Intel® XMM™ 7560 R+<br/>LTE-Advanced Pro<sup>1</sup></b> | <b>Technology/Operating bands</b>              | FDD LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3), 1700/2100 (Band 4), 850 (Band 5), 2600 (Band 7), 900 (Band 8), 700 (Band 12 lower), 700 (Band 13 upper), 700 (Band 14 upper), 700 (Band 17 lower), 850 (Band 18 lower), 850 (Band 19 upper), 800 (Band 20), 1900 (Band 25), 850 (Band 26), 700 (Band 28), 700 (Band 29 RX only), 2300 (Band 30), 1700/2100 (Band 66), 600 (band 71).<br>TDD LTE: 2100 (Band 34), 2600 (Band 38), 1900 (Band 39), 2400 (Band 40), 2500 (Band 41), 3500 (Band 42), 3700 (Band 43), 3700 (band 48), 5200 (Band 46 RX only) MHz;<br>HSPA+: 2100 (Band 1), 1900 (Band 2), 1700/2100 (Band 4), 850 (Band 5), 900 (Band 8) MHz |
|   | <b>Wireless protocol standards</b>             | 3GPP Release 12 LTE Specification DL-CAT.16, DL 100MHz BW throughput up to 978Mbps; UL-CAT.13 40MHz throughput up to 150Mbps<br>WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification  |
|   | <b>GPS</b>                                     | Standalone GPS/Beidou/Glonass, A-GPS (MS-A, MS-B)   |
|   | <b>GPS bands</b>                               | 1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz, Beidou 1561.098 MHz  |
|   | <b>Maximum data rates</b>                      | LTE: 978 Mbps (Download), 150 Mbps (Upload)<br>DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload)<br>HSPA+: 21Mbps (Download), 5.76 Mbps (Upload)   |
|   | <b>Maximum output power</b>                    | LTE: 23 dBm in all band except B41<br>LTE B41 HPUE = 26dBm<br>HSPA+: 23.5 dBm   |
|   | <b>Maximum power consumption</b>               | LTE: 1,200 mA (peak); 900 mA (average)<br>HSPA+: 1,100 mA (peak); 800 mA (average)  |
|   | <b>Form Factor</b>                             | M.2, 3042-S3 Key B  |
|   | <b>Weight</b>                                  | 6 g   |
|   | <b>Dimensions (Length x Width x Thickness)</b> | 42 x 30 x 2.3 mm  |
|   | <b>eSIM</b>                                    | Support   |

1. Mobile Broadband is an optional feature, Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE is not available on all products, in all regions.

## Technical Specifications

|  |  |  |
|--|--|--|
| <b>Near Field Communications Controller (optional)</b> | <b>Dimensions (L x W x H)</b>  | Module 25 mm by 10 mm by 2.0 mm  |
|  | <b>Chipset</b>   | NPC100   |
|  | <b>System interface</b>  | I2C  |
|  | <b>NFC RF standards</b>  | ISO/IEC 14443 A<br>ISO/IEC 14443 B<br>ISO/IEC 15693<br>ISO/IEC 18092<br>ECMA-340 NFCIP-1 Target and Initiator<br>ECMA-320 NFCIP-2  |
|  | <b>NFC Forum Support</b>   | Tag Type 1, Type 2, Type3 and Type 4, NFCIP-1 and NFCIP-2  |
|  | <b>Reader (PCD-VCD) Mode</b>   | ISO/IEC 14443 A<br>ISO/IEC 14443 B<br>ISO/IEC 15693<br>MIFARE 1K<br>MIFARE 4K<br>MIFARE DESFire<br>FeliCa<br>Jewel and Topaz cards |
|  | <b>Card Emulation (PICC-VICC) Mode</b>   | ISO/IEC 14443 A<br>ISO/IEC 14443 B and B'<br>MIFARE<br>FeliCa  |
|  | <b>Frequency</b>   | 13.56 MHz  |
|  | <b>NFC Modes Supported</b>   | Reader/Writer, Peer-to-Peer  |
|  | <b>Raw RF Data Rates</b>   | 106, 212, 424, 848 kbps  |
|  | <b>Operating temperature</b>   | 0°C to 70°C  |
|  | <b>Storage temperature</b>   | -20°C to 125°C   |
|  | <b>Humidity</b>  | 10-90% operating<br>5-95% non-operating  |
|  | <b>Supply Operating voltage</b>  | 4.35 to 5.25 Volts   |
|  | <b>I/O Voltage</b>   | 1.8V or 3.3V   |
|  | <b>Power Consumption (Booster enable, VBAT= 3.3V, VCC_BOOST = 5V)</b>                    |  |
|  | <b>Mode</b>  | Power Consumption, Typical   |
|  | <b>Polling</b>   | 7.3 mA   |
|  | <b>Detected Test Tag Type 1</b>  | Total 283.8 mA<br>Net Module 236.8 mA  |
|  | <b>Detected Test Tag Type 2</b>  | Total 288.8 mA<br>Net Module 241.8 mA  |
|  | <b>Detected Test Tag Type 3</b>  | Total 287.7 mA<br>Net Module 240.7 mA  |
|  | <b>Detected Test Tag Type 4</b>  | Total 282.3 mA<br>Net Module 235.3 mA  |
| <b>Antenna</b>   | Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module. |  |

### Technical Specifications

#### POWER

1. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors

|  |                               |   |                              |
|--|-------------------------------|---|------------------------------|
| <b>AC Adapter 45 Watt nPFC Standard USB type C Straight 1.8m</b> | <b>Dimensions (H x W x D)</b> | 94.0mm x 40.0mm x 26.5mm  |                              |
|  | <b>Weight</b>                 | 192.5g +/-10%   |                              |
| <b>Output</b>  | <b>Input</b>                  | <b>Input Efficiency</b> Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec:<br>5V : 81.5%<br>9V : 86.7%<br>12V : 87.41%<br>15V : 87.8%  |                              |
|  | <b>Input frequency range</b>  | 47 ~ 63Hz   |                              |
|  | <b>Input AC current</b>       | Max. 1.4 A at 90 Vac  |                              |
|  | <b>Output power</b>           | 5V/15W<br>9V/27W<br>12V/36W<br>15V/45W  |                              |
|  | <b>DC output</b>              | 5V/9V/12V/15V   |                              |
|  | <b>Hold-up time</b>           | 5ms at 115 Vac input  |                              |
|  | <b>Output current limit</b>   | <5.0A   |                              |
|  | <b>Connector</b>              | C6  |                              |
|  | <b>Environmental Design</b>   | <b>Operating temperature</b>  | 32°F to 95°F (0° to 35°C)    |
|  |                               | <b>Non-operating (storage) temperature</b>  | -4°F to 185°F (-20° to 85°C) |
| <b>Altitude</b>  |                               | 0 to 16,400 ft (0 to 5000m)   |                              |
| <b>Humidity</b>  |                               | 20% to 95%  |                              |
| <b>EMI and Safety Certifications</b>                             | <b>Storage Humidity</b>       | 10% to 95%  |                              |
|  | <b>Eg:</b>                    |   |                              |
|  |                               | *CE Mark - full compliance with LVD and EMC directives<br>* Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1, Class1, SELV;<br>Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE.<br>* MTBF - over 200,000 hours at 25°C ambient condition. |                              |

|  |                               |   |
|--|-------------------------------|---|
| <b>AC Adapter 65 Watt nPFC Slim USB type C Straight 1.8m</b> | <b>Dimensions (H x W x D)</b> | 88 x 53.5 x 21mm  |
|  | <b>Weight</b>                 | unit: 220g +/- 10g  |
| <b>Input</b>   | <b>Input Efficiency</b>       | 81.5% min at 115 Vac/ 230Vac @ 5V/3A<br>86.7% min at 115 Vac/ 230Vac @ 9V/3A<br>88% min at 115 Vac/ 230Vac @ 12V/5A<br>89% min at 115 Vac/ 230Vac @ 15V/4.33A<br>89% min at 115 Vac/ 230Vac @ 20V/3.25A |
|  | <b>Input frequency range</b>  | 47 ~ 63 Hz  |
|  | <b>Input AC current</b>       | 1.6 A at 90 VAC and maximum load  |

### Technical Specifications

|                             |  |  |
|-----------------------------|--|--|
| <b>Output</b>               | <b>Output power</b>                        | 65W  |
|                             | <b>DC output</b>                           | 5V/9V/12V/15V/20V  |
| <b>Connector</b>            | <b>Hold-up time</b>                        | 5ms at 115 Vac input   |
|                             | <b>Output current limit</b>                | <8.0A  |
| <b>Environmental Design</b> | C6   |  |
|                             | <b>Operating temperature</b>               | 32°F to 95°F (0° to 35°C)  |
|                             | <b>Non-operating (storage) temperature</b> | -4°F to 185°F (-20° to 85°C)   |
|                             | <b>Altitude</b>                            | 0 to 16,400 ft (0 to 5000m)  |
|                             | <b>Humidity</b>                            | 5% to 95%  |
|                             | <b>Storage Humidity</b>                    | 5% to 95%  |
|                             | <b>EMI and Safety Certifications</b>       | <p>Eg:<br/>           *CE Mark - full compliance with LVD and EMC directives<br/>           * Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1 , Class1, SELV;<br/>           Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE.<br/>           * MTBF - over 200,000 hours at 25°C ambient condition.</p> |

|  |  |                              |  |   |
|--|--|------------------------------|--|---|
| <b>AC Adapter 65 Watt nPFC Standard USB type C Straight 1.8m</b> | <b>Dimensions (H x W x D)</b>              | 90.0mm x 51.0mm x 28.5mm     |  |   |
|  | <b>Weight</b>                              | 250g +/-10%                  |  |   |
|  | <b>Input</b>                               | <b>Input Efficiency</b>      | Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec:<br>5V : 81.5%<br>9V : 86.7%<br>12V : 88%<br>15V : 88%<br>20V : 89% |   |
|  |  | <b>Input frequency range</b> | 47 ~ 63Hz  |   |
|  |  | <b>Input AC current</b>      | Max. 1.6 A at 90 Vac   |   |
|  |  | <b>Output</b>                | <b>Output power</b>  | 5V/15W<br>9V/27W<br>12V/60W<br>15V/60W<br>20V/65W |
|  |  |                              | <b>DC output</b>   | 5V/9V/12V/15V/20V                                 |
|  | <b>Hold-up time</b>                        |                              | 5ms at 115 Vac input   |   |
|  | <b>Connector</b>                           | <b>Output current limit</b>  | <8.0A  |   |
|  |  | C6                           |  |   |
| <b>Environmental Design</b>                                      |  | <b>Operating temperature</b> | 32°F to 95°F (0° to 35°C)  |   |
|  | <b>Non-operating (storage) temperature</b> | -4°F to 185°F (-20° to 85°C) |  |   |

### Technical Specifications

|                                      |  |                             |
|--------------------------------------|--|-----------------------------|
|                                      | <b>Altitude</b>  | 0 to 16,400 ft (0 to 5000m) |
|                                      | <b>Humidity</b>  | 20% to 95%                  |
|                                      | <b>Storage Humidity</b>  | 10% to 95%                  |
| <b>EMI and Safety Certifications</b> | <b>Eg:</b>   |                             |
|                                      | *CE Mark - full compliance with LVD and EMC directives   |                             |
|                                      | * Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1, Class1, SELV; |                             |
|                                      | Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE.                      |                             |
|                                      | * MTBF - over 200,000 hours at 25°C ambient condition.   |                             |

|   |  |  |                               |
|---|--|--|-------------------------------|
| <b>HP 3-cell Long Life Li-Ion (38 Wh)<sup>1</sup></b> | <b>Dimensions (H x W x D)</b>            | 251.8 x 66.1 x 6.82mm (9.91 x 2.6 x 0.27 inch) |                               |
|   | <b>Weight</b>                            | 0.184kg +/- 10g(0.406lb)                       |                               |
|   | <b>Cells/Type</b>                        | 3cell Lithium-Ion Polymer cell / 564975        |                               |
|   | <b>Energy</b>                            | <b>Voltage</b>                                 | 11.58V                        |
|   |  | <b>Amp-hour capacity</b>                       | 3.283Ah                       |
|   |  | <b>Watt-hour capacity<sup>1</sup></b>          | 38Wh                          |
|   |  | <b>Temperature</b>                             |                               |
|   |  | <b>Operating (Charging)</b>                    | 32° to 113° F (0° to 45° C)   |
|   |  | <b>Operating (Discharging)</b>                 | 14° to 140° F (-10° to 60° C) |
|   |  | <b>Fuel Gauge LED</b>                          | NA                            |
|   | <b>Warranty</b>                          | Follow product spec                            |                               |
|   | <b>Optional Travel Battery Available</b> | No   |                               |

|   |  |   |                               |
|---|--|---|-------------------------------|
| <b>HP 3-cell Long Life Li-Ion (51 Wh)<sup>1</sup></b> | <b>Dimensions (H x W x D)</b>            | 251.8*70.3*6.82mm (9.91*2.77*0.27 inch) |                               |
|   | <b>Weight</b>                            | 0.229kg +/- 10g(0.505 lb)               |                               |
|   | <b>Cells/Type</b>                        | 3cell Lithium-Ion Polymer cell / 566075 |                               |
|   | <b>Energy</b>                            | <b>Voltage</b>                          | 11.58V                        |
|   |  | <b>Amp-hour capacity</b>                | 4.431Ah                       |
|   |  | <b>Watt-hour capacity<sup>1</sup></b>   | 51.3Wh                        |
|   |  | <b>Temperature</b>                      |                               |
|   |  | <b>Operating (Charging)</b>             | 32° to 113° F (0° to 45° C)   |
|   |  | <b>Operating (Discharging)</b>          | 14° to 140° F (-10° to 60° C) |
|   |  | <b>Fuel Gauge LED</b>                   | NA                            |
|   | <b>Warranty</b>                          | Follow product spec                     |                               |
|   | <b>Optional Travel Battery Available</b> | No                                      |                               |

---

## Technical Specifications

### AUDIO

|                                   |  |
|-----------------------------------|--|
| <b>HD Stereo Codec</b>            | Realtek ALC3315  |
| <b>Audio I/O Ports</b>            | Headset: CTIA only and Headphone-out   |
| <b>Internal Speaker Amplifier</b> | Cirrus Logic High-Efficiency Boosted Class D Amplifier   |
| <b>Multi-streaming Capable</b>    | Playback multi-streaming can be enabled in the audio control panel to allow independent audio.<br>Following MSFT Behaviour |
| <b>Sampling</b>                   | DAC: 44.1k/48kHz<br>ADC: 48kHz   |
| <b>Wavetable Syntheses</b>        |  |
| <b>Analog Audio</b>               | Support 3.5mm Headset: CTIA only and Headphone-out   |
| <b># of Channels on Line-Out</b>  |  |
| <b>Internal Speaker</b>           | Yes  |

---

### FINGERPRINT READER

|                                    |                               |
|------------------------------------|-------------------------------|
| <b>Sensor vendor</b>               | Synaptics FS7604              |
| <b>Sensor type</b>                 | Capacitive                    |
| <b>DPI resolution</b>              | 363DPI                        |
| <b>Scan area</b>                   | 7.4x6mm sensor area           |
| <b>False Rejection Rate</b>        | <1%                           |
| <b>False Acceptance Rate</b>       | 1:50K FAR                     |
| <b>Mobile Voltage Operation</b>    | 3.0V to 3.6V                  |
| <b>Operating Temperature</b>       | 0~60°C                        |
| <b>Current Consumption</b>         | 100mA Max                     |
| <b>Image</b>                       |                               |
| <b>Low Latency Wait For Finger</b> | 260 uA                        |
| <b>Capture Rate</b>                | <30msec per image             |
| <b>ESD Resistance</b>              | IEC 61000-4-2 4B (+/-15KV)    |
| <b>Detection Matrix</b>            | 363 dpi / 7.4x6mm sensor area |

---



### Technical Specifications

#### ENVIRONMENTAL DATA

|  |  |                     |   |
|--|--|---------------------|---|
| <b>Eco-Label Certifications &amp; declarations</b>                         | <p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> <li>• IT ECO declaration</li> <li>• US ENERGY STAR®</li> <li>• US Federal Energy Management Program (FEMP)</li> <li>• EPEAT<sup>®</sup> Gold registered in the United States. See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.</li> <li>• TCO Certified</li> <li>• China Energy Conservation Program (CECP)</li> <li>• China State Environmental Protection Administration (SEPA)</li> <li>• Taiwan Green Mark</li> <li>• Korea Eco-label</li> <li>• Japan PC Green label*</li> </ul> |                     |   |
| <b>Sustainable Impact Specifications</b>                                   | <ul style="list-style-type: none"> <li>• Ocean-bound plastic in Speaker</li> <li>• 60% post-consumer recycled plastic</li> <li>• Low halogen</li> <li>• Outside Box and corrugated cushions are 100% sustainably sourced and recyclable</li> <li>• Molded Paper Pulp Cushion inside box is 100% sustainably sourced and recyclable</li> <li>• Bulk packaging available</li> </ul>  |                     |   |
| <b>System Configuration</b>  | <p>The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a “Typically Configured Notebook”.</p>   |                     |   |
| <b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b> | <b>115VAC, 60Hz</b>  | <b>230VAC, 50Hz</b> | <b>100VAC, 50Hz</b>                             |
| Normal Operation (Sort idle)   | 5.88 W   | 6.17 W              | 5.92 W  |
| Normal Operation (Long idle)   | 1.66 W   | 1.85 W              | 1.76 W  |
| Sleep  | 1.66 W   | 1.85 W              | 1.76 W  |
| Off  | 0.46 W   | 0.48 W              | 0.41 W  |
|  | <p>Note:<br/>Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>   |                     |   |
| <b>Heat Dissipation*</b>   | <b>115VAC, 60Hz</b>  | <b>230VAC, 50Hz</b> | <b>100VAC, 50Hz</b>                             |
| Normal Operation (Short idle)  | 20.1 BTU/hr  | 21.1 BTU/hr         | 20.2 BTU/hr                                     |
| Normal Operation (Long idle)   | 5.7 BTU/hr   | 6.3 BTU/hr          | 6 BTU/hr  |
| Sleep  | 5.7 BTU/hr   | 6.3 BTU/hr          | 6 BTU/hr  |
| Off  | 1.6 BTU/hr   | 1.6 BTU/hr          | 1.4 BTU/hr                                      |
|  | <p>*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.</p>   |                     |   |
| <b>Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)</b> | Sound Power<br>(L <sub>WAd</sub> , bels)   |                     | Sound Pressure<br>(L <sub>pAm</sub> , decibels) |

### Technical Specifications

|                                  |  |   |       |
|----------------------------------|--|---|-------|
| Typically Configured – Idle      | 2.9  | 21.6                                    |       |
| Fixed Disk – Random writes       | 3.6  | 28.5                                    |       |
| Optical Drive – Sequential reads | 4.1  | 33.2                                    |       |
| <b>Longevity and Upgrading</b>   | This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the   |   |       |
|                                  | Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.   |   |       |
| <b>Additional Information</b>    | <ul style="list-style-type: none"> <li>• This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li> <li>• This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>• This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>• This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see <a href="http://www.epeat.net">www.epeat.net</a></li> <li>• Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li> <li>• This product is 95.4% recycle-able when properly disposed of at end of life.</li> </ul>   |   |       |
| <b>Packaging Materials</b>       | <b>External:</b>   | PAPER/Corrugated                        | 269 g |
|                                  |  | PAPER/Paper                             | 3 g   |
|                                  |  | PAPER/Molded Pulp                       | 108 g |
|                                  | <b>Internal:</b>   | PLASTIC/Polyethylene low density - LDPE | 13 g  |
|                                  | The plastic packaging material contains at least 0.0% recycled content.  |   |       |
|                                  | The corrugated paper packaging materials contains at least 59.1% recycled content.   |   |       |
| <b>RoHS Compliance</b>           | <p>HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.</p> <p>We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.</p> <p>We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve.</p> <p>To obtain a copy of the HP RoHS Compliance Statement, see <a href="#">HP RoHS position statement</a>.</p> |   |       |
| <b>Material Usage</b>            | <p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html">http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html</a>):</p> <ul style="list-style-type: none"> <li>• Asbestos</li> <li>• Certain Azo Colorants</li> <li>• Certain Brominated Flame Retardants – may not be used as flame retardants in plastics</li> <li>• Cadmium</li> <li>• Chlorinated Hydrocarbons</li> </ul>  |   |       |

### Technical Specifications

|   |   |
|---|---|
|   | <ul style="list-style-type: none"> <li>• Chlorinated Paraffins</li> <li>• Bis(2-Ethylhexyl) phthalate (DEHP)</li> <li>• Benzyl butyl phthalate (BBP)</li> <li>• Dibutyl phthalate (DBP)</li> <li>• Diisobutyl phthalate (DIBP)</li> <li>• Formaldehyde</li> <li>• Halogenated Diphenyl Methanes</li> <li>• Lead carbonates and sulfates</li> <li>• Lead and Lead compounds</li> <li>• Mercuric Oxide Batteries</li> <li>• Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>• Ozone Depleting Substances</li> <li>• Polybrominated Biphenyls (PBBs)</li> <li>• Polybrominated Biphenyl Ethers (PBBEs)</li> <li>• Polybrominated Biphenyl Oxides (PBBOs)</li> <li>• Polychlorinated Biphenyl (PCB)</li> <li>• Polychlorinated Terphenyls (PCT)</li> <li>• Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.</li> <li>• Radioactive Substances</li> <li>• Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul> |
| <b>Packaging Usage</b>                              | <p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>   |
| <b>End-of-life Management and Recycling</b>         | <p>HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/go/reuse-recycle">http://www.hp.com/go/reuse-recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="http://www.hp.com/go/recyclers">http://www.hp.com/go/recyclers</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>   |
| <b>HP, Inc. Corporate Environmental Information</b> | <p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report<br/> <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a></p> <p>Eco-label certifications<br/> <a href="http://www8.hp.com/us/en/hp-information/environment/ecolabels.html">http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</a></p> <p>ISO 14001 certificates:<br/> <a href="http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842">http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842</a><br/> and<br/> <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</a></p>  |

### Technical Specifications

|                  |  |
|------------------|--|
| <b>footnotes</b> | <ul style="list-style-type: none"><li>• Percentage of ocean-bound plastic contained in each component varies by product</li><li>• Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.</li><li>• External power supplies, WWAN modules, power cords, cables and peripherals excluded.</li><li>• 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.</li><li>• Fiber cushions made from 100% recycled wood fiber and organic materials.</li></ul> |
|------------------|--|

### COUNTRY OF ORIGIN

China

### Options and Accessories (Sold separately and availability may vary by country)

#### DOCKING (Sold Separately)

|  |   |
|--|---|
| <b>Docking station model #1</b>  | HP Thunderbolt Dock G2  |
| <b>Total number of supported displays (incl. the notebook display)</b> | 4   |
| <b>Max. resolutions supported</b>                                      | Dual 4K @30Hz or dual 4K UHD @ 60Hz is supported<br>Single 8K@ 30Hz (multiple tiles) for Thunderbolt hosts<br>Non-TBT hosts DP 1.4 in high res mode (1) 8K video single cable@30Hz [10]   |
| <b>Dock Connectors</b>   | 2xDP, 1xVGA, 1xTB, 1xUSB-C alt-mode   |
| <b>Technical limitations</b>   | Thunderbolt Hosts:<br>Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.<br>Max resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in High Resolution mode @30Hz<br>Non-Thunderbolt hosts:<br>The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is<br>(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port<br>Non-Thunderbolt hosts support (3) displays with a max resolution of: (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz. |
| <b>Docking station model #2</b>  | HP USB-C Dock G5  |
| <b>Total number of supported displays (incl. the notebook display)</b> | 3   |
| <b>Max. resolutions supported</b>                                      | Dual 5K@ 30Hz + (1) 4K UHD (multi-function mode) [10]   |
| <b>Dock Connectors</b>   | 1xHDMI, 2xDP  |
| <b>Technical limitations</b>   | Highest resolution with dual displays is two 8K@ 60Hz host in High Resolution mode.<br>Three maximum displays supported are two 5K@ 30 Hz on DP ports plus one 4K UHD@ 30 Hz on HDMI in multi-function mode<br>The highest resolution for a non-Thunderbolt host in Multi-function mode is a single 5K dual cable (using both DP ports) + (1) 4K on HDMI port.  |
| <b>Docking station model #3</b>  | HP USB-C/A Universal Dock G2  |
| <b>Total number of supported displays (incl. the notebook display)</b> | 3   |
| <b>Max. resolutions supported</b>                                      | Triple 4K UHD@ 60Hz [10]  |
| <b>Dock Connectors</b>   | 1xHDMI, 2xDP  |
| <b>Technical limitations</b>   | The best resolution for dual or triple displays is 4K UHD@ 60Hz.<br>For use with the USB-A adapter that comes in the box the maximum number of displays supported is (2) 4k x 60 Hz on the Type-A Gen 1 connection from the host  |

### Options and Accessories (Sold separately and availability may vary by country)

| Type                              | Description                               | Part Number     |
|-----------------------------------|---|-----------------|
| Audio/Video                       | HP Wired USB-A Stereo Headset             | 428K6AA         |
|                                   | HP Wired 3.5mm Stereo Headset             | 428K7AA         |
| Cases                             | HP Executive 15.6 Backpack                | 6KD07AA         |
|                                   | HP Executive 15.6 Top Load                | 6KD06AA         |
|                                   | HP Executive Slim 14.1 Top Load           | 6KD04AA         |
|                                   | HP Prelude G2 15.6 Backpack               | 1E7D6AA         |
|                                   | HP Prelude G2 15.6 Top Load               | 1E7D7AA         |
|                                   | HP Prelude Pro Recycled 15.6 Backpack     | 1X644AA         |
|                                   | HP Prelude Pro Recycled 15.6 Top Load     | 1X645AA         |
|                                   | HP Renew 14 Laptop Sleeve                 | 2E6U9AA,2E6V0AA |
|                                   | HP Renew Business 14.1 Laptop Bag         | 3E5F9AA         |
|                                   | HP Renew Business 14.1 Laptop Sleeve      | 3E2U7AA         |
|                                   | HP Renew Business 17.3 Laptop Backpack    | 3E2U5AA         |
|                                   | HP Renew Business 17.3 Laptop Bag         | 3E2U6AA         |
| HP Renew Business 15.6 Laptop Bag | 3E5F8AA                                   |                 |
| Docking                           | HP Thunderbolt 120W G2 Dock               | 2UK37AA         |
|                                   | HP Thunderbolt 120W G2 Dock w/Audio       | 3YE87AA         |
|                                   | HP Thunderbolt 230W G2 Dock w/Combo Cable | 3TR87AA         |
|                                   | HP USB-C 120W G5 Dock                     | 5TW10AA         |
|                                   | HP USB-C/A 120W G2 Universal Dock         | 5TW13AA         |
| Hub                               | HP USB-C Mini Dock                        | 1PM64AA         |
|                                   | HP Universal USB-C Multiport Hub          | 50H55AA         |
|                                   | HP USB-C Travel Dock G2                   | 7PJ38AA         |
|                                   | HP USB-C to USB-A Hub                     | Z6A00AA         |
| Adapter                           | HP USB-C to RJ45 Adapter G2               | 4Z527AA         |
|                                   | HP USB 3.0 to Gigabit RJ45 Adapter G2     | 4Z7Z7AA         |
|                                   | HP HDMI to DVI Adapter                    | F5A28AA         |
|                                   | HP HDMI to VGA Adapter                    | H4F02AA         |
|                                   | HP USB to Gigabit RJ45 Adapter            | N7P47AA         |
|                                   | HP USB-C to DisplayPort Adapter           | N9K78AA         |
|                                   | HP USB-C to HDMI 2.0 Adapter              | 1WC36AA         |
|                                   | HP USB-C to RJ45 Adapter                  | V7W66AA         |
|                                   | HP USB-C to USB 3.0 Adapter               | N2Z63AA         |
|                                   | HP USB-C to VGA Adapter                   | N9K76AA         |
| Keyboard/Combo                    | HP 975 USB+BT Dual-Mode Wireless Keyboard | 3Z726AA         |
|                                   | HP 455 Programmable Wireless Keyboard     | 4R177AA         |
|                                   | HP 125 WD USB Keyboard                    | 266C9AA         |
|                                   | HP 320K WD USB Keyboard                   | 9SR37AA         |

### Options and Accessories (Sold separately and availability may vary by country)

|                  |  |         |
|------------------|--|---------|
|                  | HP 655 Wireless Keyboard and Mouse Combo                 | 4R009AA |
|                  | HP 225 Wired Mouse and Keyboard Combo                    | 286J4AA |
|                  | HP 235 Wireless Mouse and Keyboard Combo                 | 1Y4D0AA |
|                  | HP Slim Wireless Keyboard and Mouse                      | T6L04AA |
|                  | HP Wired Desktop 320MK Mouse and Keyboard                | 9SR36AA |
|                  | HP Wireless Rechargeable 950MK Mouse and Keyboard        | 3M165AA |
| <b>Mouse</b>     | HP USB Premium Wireless Mouse                            | 1JR31AA |
|                  | HP 435 Multi-Device Wireless Mouse                       | 3B4Q5AA |
|                  | HP 125 USB-A Wired Mouse                                 | 265A9AA |
|                  | HP 128 USB Laser Wired Mouse                             | 265D9AA |
|                  | HP 320M USB-A Wired Mouse                                | 9VA80AA |
|                  | HP Creator USB-A+Bluetooth 935 Wireless Mouse Black      | 1D0K8AA |
|                  | HP USB-A+Bluetooth Multi-Device 635 Wireless Mouse Black | 1D0K2AA |
|                  | HP USB-A+Bluetooth Travel Bluetooth Mouse                | 6SP30AA |
| <b>Power</b>     | HP 65W USB-C Auto Chevy AC Power Adapter                 | 5TQ76AA |
|                  | HP 45W USB-C G2 Zeus AC Power Adapter                    | 1HE07AA |
|                  | HP 45W USB-C LC Dali AC Power Adapter                    | 1MZ01AA |
|                  | HP 65W USB-C Hades AC Power Adapter                      | 1HE08AA |
|                  | HP 65W USB-C LC AC Power Adapter                         | 1P3K6AA |
|                  | HP 65W USB-C Travel Slim Kermit AC Power Adapter         | 3PN48AA |
| <b>Commodity</b> | HP USB DVD-Writer EXT ODD                                | F2B56AA |
|                  | HP Nano Keyed Cable Lock                                 | 1AJ39AA |
|                  | HP Nano Master Keyed Cable Lock                          | 1AJ40AA |
|                  | HP SureKey Standard/Nano/Wedge Cable Lock                | 6UW42AA |

### Change Log

| <b>Date of change:</b> | <b>Version History:</b> |         | <b>Description of change:</b>                              |
|------------------------|-------------------------|---------|--|
| June 10, 2022          | V1 to V2                | Updated | Function Keys section; added note in Manageability feature |
| September 7, 2022      | V2 to V3                | Removed | Tile App   |
| September 30, 2022     | V3 to V4                | Updated | Product weight section                                     |
| October 19, 2022       | V4 to V5                | Updated | Bluetooth version  |
|                        | V5 to V6                |         |  |
|                        |                         |         |  |
|                        |                         |         |  |

© Copyright 2022 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.