HP Color LaserJet Enterprise CP5520 Printer series



Ideal for workgroup or fleet printing in managed enterprise, public sector or medium-sized businesses, wanting an easy-to-use, colour printer with superior paper capacity, that can handle general office documents and wide-format output.





HP Color LaserJet Enterprise CP5525n Printer



HP Color LaserJet Enterprise CP5525dn Printer



HP Color LaserJet Enterprise CP5525xh Printer

Enable colour printing from postcards to posters.

- Expand your business options: print presentations, high-impact reports and marketing materials on a wide range of media types and sizes, from postcard to SRA3.
- Produce high-volume print jobs without frequent paper changes, with a paper capacity up to 2,350 sheets 1
- Improve efficiency: HP Advanced Auto Media Sensing automatically adjusts settings according to paper type and size, for best printing results.
- Increase productivity and versatility with automatic two-sided printing².

Achieve great colour prints with uncompromised speed.

- Save time with fast printing: documents are printed at up to 30 ppm A4.
- Get a first page out in 10 seconds from ready mode and in 16 seconds from power save mode with no-wait Instant-on Technology.
- Enjoy consistent print quality: get accurate high-quality, glossy text, graphics, and images automatically with HP EasyColor and HP ImageREt.
- Use Original HP LaserJet print cartridges with HP ColorSphere toner to achieve sharp contrast, precise drawings and vibrant images from a broad colour qamut.

Count on a printer that is easy to use and manage.

- Print from anywhere, anytime, with a smartphone, notebook PC or other mobile device, using HP ePrint³.
- Expand your security options and easily integrate enterprise-ready gigabit networking into your printing fleet.
- Supervise printing fleets remotely using HP Web Jetadmin and control colour printing usage and costs with HP Color Access Controls.
- Print quickly and easily just plug a Flash drive into the USB port and print. Keep sensitive data safe with HP High-Performance Secure Hard Disk⁴.

ECOHIGHLIGHTS

- Reduce energy use by up to 50% with Instant-on Technology ¹. Avoid reprints with the consistency of Original HP toners plus HP Professional Color Technologies.
- Reduce paper use by up to 50% using automatic two-sided printing2 Convenient cartridge recycling in 53 countries.

FNFRGY STAR® Qualified

(m)

- ¹ Optional 500-sheet paper tray is available and sold separately for the n and dn models.
- $2\ _{\rm Automatic two-sided}$ printing is available on the dn and xh model only.
- 3 Available as of Spring 2011. May require an Internet connection to the printer. Feature works with any Internet and e-mail-capable device and may require a firmware uparade. For details, www.hp.com/ao/ePrintCenter
- 4 Optional HP High-Performance Secure Hard Disk is available and sold separately for the n and dn models.

Product walkaround

- HP Color LaserJet Enterprise CP5520 Printer series 1 Intuitive control panel with 4 line color display
- I Infutive control panel with 4 line co
- 2 300-sheet top output bin
- 3 One-door access to the easy to install print cartridges 4 100-sheet multipurpose tray recognizes paper sizes up to
- SRA3
- 5 250-sheet tray 2
- 6 500-sheet tray 3
- 7 Three 500-sheet input trays with print stand for 2,350-sheet total input capacity
- 8 USB 2.0 port for walk up printing
- 9 Built-in automatic two-sided printing
- 10 Hi-Speed USB 2.0 port for direct connection to printer
- 11 HP Jetdirect Gigabit Ethernet embedded print server
- 12 1 GB RAM and an 800 MHz processor
- 13 120 GB HP Encrypted High Performance Hard Disk
- 14 One open EIO slot



Series at a glance



- HP Color LaserJet Enterprise CP5525n Printer
- HP Color LaserJet Enterprise CP5525n Printer: print speed of up to 30 ppm colour and 30 ppm black
- up to 600 x 600 dpi effective output quality with HP ImageREt 3600
- 1 GB RAM
- 800 MHz processor
- 1 Hi-Speed USB 2.0 port
- 1 USB 2.0 port for walk up printing
- 8 GB HP High-Performance Secure Hard Disk
- HP Jetdirect Gigabit Ethernet embedded print server
- 100-sheet multipurpose tray
- 250-sheet input tray 2
- 500-sheet input tray 3



 HP Color LaserJet Enterprise CP5525dn Printer
HP Color LaserJet Enterprise CP5525dn Printer: as CP5525n model plus automatic two-sided printing.



- HP Color LaserJet Enterprise CP5525xh Printer
- HP Color LaserJet Enterprise CP5525xh Printer: as CP5525n model plus
- two-sided printing
- additional 3 x 500-sheet input trays 4 and 5 and 6
- 120 GB HP High-Performance Secure Hard Disk

Recommended accessories



CE860A HP Color LaserJet 500-sheet Paper Tray

Enhance productivity with a simple-to-install paper tray that allows you to print more pages without reloading paper and keep two different types of paper loaded.

J8019A HP Secure High Performance EIO Hard Disk Securing your business means protecting information. With the HP High-Performance Secure EIO Hard Disk with a Kensington-style lock, you can easily help secure valuable data at rest on your HP printer or MFP and still achieve optimal performance.



J8021A HP Jetdirect ew2500 802.11b/g Wireless Print Server

Get the best of both worlds — share HP printers and multifunction products via wireless or wired networks. Send and print documents protected by IPSec, 802.11x and several encryption options. Enjoy easy installation, set up and management.

HP Jetdirect 620n Fast

With advanced security and

. Jetdirect 620n Fast Ethernet

Internal Print Server enables

printers with EIO slots, easily

and affordably across the

network and the Internet.

Ethernet Print Server

performance, the HP

businesses to share HP

industry-leading

17934G



J7961G HP Jetdirect 635n IPv6/IPsec Print Server

Share supported peripherals over your network with one of the first Gigabit EIO print servers to support IPv6, IPv4 and IPsec. Rely on advanced network technology and security, and get data transmission at Gigabit speeds (up to 1000 Mbit per second).



J8007G HP Jetdirect 690n IPv6/IPSec 802.11g Wireless Print Server

The HP Jetdirect 690n Wireless 802.11g Print Server provides both wireless or wired connectivity. Get advanced authentication and encryption through IPsec. Enjoy broad compatibility, robust security and easy management in the IT environment.

Ordering information



HP Color LaserJet Enterprise CP5525n Printer (CE707A) HP Color LaserJet CP5525n printer; Print cartridges (1 each black, cyan, magenta, yellow); HP Color LaserJet 250-sheet Paper Tray 2; HP Color LaserJet 500-sheet Paper Tray 3; CDs containing device software and electronic User's Guide; Documentation (including Getting Started Guides); power cord



HP Color LaserJet Enterprise CP5525dn Printer (CE708A) HP Color LaserJet CP5525dn printer; Print cartridges (1 each black, cyan, magenta, yellow); HP Color LaserJet 250-sheet Paper Tray 2; HP Color LaserJet 500-sheet Paper Tray 3; CDs containing device software and electronic User's Guide; Documentation (including Getting Started Guides); power cord



HP Color LaserJet Enterprise CP5525xh Printer (CE709A) HP Color LaserJet CP5525xh printer, Print cartridges (1 each black, cyan, magenta, yellow); HP Color LaserJet 250-sheet Paper Tray 2; HP Color LaserJet 500-sheet Paper Tray 3; HP Color LaserJet 3 x 500-sheet Paper Feeder and Stand ; 120 GB secure hard disk drive; CDs containing device software and electronic User's Guide; Documentation (including Getting Started Guides); power cord

Accessories, Supplies and Support

Accessori	es
CE860A	HP Color LaserJet 500-sheet Paper Tray
J8019A	HP Secure High Performance EIO Hard Disk
Supplies	
CE270A	HP Color LaserJet CE270A Black Print Cartridge
	Average continuous Black Cartridge yield 13,500
	standard pages. Declared yield value in accordance
	with ISO/IEC 19798 in continuous printing.
CE271A	HP Color LaserJet CE271A Cyan Print Cartridge
	Average continuous composite Cyan/Yellow/Magenta
	Cartridge yield 15,000 standard pages. Declared yield
	value in accordance with ISO/IEC 19798 in continuous
	printing.
CE272A	HP Color LaserJet CE272A Yellow Print Cartridge
	Average continuous composite Cyan/Yellow/Magenta
	Cartridge yield 15,000 standard pages. Declared yield
	value in accordance with ISO/IEC 19798 in continuous
	printing.
CE273A	HP Color LaserJet CE273A Magenta Print Cartridge
	Average continuous composite Cyan/Yellow/Magenta Cartridge yield 15,000 standard pages. Declared yield
	value in accordance with ISO/IEC 19798 in continuous
	printing.
CE980A	HP Color Laserlet CE980A Toner Collection Unit
CEYOUA	Up to 150,000 pages
CF977A	HP Color Laserlet CE977A 110V Fuser Kit
CE9//A	Up to 150,000 pages
CF978A	1 10
CEA18U	HP Color LaserJet CE978A 220V Fuser Kit
	Up to 150,000 pages

CE979A	HP Color LaserJet CE979A Transfer Kit
	Up to 150,000 pages
Connectiv	vity
J8021A	HP Jetdirect ew2500 802.11b/g Wireless Print Server
J7934G	HP Jetdirect 620n Fast Ethernet Print Server
J7961G	HP Jetdirect 635n IPv6/IPsec Print Server
J8007G	HP Jetdirect 690n IPv6/IPSec 802.11g Wireless Print Server
Service &	support
UV276E HI	P Care Pack, 4 Hour Response Time 13x5 Color LaserJet
Enterprise	CP5520 Printer Hardware Support, 3 years
UX964E H	P Care Pack, Next Business Day Color LaserJet Enterprise
CP5520 Pr	rinter Hardware Support, 3 years
	P Care Pack, Next Business Day Color LaserJet Enterprise rinter Hardware Support, 4 years
	P Care Pack, Next Business Day Color LaserJet Enterprise
	MFP Hardware Support, 5 years
	IP Care Pack, Post Warranty Next Business Day Color
	terprise CP5520 Printer Hardware Support, 1 year
UV268PE	HP Care Pack, Post Warranty Next Business Day Color
	terprise CP5520 Printer Hardware Support, 2 years
UV271PE	HP Care Pack, Post Warranty 4 Hour Response Time
12.5 Cala	r Lasselat Enternaise CP5520 Printer Hardware Support

13x5 Color LaserJet Enterprise CP5520 Printer Hardware Support, 1 year. For a complete list of supplies, accessories and services, please

refer to http://www.hp.com

Count on dependable support to create the best image possible. We can help you enhance your printing and imaging environment, protect your IT investment, and grow your business—with expert support that's affordable, personal, and tailored to your needs through HP Care Pack Services.



Print technology	Laser							
Print speed	First page out Black: As fast as 10 sec, Colour: As fast as 10 sec							
······································	A4 Black: Up to 30 ppm, Colour: Up to 30 ppm							
	Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the							
	system configuration, software application, driver, and document complexity.							
rocessor	800 MHz, Intel® X86-VR							
1emory	1 GB, Not expandable, Hard disk capacity: None							
rint resolution	Black: Up to 600 x 600 dpi							
	Colour: Up to 600 x 600 dpi							
rint quality	HP ImageREt 3600							
rinter languages	HP PCL 6, HP PCL 5c (HP PCL 5c driver available from the Web only), HP Postscript level 3 emulation, native PDF printing (v1.4)							
ypefaces/fonts	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript Level 3 emulation (Euro symbol built-in); additional font solutions available via third-pai							
	flash memory cards							
uty cycle (monthly, A4)	Up to 120 000 pages							
ecommended Monthly Page Volume	2500 to 10,000							
rint margins	top: 5 mm, left: 5 n	nm, right: 5 mm, bottom: 5 mm						
Aedia handling	Input	Capacity	Weight	Size				
5	Tray 1	sheets: 100; transparencies: 50; envelopes: 10	60 to 220 g/m ²	A3; A4; A5; B4 (JIS); B5; B5 (JIS); C5; DL; SRA				
	Tray 2	sheets: 250; transparencies: 50	60 to 120 g/m ² plain papers, up to 160 g/m ²	A3; A4; A5; B4 (JIS); B5; B5 (JIS); C5; DL				
			coated papers					
	Tray 3	sheets: 500	60 to 120 g/m ² plain papers, up to 160 g/m ²	A3; A4; A5; B4 (JIS); B5; B5 (JIS); C5; DL				
			coated papers					
	Duplex printing:	CP5525n: Manual (driver support provided);	60 to 120 g/m ² plain papers, up to 160 g/m ²	A3; A4; B4; B5 (JIS); SRA3				
		CP5525dn: Automatic (standard); CP5525xh:	coated papers					
	Outroute	Automatic (standard)	nuelenen Transportensien Un to 200 shoots					
- Bartan	Output:	Sheets: Up to 300 sheets. Envelopes: Up to 40 er		de combre de transmission des				
Nedia types		glossy, heavy, heavy glossy, high gloss images, inter		eis, carastock, transparencies				
nterface and connectivity		hernet, Gigabit Ethernet, IPv6, BiDi, Hi-Speed USB 2.						
Operating systems compatibility		it and 64-bit; Windows Vista® 32-bit and 64-bit; Mic						
)3 32-bit and 64-bit, Citrix® and Windows® Termino		go/upd, Documentation tab); Novell® (see				
	http://www.novell.com/iprint); Mac OS X v10.4 or higher; Linux (see http://www.hplip.net); UNIX, SAP device types							
			Optional: Latest drivers for all supported operating systems available at http://www.hp.com/support/cljcp5525. If no access to the Internet, see support flyer that came in printe					
	Optional: Latest dri	vers tor all supported operating systems available at		, 11 , 1				
letwork operating systems compatibility	Optional: Latest dri box		rocoft® Windowe® XP 32-bit or 64-bit (SP2 or bigh					
Network operating systems compatibility	Optional: Latest dri box Windows® 7 32-bi	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mic		er), Server 2008 32-bit and 64-bit, and 2008 R2				
Network operating systems compatibility	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33 32-bit and 64-bit, Citrix® and Windows® Terminc	Il Services (see whitepapers at http://www.hp.com/	er), Server 2008 32-bit and 64-bit, and 2008 R2				
	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell.	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33 32-bit and 64-bit, Citrix® and Windows® Terminc com/iprint); Mac OS X v10.4 or higher; Linux (see h	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types	er), Server 2008 32 bit and 64 bit, and 2008 R2 go/upd, Documentation tab); Novell® (see				
	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33 32-bit and 64-bit, Citrix® and Windows® Terminc .com/iprint); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high	Il Services (see whitepapers at http://www.hp.com/ tttp://www.hplip.net); UNIX, SAP device types er, Server 2003, Server 2008; OS Compatible hard	er), Server 2008 32:bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see				
	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.micros	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mid 332-bit and 64-bit, Citrix® and Windows® Terminc com/iprint); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard	Il Services (see whitepapers at http://www.hp.com/ tttp://www.hplip.net); UNIX, SAP device types er, Server 2003, Server 2008; OS Compatible hard	er), Server 2008 32:bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see				
linimum system requirements	Optional: Latest dri box Windows® 7 32.bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.micros http://www.apple.	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33 32-bit and 64-bit; Citrix® and Windows® Termino com/iprint); Mac OS X v10.4 or higher; Linux (see h idows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types ter, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating	er), Server 2008 32:bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see				
1inimum system requirements oftware	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.micros http://www.apple. Print drivers and ins	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33 32-bit and 64-bit; Citrix® and Windows® Termine com/iprint); Mac OS X v10.4 or higher; Linux (see h idows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (Hf	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types ter, Server 2003, Server 2008; OS Compatible hard I disk space, Mac OS X v10.4 or higher; Operating P PCL 6 discrete), SNP alerts, Mac print driver	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements,				
1inimum system requirements oftware	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.apple. Print drivers and ins 5.2 cm, 4-line colo	tand 64-bit; Windows Vista® 32-bit and 64-bit; Mit 3 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HT ur, graphical and text, LCD control panel display; 7 j	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types er, Server 2003, Server 2008; OS Compatible hard I disk space, Mac OS X v10.4 or higher; Operating P PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements,				
Ninimum system requirements oftware iontrol panel	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.micros http://www.apple. Print drivers and ins 5.2 cm, 4-line colo (Attention, Data, Re	it and 64-bit; Windows Vista® 32-bit and 64-bit; Min 3 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (Hf ur, graphical and text, LCD control panel display; 7 j eady); Enhanced help with animated graphics; Walk-	Il Services (see whitepapers at http://www.hp.com/ tttp://www.hplip.net); UNIX, SAP device types erer, Server 2003, Server 2008; OS Compatible hard I disk space, Mac OS X v10.4 or higher; Operating P PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements,				
Ainimum system requirements Software Control panel rinter management	Optional: Latest dri box Windows® 7 32-bi Edition, Server 2006 http://www.novell. Windows® 7; Win http://www.micros http://www.micros http://www.apple. Print drivers and ins 5.2 cm, 4-line colo (Attention, Data, Re HP Web Jetadmin;	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mindows Vista® 32-bit and 64-bit, Citrix® and Windows® Termino. com/iprint); Mac OS X v10.4 or higher; Linux (see h idows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (Hf ur, graphical and text, LCD control panel display; 7 j ady); Enhanced help with animated graphics; Walk- Status Notification Pop-up (SNP) for domains less tha	Il Services (see whitepapers at http://www.hp.com/ http://www.hplip.net); UNIX, SAP device types ler, Server 2003, Server 2008; OS Compatible hard I disk space, Mac OS X v10.4 or higher; Operating PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover in 100 users	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights				
Network operating systems compatibility Ainimum system requirements Software Control panel Printer management Power	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.apple. Print drivers and ins 5.2 cm, 4-line colo (Attention, Data, Re HP Web Jetadmin; Requirements: Inpu;	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mid 03 32-bit and 64-bit, Citrix® and Windows® Termino com/iprint); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF ur, graphical and text, ICD control panel display; 7 ji addy); Enhanced help with animated graphics; Walk Status Notification Pop-up (SNP) for domains less that tvoltage: 220 to 240 VAC (- 10/+ 6%), 50/60 Hz (Il Services (see whitepapers at http://www.hp.com/ http://www.hplip.net); UNIX, SAP device types ler, Server 2003, Server 2008; OS Compatible hard I disk space, Mac OS X v10.4 or higher; Operating PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover in 100 users	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights				
Ainimum system requirements ioftware Control panel trinter management ower	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.micros http://www.apple. Print drivers and ins 5.2 cm, 4-line colo (Attention, Data, Re HP Web Jetadmin; Requirements: Input Typical electricity co	it and 64-bit; Windows Visto® 32-bit and 64-bit; Mic 33 2-bit and 64-bit, Citrix® and Windows® Termino com/iprint); Mac OS X v10.4 or higher; Linux (see h idows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stalllation software on CD: Windows® print driver (HF ur, graphical and text, ICD control panel display; 7 j scady); Enhanced help with animated graphics; Walk- t voltage: 220 to 240 VAC (- 10/+ 6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types ler, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating P PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 wat	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights				
Ainimum system requirements Software Control panel Printer management	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.apple. Print drivers and im 5.2 cm, 4-line colo (Attention, Data, Re HP Web Jetadmin; Requirements: Input Typical electricity co Out of package: Cl	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mit 3 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HT ur, graphical and text, ICD control panel display; 7 j sady); Enhanced help with animated graphics; Walke Status Notification Pop-up (SNP) for domains less that tvoltage: 220 to 240 VAC (+ 10/+ 6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week P5525n: 544 x 586 x 465 mm; CP5525dn: 544 x 5	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types ler, Server 2003, Server 2008; OS Compatible hard I disk space, Mac OS X v10.4 or higher; Operating PPCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover In 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 wat 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights				
Ainimum system requirements oftware Control panel trinter management ower Dimensions (w x d x h)	Optional: Latest dri box Windows® 7 32-bi Edition, Server 2001. http://www.novell. Windows® 7; Win http://www.apple. Print drivers and ins 5.2 cm, 4-line colo (Attention, Data, Re HP Web Jetadmin; Requirements: Inpui Typical electricity co Out of package: CP5525	it and 64-bit; Windows Vista® 32-bit and 64-bit; Min 33 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X 10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (Hf ur, graphical and text, LCD control panel display; 7 j sady); Enhanced help with animated graphics; Walk- Status Notification Pop-up (SNP) for domains less that t voltage: 220 to 240 VAC (+ 10/+ 6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week P5525n: 544 x 586 x 465 mm; CP5525dn: 544 x 55 in: 995 x 767 x 822 mm; CP5525dn: 995 x 767 x 8	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types ler, Server 2003, Server 2008; OS Compatible hard I disk space, Mac OS X v10.4 or higher; Operating PPCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 wat 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights				
Ainimum system requirements oftware Control panel trinter management ower Dimensions (w x d x h)	Optional: Latest dri box Windows® 7 32-bi Edition, Server 2001. http://www.novell. Windows® 7; Win http://www.apple. Print drivers and ins 5.2 cm, 4-line colo (Attention, Data, Re HP Web Jetadmin; Requirements: Input Typical electricity or Out of package: CP5525 Out of package: CD	it and 64-bit; Windows Vista® 32-bit and 64-bit; Min 33 2-bit and 64-bit, Citrix® and Windows® Termino com/iprint); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (Hf ur, graphical and text, LCD control panel display; 7 j ady); Enhanced help with animated graphics; Walk Status Notification Pop-up (SNP) for domains less that t voltage: 220 to 240 VAC (-10/+ 6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week P5525n: 544 x 586 x 465 mm; CP5525dn: 544 x 58 n: 995 x 767 x 822 mm; CP5525dn: 53.5 kg; CP5525xh: 8	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types ler, Server 2003, Server 2008; OS Compatible hard I disk space, Mac OS X v10.4 or higher; Operating PPCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 wat 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights				
Ainimum system requirements oftware control panel rinter management ower Dimensions (w x d x h) Veight	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.micros http://www.apple. Print drivers and ins 5.2 cm, 4-line colo (Attention, Dato, Re HP Web Jetadmin; Requirements: Inpui Typical electricity cc Out of package: CP 5525 Out of package: CP 5525 Out of package: CP	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mindows Vista® 32-bit and 64-bit, Citrix® and Windows® Termino com/iprint); Mac OS X 10.4 or higher; Linux (see h idows Vista®; Microsoft® Windows® XP SP2 or high off.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (Hf ur, graphical and text, LCD control panel display; 7 i addy); Enhanced help with animated graphics; Walk Status Notification Pop-up (SNP) for domains less that tvoltage: 220 to 240 VAC (-10/+ 6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week P5525n: 544 x 586 x 465 mm; CP5525dn: 544 x 5 in: 995 x 767 x 822 mm; CP5525dn: 53.4 kg; CP5525Ah: 8 in: 85 kg; CP5525dn: 85 kg; CP5525Ah: 168 kg	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types er, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating PPCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 wat 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 14 kg	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights ts (standby), 19.5 watts (sleep), 0.5 watts (manual-				
Ainimum system requirements oftware control panel rinter management ower Dimensions (w x d x h) Veight	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.apple. Print drivers and ins 5.2 cm, 4-line colo (Attention, Data, Re HP Web Jetadmin; Requirements: Input Typical electricity ci Out of package: CC Packaged: CP5525 Out of package: CP	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mit 332-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HI ur, graphical and text, LCD control panel display; 7 j sady); Enhanced help with animated graphics; Walk Status Notification Pop-up (SNP) for domains less that t voltage: 220 to 240 VAC (+ 10/+ 6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week P5525n: 544 x 586 x 465 mm; CP5525dn: 544 x 5 n: 995 x 767 x 822 mm; CP5525dn: 955 x 767 x 8 P5525n: 53.3 kg; CP5525dn: 85 kg; CP5525hx: 168 kg ture: 15 to 27° C. Recommended operating tempera	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types ler, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating P PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 wat 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 14 kg ture: 17 to 25° C. Operating humidity: 10 to 70% R	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights ts (standby), 19.5 watts (sleep), 0.5 watts (manual-				
tinimum system requirements oftware ontrol pane! rinter management ower imensions (w x d x h) Veight Vperating environment	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.apple. Print drivers and im 5.2 cm, 4-line colo (Attention, Data, Re HP Web Jetadmin; Requirements: Input Typical electricity co Out of package: CP Fackaged: CP5525 Out of package: CP Fackaged: CP5525 Operating temperatur	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mit 332-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high- form system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HI w, graphical and text, ICD control panel display; 7 j sady); Enhanced help with animated graphics; Walk- Status Notification Pop-up (SNP) for domains less the t voltage: 220 to 240 VAC (+ 10/+ 6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week P5525n: 53.3 kg; CP5525dn: 53.5 kg; CP5525xh: 8 in: 85 kg; CP5525dn: 85 kg; CP5525xh: 168 kg thre: 15 to 27° C. Recommended operating tempera e: 0 to 35° C. Storage humidity: 10 to 90% RH. Noi	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types ler, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating P PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 wat 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 14 kg ture: 17 to 25° C. Operating humidity: 10 to 70% R	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights ts (standby), 19.5 watts (sleep), 0.5 watts (manual				
tinimum system requirements oftware ontrol pane! rinter management ower imensions (w x d x h) Veight Vperating environment	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200L http://www.novell Windows® 7; Win http://www.apple. Print drivers and ins 5.2 cm, 4-line colo (Attention, Data, Re HP Web Jetadmin; Requirements: Input Typical electricity cr Out of package: CP5525 Out of package: CP5525 Out of package: CP5525 Out of package: CP5525 Operating temperature Storage temperature Acoustic Power Em	it and 64-bit; Windows Vista® 32-bit and 64-bit; Min 33 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X 10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (Hf ur, graphical and text, LCD control panel display; 7 j eady); Enhanced help with animated graphics; Walk- Status Notification Pop-up (SNP) for domains less that t voltage: 220 to 240 VAC (- 10/+ 6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week P5525n: 544 x 586 x 465 mm; CP5525dn: 544 x 5 in: 995 x 767 x 822 mm; CP5525dn: 995 x 767 x 8 P5525n: 53.3 kg; CP5525dn: 53.5 kg; CP5525xh: 168 kg ture: 15 to 27° C. Recommended operating tempera e: 0 to 35° C. Storage humidity: 10 to 90% RH. Noi isisons: 6.6 B(A)	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types ler, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating P PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 wat 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 14 kg ture: 17 to 25° C. Operating humidity: 10 to 70% R	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights ts (standby), 19.5 watts (sleep), 0.5 watts (manual				
Ainimum system requirements oftware control panel trinter management ower Vimensions (w x d x h) Veight Operating environment Acoustics	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.micros http://www.apple. Print drivers and ins 5.2 cm, 4-line colo (Attention, Data, Re HP Web Jetadmin; Requirements: Input Typical electricity ca Out of package: CP Packaged: CP5525 Out of package: CP Packaged: CP5525 Operating temperatur Acoustic Pressure E	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mindows Vista® 32-bit and 64-bit, Citrix® and Windows® Termino com/iprint); Mac OS X v10.4 or higher; Linux (see h idows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (Hf ur, graphical and text, LCD control panel display; 7 j aady); Enhanced help with animoted graphics; Walk Status Notification Pop-up (SNP) for domains less that t voltage: 220 to 240 VAC (·10/+ 6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week P5525n: 544 x 586 x 465 mm; CP5525dn: 544 x 5 n: 995 x 767 x 822 mm; CP5525dn: 5345 x 67 x 8 P5525n: 53.3 kg; CP5525dn: 53.5 kg; CP5525xh: 168 kg ture: 15 to 27° C. Recommended operating tempera e: 0 to 35° C. Storage humidity: 10 to 90% RH. Noi tissions: 6.6 B(A)	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.nel); UNIX, SAP device types ier, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 wat 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 14 kg ture: 17 to 25° C. Operating humidity: 10 to 70% R se level per ISO 9296: Sound power: LwAd6.6 B(A)	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see Aware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights ts (standby), 19.5 watts (sleep), 0.5 watts (manual H. Recommended operating humidity: 30 to 70%				
Ainimum system requirements oftware iontrol panel rinter management ower Verght Operating environment Acoustics	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.micros http://www.apple. Print drivers and ins 5.2 cm, 4-line colo (Attention, Data, Re HP Web Jetadmin; Requirements: Input Typical electricity or Out of package: CD Packaged: CP5525 Out of package: CD Packaged: CP5525 Out of package: CD Packaged: CP5525 Operating temperatur Acoustic Pressure E Safety certifications	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mid 332-bit and 64-bit, Citrix® and Windows® Termino com/iprint); Mac OS X 10.4 or higher; Linux (see h idows Vista®; Microsoft® Windows® PSP2 or high off.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (Hf ur, graphical and text, LCD control panel display; 7 i ady); Enhanced help with animated graphics; Walk- Status Notification Pop-up (SNP) for domains less that tvoltage: 220 to 240 VAC (-10/+ 6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week P5525n: 544 × 586 × 465 mm; CP5525dn: 544 × 5 in: 995 × 767 × 822 mm; CP5525dn: 544 × 5 in: 955 × 767 × 822 mm; CP5525dn: 544 × 5 in: 85 kg; CP5525dn: 85 kg; CP5525xh: 168 kg ture: 15 to 27° C. Recommended operating tempera e: 0 to 35° C. Storage humidity: 10 to 90% RH. Noi isisions: 6.6 B(A) missions: 49 dB(A) :: IEC 60950-1 (International); EN 60950-1+A11 (EL	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types ler, Server 2003, Server 2008; OS Compatible hard I disk space, Mac OS X v10.4 or higher; Operating PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 wat 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 14 kg ture: 17 to 25° C. Operating humidity: 10 to 70% R se level per ISO 9296: Sound power: LwAd6.6 B(A) J); IEC 60825-1+A1+A2; GS License (Europe); EN G	er), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see Aware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights ts (standby), 19.5 watts (sleep), 0.5 watts (manual H. Recommended operating humidity: 30 to 70% (
finimum system requirements oftware control panel rinter management ower bimensions (w x d x h) Veight Departing environment	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.apple. Print drivers and ins 5.2 cm, 4-line colo (Attention, Data, Re HP Web Jetadmin; Requirements: Input Typical electricity ci Out of package: CC Packaged: CP5525 Out of package: CC Packaged: CP5525 Operating temperatur Acoustic Powers and Storage temperatur Acoustic Pressure E Safety certifications	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mit 33 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (Hf ur, graphical and text, ICD control panel display; 7 j sady); Enhanced help with animated graphics; Walk Status Notification Pop-up (SNP) for domains less the t voltage: 220 to 240 VAC (+ 10/+ 6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week P5525n: 53.3 kg; CP5525dn: 544 x 5 in: 995 x 767 x 822 mm; CP5525dn: 995 x 767 x 8 P5525n: 53.3 kg; CP5525dn: 35.5 kg; CP5525xh: 8 in: 85 kg; CP5525dn: 85 kg; CP5525xh: 84 kg thre: 1 5 to 27° C. Recommended operating tempera e: 0 to 35° C. Storage humidity: 10 to 90% RH. Noi issions: 40 dB(A) Einsistons: 49 dB(A) EinStong (Europe); other safety	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types ler, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating P PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 wat 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 14 kg ture: 17 to 25° C. Operating humidity: 10 to 70% R se level per ISO 9296: Sound power: LwAd6.6 B(A) J); IEC 60825-1+A1+A2; GS License (Europe); EN 6 approvals as required by individual countries	ery, Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights ts (standby), 19.5 watts (sleep), 0.5 watts (manual H. Recommended operating humidity: 30 to 70% f 50825-1+A1+A2 (Class 1 Laser/LED Device); Low				
Ainimum system requirements oftware control panel trinter management ower Vimensions (w x d x h) Veight Operating environment Acoustics	Optional: Latest dri box Windows® 7 32-bi Edition, Server 200 http://www.novell. Windows® 7; Win http://www.apple. Print drivers and im 5.2 cm, 4-line colo (Attention, Dato, Re HP Web Jetadmin; Requirements: Input Typical electricity ca Out of package: CP5525 Out of package: CP5525 Out of package: CP5525 Operating temperatur Acoustic Pressure E Safety certifications: Voltage Directive 2 EMC certifications:	it and 64-bit; Windows Vista® 32-bit and 64-bit; Mid 332-bit and 64-bit, Citrix® and Windows® Termino com/iprint); Mac OS X 10.4 or higher; Linux (see h idows Vista®; Microsoft® Windows® PSP2 or high off.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (Hf ur, graphical and text, LCD control panel display; 7 i ady); Enhanced help with animated graphics; Walk- Status Notification Pop-up (SNP) for domains less that tvoltage: 220 to 240 VAC (-10/+ 6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week P5525n: 544 × 586 × 465 mm; CP5525dn: 544 × 5 in: 995 × 767 × 822 mm; CP5525dn: 544 × 5 in: 955 × 767 × 822 mm; CP5525dn: 544 × 5 in: 85 kg; CP5525dn: 85 kg; CP5525xh: 168 kg ture: 15 to 27° C. Recommended operating tempera e: 0 to 35° C. Storage humidity: 10 to 90% RH. Noi isisions: 6.6 B(A) missions: 49 dB(A) :: IEC 60950-1 (International); EN 60950-1+A11 (EL	Il Services (see whitepapers at http://www.hp.com/ ttp://www.hplip.net); UNIX, SAP device types ler, Server 2003, Server 2008; OS Compatible hard I disk space, Mac OS X v10.4 or higher; Operating PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, H up USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 wat 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 14 kg ture: 17 to 25° C. Operating humidity: 10 to 70% R se level per ISO 9296: Sound power: LwAd6.6 B(A) J); IEC 60825-1+A1+A2; GS License (Europe); EN 6 approvals as required by individual countries A, EN 61000-3-2: 2006, EN 61000-3-3: 1995+A1	ery, Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, elp, Up arrow, Down arrow); 3 LED status lights ts (standby), 19.5 watts (sleep), 0.5 watts (manual H. Recommended operating humidity: 30 to 70% 50825-1+A1+A2 (Class 1 Laser/LED Device); Low +A2, EN 55024: 1998+A1+A2, FCC Title 47 Cl				

http://www.hp.com/uk http://www.hp.com/go/cljcp5525





© Copyright 2010 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

