


HP Colorlucent Backlit Film



HP Designjet printing system The complete solution

HP Designjet
printers



HP Designjet
ink supplies

HP large format
printing material

HP Colorlucent Backlit Film

Durable, translucent, front-print film and HP designjet UV inks deliver sharp photo quality to indoor and outdoor lightbox displays.

Target customers

- Design professionals and print-service providers who want to print indoor and outdoor color signage and other graphics on backlit film.

Applications

- Trade Show and Event Displays
- Backlit Displays
- POP and Retail Displays
- Photo Enlargements
- Geographic Information Systems (GIS)

Benefits

- Near Duratrans quality
- Incredibly vibrant
- Industry award winning



Printer/ink compatibility

Printer	Ink	Front panel setting
Designjet 2800cp/2500cp/2000cp	HP CP uv	UV Custom Media B
Designjet 3800cp/3500cp/3000cp	HP CP uv	UV Custom Media B
Designjet 5000/5000ps	HP 83 uv	Studio Canvas
Designjet 5500/5500ps	HP 83 uv	Studio Canvas

For the latest ICC/Media profiles, please visit www.hp.com/go/designjet/supplies/support (click on the ICC profiles and select your printer). For non-Post Script printers see your external RIP Vendor.

Product specifications

Property	Value and test method
Grammage	205 g/m ²
Thickness/caliper	6 mil
Core size	2 in (50.8 mm)
CIE whiteness	80 per CIE Ganz 82 Test Method
Brightness	Not applicable
Opacity	77% per TAPPI T-425 Test Method
Finish	Matte per ASTM D-523 Test Method
Country of Origin	Product of US
Waterfastness	Water resistant

Image permanence

	Dye	Pigment
Fade resistance (indoor)+	Not compatible	5 years (in sealed lightbox)
Fade resistance (commercial window)	Not compatible	Not tested
Fade resistance (outdoor)	Not compatible	Not tested

+ For the 'Indoor' category, test results were achieved under glass unless otherwise indicated.

Operating specifications

Operating temperature	15 to 30 ° C (59 to 86 ° F)
Operating humidity	20 to 70% RH
Dry time	7 minutes (@ 23°C, 50% RH)
Shelf life	1 year, unopened in original packaging

Finishing/post-processing

Lamination Can be laminated with commercially available pressure-sensitive laminate films. Visit HP's lamination partner for more information.

Acid Free

Ordering information

C6778A	36 in x 100 ft (914 mm x 30.5 m)	NA, LAR, JA, AP, EMEA
C6779A	54 in x 100 ft (1372 mm x 30.5 m)	NA, JA, AP, EMEA
C6780A	60 in x 100 ft (1524 mm x 30.5 m)	NA, LAR, JA, AP, EMEA

Warranty Statement

Technical information contained in this document is subject to change without notice. © Copyright 2007 Hewlett-Packard Development Company, L.P. Hewlett-Packard large-format printing materials are guaranteed to meet HP published specifications, to be free of manufacturing flaws and defects, and are designed to resist paper jams when used correctly. If you are not satisfied with this product for any reason, please visit www.hp.com/go/designjet/supplies, and select HP product support center to locate product support in your region.

For information on similar products, please visit HP Designjet Supplies at <http://www.hp.com/go/designjet/supplies>

Last revised: 11/2007

