

HP Color LaserJet CM4730 MFP series



Workgroup performance soars with this fast, compact, award-winning¹ colour MFP. Get reliable print, copy, fax² and send-to functionality at a surprisingly affordable price. Enjoy ease-of-use and access to HP and key partner solutions.

The perfect tool for mid-volume workgroups of 6 to 15 users in both small and medium businesses and enterprise environments, this fast, colour MFP enables them to be more productive with print, copy, send-to functionality, fax (optional), plus HP and key partner solutions close at hand.

Work more effectively with a colour MFP that delivers the functionality you need.

Get more done with a fast first page out, print and copy speeds of up to 30 ppm for colour and black, two-sided printing at full speed, plus colour scanning. Send and receive documents by adding fax functionality with an internal 33.6 kbps analogue fax card³. Facilitate document workflow with embedded send to e-mail functionality, and send to folder and fax with optional HP Digital Sending Software 4⁴. Professional finishing solutions include a stacker/stapler⁵ and 3-bin mailbox⁶.

Keep costs down with an MFP that saves money initially and over time.

Preserve your budget and still get the functionality you need with this surprisingly affordable MFP which also delivers a low cost per colour page. Control costs when you choose Original HP print cartridges, which feature consistent, high-quality performance that saves your business time and money. Get the benefit of colour with no cost penalty: Colour Access Controls let you monitor colour printing by user or even by application, and choose when and how colour is used in your workgroup

Now you can focus on your business with an MFP that is easy to use and easy to manage.

Use, manage and maintain your device with HP's simple, award-winning Easy Select Control Panel. Take advantage of your MFP's features with an intuitive interface that clearly displays all available applications. Enjoy best-in-class networking through the HP Jetdirect Internal Print Server.

Proactively manage your MFP and save valuable IT time with HP Web Jetadmin fleet management software. Original HP Color LaserJet print cartridges with built-in intelligence ensure trouble-free printing.

¹ Buyer's Lab gave HP a "Pick of the Year" award in December 2006 for "Outstanding Achievement for the User Interface Design of its Multifunction Printers"

² Fax available with HP Color LaserJet CM4730f MFP, CM4730fsk MFP, and CM4730fm MFP.

³ Available with HP Color LaserJet CM4730f MFP, CM4730fsk MFP and CM4730fm MFP

⁴ HP Digital Sending Software 4 is not included, sold separately
Software is server based, server required
Trial included

⁵ Available with HP Color LaserJet CM4730fsk MFP only

⁶ Available with HP Color LaserJet CM4730fm MFP only.



HP Color LaserJet
CM4730 MFP



HP Color LaserJet
CM4730f MFP



HP Color LaserJet
CM4730fsk MFP



HP Color LaserJet
CM4730fm MFP

Series at a glance



HP Color LaserJet CM4730 MFP

- Print speed of up to 30 ppm colour and black
- 600 dpi resolution
- Imageret 3600
- 384 MB RAM
- 533 MHz processor
- 40 GB hard drive
- USB and parallel port
- EIO slot
- three Flash memory card slots
- standard input capacity of 1600 sheets from 100-sheet MP tray and three 500-sheet trays
- 50-sheet automatic document feeder
- automatic two-sided printing
- Colour Access Controls



HP Color LaserJet CM4730f MFP

- As base model plus
- 33.6 kbps analogue fax card



HP Color LaserJet CM4730fsk MFP

- As base model plus
- 33.6 kbps analogue fax card
- stapler/stacker unit



HP Color LaserJet CM4730fm MFP

- As base model plus
- 33.6 kbps analogue fax card
- three-bin mailbox (for a total output capacity of 700 pages)

Recommended accessories



Q7722A
HP 256 MB DDR 200-pin SDRAM DIMM



Q3701A
HP LaserJet MFP Analog Fax Accessory 300



Q7521A
HP Color LaserJet 4730mpf Stapler/Stacker



Q7523A
HP Color LaserJet 4730mpf 3-bin Mailbox



T1936AA
HP Digital Sending Software 4



C8091A
HP Staple Cartridge 4

HP Kits



Q5997A
HP LaserJet ADF Maintenance Kit



Q7504A
HP Image Transfer Kit (120,000 pages)



Q7503A
HP 220V Image Fuser Kit (150,000 pages)



J7951G
HP Jetdirect ew2400 802.11g Wireless and Fast Ethernet External Print Server



J7961G
HP Jetdirect 635n IPv6/IPsec Internal Print Server (EIO, 10/100/1000TX)

Operating and warranty specifications

Operating environment	Operating temperature: 15 to 30° C. Recommended operating temperature: 17 to 25° C. Operating humidity: 10 to 80% RH. Operating humidity recommended: 30 to 70% RH. Storage temperature: -20 to 40° C. Storage humidity: 10 to 90% RH. Noise level per ISO 9296: sound power: LwAd 6.7 B(A) (active, printing); 6.3 B(A) (active, copy or scan); inaudible (ready). Sound pressure: LpAm 50 dB(A) (active, printing); 52 dB(A) (active, copy or scan); inaudible (ready)
Certifications	CISPR 22:2005 / EN 55022:2006 Class A, EN 61000-3-2:2000, EN 61000-3-3:1995, EN 55024:1998, FCC Title 47 CFR, Part 15 Class A / ICES-003, Issue 4 / GB9254-1998, GB17625.1-2003, EMC Directive 89/336/EEC and the Low Voltage Directive 73/23/EEC and carries the CE-Marking accordingly. Regulatory standards: Czech Republic (CSN-IEC 60950-1; IEC 60825-1), Estonia (EEI-EN60950-1; IEC 60825-1), EU (CE Mark-Low Voltage Directive 73/23/EEC), Germany (TUV- EN60950-1; IEC 60825-1), Hungary (MEEI- IEC 60950-1; IEC 60825-1), Lithuania (LS- IEC 60950-1; IEC 60825-1), (Russia (GOST- R50377), Slovakia (IEC 60950-1; IEC60825-1), Slovenia (SQI- IEC 60950-1; EN60825-1), South Africa (IEC 60950-1; IEC60825-1).. ENERGY STAR: Yes
Warranty	One-year warranty

Ordering information



HP Color LaserJet CM4730 MFP (CB480A)
HP Color LaserJet CM4730 MFP, power cord, control panel overlay, four print cartridges (one each: black, cyan, magenta, yellow), software drivers and documentation on CD-ROM, information and training CD, in-box documentation (getting started guide, walk up wall poster, telephone support flyer)



HP Color LaserJet CM4730f MFP (CB481A)
As CM4730 MFP plus analogue fax accessory, and fax install guide



HP Color LaserJet CM4730fsk MFP (CB482A)
As CM4730 MFP plus analogue fax accessory, fax install guide and stapler/stacker unit



HP Color LaserJet CM4730fm MFP (CB483A)
As CM4730 MFP plus analogue fax accessory, fax install guide and three-bin mailbox

Accessories, Supplies and Support

Accessories

Q7722A	HP 256 MB DDR 200-pin SDRAM DIMM
Q3701A	HP LaserJet MFP Analog Fax Accessory 300
Q7521A	HP Color LaserJet 4730mfp Stapler/Stacker
Q7523A	HP Color LaserJet 4730mfp 3-bin Mailbox
T1936AA	HP Digital Sending Software 4
C8091A	HP Staple Cartridge
Q5997A	HP LaserJet ADF Maintenance Kit
Q7504A	HP Image Transfer Kit (120,000 pages)
Q7503A	HP 220V Image Fuser Kit (150,000 pages)

Supplies

Q6460A	HP Color LaserJet Q6460A Black Print Cartridge with ColorSphere Toner Approx. 12,000 pages at 5% coverage
Q6461A	HP Color LaserJet Q6461A Cyan Print Cartridge with ColorSphere Toner Approx. 12,000 pages at 5% coverage
Q6462A	HP Color LaserJet Q6462A Yellow Print Cartridge with ColorSphere Toner Approx. 12,000 pages at 5% coverage
Q6463A	HP Color LaserJet Q6463A Magenta Print Cartridge with ColorSphere Toner Approx. 12,000 pages at 5% coverage

Connectivity

J7951G	HP Jetdirect ew2400 802.11g Wireless and Fast Ethernet External Print Server
---------------	--

J7961G	HP Jetdirect 635n IPv6/IPsec Internal Print Server (EIO, 10/100/1000TX)
---------------	---

Service & support

HC119A/E	HP Care Pack, 4-Hour, 13x5 Onsite, Hardware Support, 3 years
HC113A/E	HP Care Pack, Next Business Day Onsite, Hardware Support, 3 years
HC115A/E	HP Care Pack, Next Business Day Onsite, Hardware Support, 5 years
HC114A/E	HP Care Pack, Next Business Day Onsite, Hardware Support, 4 years
UC755PA/PE	HP Care Pack, Post Warranty Service, Next Business Day Onsite, Hardware Support, 1 year
UC757PA/PE	HP Care Pack, Post Warranty Service, 4-Hour, 13x5 Onsite, Hardware Support, 1 year
U2010A/E	HP Care Pack, Installation for 1 Network Configuration for Dept and Color LaserJet printer

For a complete list of supplies, accessories and services, please refer to <http://www.hp.com>

Technical specifications

Print technology	Laser		
Print speed	A4: Up to 30 ppm. First page out black: < 11 sec (from ready) Colour: < 11 sec (from ready). Warm-up time: less than < 165 sec Exact speed varies depending on the system configuration, software program and document complexity.		
Processor	533 MHz. RISC		
Memory	448 MB: 384 MB RAM and 64 MB fixed memory. Expandable to 512 MB RAM, 2 available Flash memory slots for font cards or third-party solutions. Hard Disk Capacity: Standard, 40 GB		
Print	Quality	HP ImageREt 3600	
	Resolution	Up to 600 x 600 dpi	
	Printer languages	HP PCL 6, HP PCL 5c, HP Postscript level 3 emulation, direct PDF printing (v 1.4), PML (Printer Management Language)	
	Economical printing	Economode, immediate return to Powersave mode after each print job due to Instant-on fuser technology (saves electricity). Standard automatic two-sided printing and N-up printing (saves paper)	
	Typefaces/fonts	80 internal TrueType fonts scalable in HP PCL and HP Postscript Level 3 emulation; additional font solutions available via Flash memory	
	Duty cycle (pages per month)	Up to 175000	
	Print margins (mm)	Top: 4.2 mm. Left: 4.2 mm. Right: 4.2 mm. Bottom: 4.2 mm	
Fax	Modem speed	Up to 33.6 kbps	
	Telecom compliance	Telecom: TBR-21:1998; EG 201 121:1998, FCC Part 68; CIT certificate per TBR-21 (Croatia); Spec. for Terminal Equipment No. 023/96 (Israel); MoC Tec. Requirements plus GOST Telecom series (Russia); TE001, 003, 006 (South Africa)	
	Fax resolution	Standard: 200 x 100 dpi. Superfine: 300 x 300 dpi. Photo: 300 x 300 dpi	
Digital sending	File formats	PDF, JPEG, TIFF, MTIFF	
	Installation	Fast Ethernet (standard), Gigabit (optional), 802.11g wireless (optional), Bluetooth wireless (optional)	
Scan	Type	Flatbed, ADF. Colour scanning: Yes	
	Scan resolution	Optical: Up to 600 dpi. Enhanced: Up to 600 dpi	
	Grey scale levels	256	
	Scannable area	Minimum media size: 14.8 x 12.7 cm (from ADF). Maximum media size: 12.7 x 14.8 cm (Letter size via the glass), 21.6 x 29.7 cm (Legal size via the ADF)	
	Margins for scanned items	Left: 4.2. Top: 4.2. Right: 4.2. Bottom: 4.2	
Copy	Copy speed	Up to 30 cpm	
	Copy resolution	600 x 600 dpi	
	Multiple copies	Up to 999 copies	
	Reduce/enlarge	25 to 400%, 25 to 200% (ADF)	
Media handling	Input:	Capacity	Weight
	Tray 1	Sheets: 100, envelopes: 20, transparencies: 10 mm stack	60 to 220 g/m ²
	Tray 2	Sheets: 500, transparencies: 56 mm stack	60 to 120 g/m ²
	Tray 3	Sheets: 500, transparencies: 56 mm stack	60 to 120 g/m ²
	ADF	Sheets: 50	60 to 120 g/m ²
	Output:	Sheets: Up to 500. Envelopes: Up to 20	
	Duplex printing: Automatic (standard)		
Media types	Paper (plain, preprinted, letterhead, prepunched, bond, recycled, colour, light, intermediate, heavy, extra heavy, rough, glossy, heavy glossy, tough), transparencies, labels, envelopes, card stock		
Interface and connectivity	Bidirectional IEEE-1284C parallel port, Hi-Speed USB port (compatible with USB 2.0 specifications), HP Jetdirect Fast Ethernet Embedded Print Server, 1 open EIO slot, foreign interface harness, host USB accessory port. Optional: HP Jetdirect internal and external print servers, HP wireless print servers, Bluetooth wireless printer adapter		
Operating systems compatibility	Windows® 98, 2000, Me, XP Home, XP Professional, Server 2003; Mac OS 9.x and higher; Mac OS X 10.1 or higher, OS/2, UNIX, Linux, HP OpenVMS. Recent printer drivers and software for all supported operating systems are available at http://www.hp.com/support/ljcm4730mpf . If no access to the Internet, see the support flyer that came in the box with the MFP. Optional: Windows® 2003 and Windows® XP Home and XP Professional; IPsec on IPv4 only on Windows® 2003 and Windows®. Recent printer drivers and software for all supported operating systems are available at http://www.hp.com/support/ljcm4730mpf .		
Network operating systems compatibility	Microsoft® Windows Vista™ Compatible, Windows Vista™ Premium, XP, Server 2003, XP, 2003 64-bit, XP 64-bit, 2000 (IPv6 only supported on Windows® 2003 and Windows® XP; IPsec on IPv4 only on Windows® 2003 and Windows® XP); Novell 5.1 and later; Apple Mac OS 9.x, OS X 10.2 and later; RED HAT Linux 7.x and later; SUSE Linux 8.x and later; HP-UX 10.20, 11.x, 11.i; Solaris® 2.5 and later (SPARC® systems only); IBM® AIX 3.2.5 and later 1; MPE-iX; Citrix® MetaFrame Server; Windows® Terminal Services. Optional: Windows® 2000, Windows® Server 2003 x86, XP x86, Windows Vista™ x86, Vista x64, Windows® Server 2003 x64, XP x64; Mac OS 10.2 and higher		
Minimum system requirements	Pentium® 90, 16 MB RAM (Windows 98); 133 MHz processor, 64 MB RAM (Windows® 2000); 233 MHz processor, 64 MB RAM (Windows® XP Home, XP Professional); Pentium® 150, 32 MB RAM (Windows® Me); 550 MHz processor, 128 MB RAM (Windows® Server 2003); 220 MB of free hard disk space for Windows®, CD-ROM drive or Internet connection, IEEE 1284-compliant bidirectional parallel port, USB 1.1 port, USB port (compatible with USB 2.0 specifications). Mac OS 9.x, Mac OS X v 10.1 or higher, 160 MB available hard disk space, CD-ROM drive, USB port		
Standard software	Windows® Installer for 2000 and up x86 and x64; Mac Installer for OS 10.2 and higher. Drivers on the web: Printing system; PCL 6 driver only, PCL 5 driver only, Postscript driver only; WJA applet; UPD PCL 6; UPD PCL 5, UPD Postscript; Easy printer care; PC Fax Driver		
Control panel	Touch screen graphical display, job control buttons, numeric keypad, LED status lights		
Power	Requirements: Input voltage 100 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); Input voltage 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz)		
Dimensions (w x d x h)	Out of package: CM4730: 788 x 639 x 1153 mm; CM4730f: 788 x 639 x 1153 mm; CM4730fsk: 1106 x 639 x 1153 mm; CM4730fm: 1106 x 639 x 1153 mm. Packaged: CM4730: 900 x 815 x 1518 mm; CM4730f: 900 x 815 x 1518 mm; CM4730fsk: 900 x 815 x 1636 mm; CM4730fm: 900 x 815 x 1636 mm		
Weight	Out of package: CM4730: 124 kg; CM4730f: 124 kg; CM4730fsk: 136 kg; CM4730fm: 136 kg. Packaged: CM4730: 154.2 kg; CM4730f: 154.2 kg; CM4730fsk: 169.43 kg; CM4730fm: 169.43 kg		
Printer management	HP Embedded Web Server, HP Web Jetadmin, HP Easy Printer Care Software (Web only), HP LaserJet Utility, HP Universal Print Driver		

<http://www.hp.com/uk>



© Copyright Hewlett-Packard Development Company, L.P. 2007. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 05/07 4AA0-9482EEE

