



HP Self-adhesive Gloss Polypropylene produces glossy prints with excellent colour vibrancy for brilliant images. Tear-resistant and easy to handle, its strong adhesive ensures secure, reliable mounting.

Designed for commercial Print Service Providers, especially Quick Printers and Copy Shops, looking for an affordable type of polypropylene self-adhesive media.

This self-adhesive polypropylene film produces prints with excellent colour vibrancy for brilliant, photo-realistic images. The engineered glossy coating of this media helps ensure excellent ink-media interaction and the optimum dot gain.

Polypropylene material features a permanent self adhesive to ensure secure, reliable mounting. It resists peeling and offers long-term quality and superb tear-resistance.

This versatile film is perfect for indoor and outdoor applications. Get excellent fade resistance¹ when used with Original HP pigment inks. Lamination is required with Original HP pigment and dye inks for water resistance.

¹ Display permanence and water resistant ratings by HP Image Permanence Lab, using HP 83 inks and HP 91 Viverra pigment inks
For details, visit: www.hp.com/go/printpermanence

HP Self-adhesive Gloss Polypropylene 180 g/m²

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Weight	180 g/m ² per ISO 536 Test Method (with liner)		
Thickness	5.5 mil/140 microns per ISO 534 Test Method (without liner), 7.8 mil/198 microns (with liner and glue)		
Opacity	Greater than 95% CIE per TAPPI T-425 Test Method		
Brightness	Greater than 97% per TAPPI T-452 Test Method (with liner)		
Whiteness	Greater than or equal to 120 per CIE Ganz 82 Test Method (with liner)		
Lamination	Yes, cold		
Finish	Gloss		
Adhesive backing	Permanent		
Operating temperature	15 to 30° C		
Operating humidity	20 to 70 % RH		
Dry time	3 minutes (@ 23°C, 50% RH)		
Shelf time	1 year, unopened in original packaging		
Storage temperature	5 to 40° C		
Storage humidity	20 to 70 % RH		
Country of origin	Product of China		
Ordering information	Product Numbers	Roll sizes	UPC codes
	Q8834A	914 mm x 22.9 m	882780992931
	Q8835A	1067 mm x 22.9 m	882780992948
Warranty	HP large format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the users are unsatisfied with HP large format printing material they should contact their HP reseller.		

© 2007 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit
<http://www.hp.com/go/designjet/supplies>

Published in EMEA 4AA0-6784 EEE

